Polycom SoundStation IP 3000

Polycom's first Voice over IP (VoIP) conference phone



Polycom Soundstation IP 3000 Highlights

Acoustic Clarity Technology – Allows simultaneous natural conversation – the industry's best full duplex

Platform independence – Supports multiple protocols and platforms

Investment protection – Downloadable upgrades as standards develop and protocols evolve

360-degree room coverage – A powerful, digitally-tuned custom speaker and three sensitive microphones provide uniform coverage of a small to medium-sized conference room or office

Easy-to-install and use – Easily configures with your iPBX or Softswitch. Standard keypad with softkeys and graphical LCD display With the SoundStation IP 3000, the promise of single-network communications is now a reality in the conference room. The SoundStation IP 3000 is designed to accommodate leading VoIP protocols for the converged enterprise network.

Whether you are conferencing with colleagues down the block or customers around the world, the SoundStation IP 3000 delivers the same Acoustic Clarity Technology in IP-enabled telephone systems that has made Polycom the leader in circuitswitched voice conferencing. Start having more efficient and productive meetings with the SoundStation IP 3000.

The best-in-class choice for The Polycom Office™

With integrated video, voice, data, and Web capabilities, The Polycom Office is the only solution that offers you an easy way to connect, conference, and collaborate any way you want. The Polycom Office is our commitment to making distance communications as natural and interactive as being there. Work faster, smarter and better with the SoundStation IP 3000 and The Polycom Office.





Connect. Any Way You Want.

Polycom SoundStation IP 3000 Specifications

PolycomSoundStationIP 3000 Technical specifications

Size

14.5 x 12.25 x 2.5 in (36.8 x 31.1 x 6.4 cm) (L x W x H)

Weight

1.75 lb. (0.8 kg)

Power

Universal power supply (110/220 V, 50/60 cycles) (100 V for Japan) Requires country-specific AC cable to be ordered

Display

.

- High-resolution graphical LCD
- Keypad
- 12-key telephone keypad
- On-hook/off-hook, redial, mute, volume up/down keys, menu navigation keys
- Three context-dependent softkeys

Loudspeaker

- Frequency response: 300 3300 Hz
- Volume: Adjustable to 85 dB at 1/2 meter peak volume

Network interface

- Ethernet 10/100BaseT
- IP address configuration DHCP
- Static IP
- · Supported codecs G.711 (A-law and µ-law)
- G.729a (Annex B)
- Time synchronization with SNTP server
- · User selectable ringer tones
- Convenient volume adjustment keys .
- Easily upgrade SoundStation IP 3000 in the field - Trouble-free software maintenance
 - Extends the life of the product to protect your investment as standards develop and protocols evolve

Regulatory compliance

- Safety
 - UL1950
 - CSA C22.2, No. 950 - EN60950
 - IEC60950
 - AS/NZS3260
- FMC
 - FCC (47 CFR Part 15) Class B
 - ICES-003 Class
 - EN55022 Class B
 - CISPR22 Class B
 - AS/NZS 3548 Class B
 - VCCI Class B
 - EN50224

Protocol support

- H.323 V2
- Gatekeeper-routed or gatekeeper-less operation -- E.164 dialing
- IP dialing
- Call Transfer using facility message
- · Quality of service architecture
- Silence suppression
- Echo cancellation
- Jitter buffer

Management support

Web-based configuration (HTTP) TFTP support for downloading of software updates

SoundStation IP 3000 ships with:

- Quick reference guide
- User manual
- Warranty registration card
- Tabletop console with integrated display and keypad
- -Power Interface Module (PIM)
- Universal power supply brick
- 6-ft Cat 5 Ethernet cable
- 25-ft Power/Ethernet cable (Connects PIM to console)

Warranty

One year

Polycom SoundStationIP 3000 features

- · Full-duplex echo cancellation
- Multiple call support
- Hold
- Call transfer (if supported by IP telephony system)
- Redial
- Mute
- Caller ID (if supported by IP telephony system)
- · Phone book

Environment conditions

- Operating temperature: $32^{\circ} 104^{\circ} \text{ F} (0^{\circ} 40^{\circ} \text{ C})$
- Relative humidity: 20% 85% (noncondensing)
- Storage temperature: $-22^{\circ} 131^{\circ}$ F ($-30^{\circ} 55^{\circ}$ C)

Part number

2200-06622-001 North American part number only.

Please call for more information on international products.

©2003 Polycom, Inc. All rights reserved

Polycom, the Polycom logo, and SoundStation are registered requery, us reportingly, and soundation are registered trademarks and The Polycom Office is a trademark of Polycom, Inc. in the U.S. and various countries. All other trademarks are the property of their respective companies.

Specifications subject to change without notice.

POLYCOM® IVCi 1-800-224-7083 www.ivci.com

Free Manuals Download Website <u>http://myh66.com</u> <u>http://usermanuals.us</u> <u>http://www.somanuals.com</u> <u>http://www.4manuals.cc</u> <u>http://www.4manuals.cc</u> <u>http://www.4manuals.cc</u> <u>http://www.4manuals.com</u> <u>http://www.404manual.com</u> <u>http://www.luxmanual.com</u> <u>http://aubethermostatmanual.com</u> Golf course search by state

http://golfingnear.com Email search by domain

http://emailbydomain.com Auto manuals search

http://auto.somanuals.com TV manuals search

http://tv.somanuals.com