

# ENFORCER®

## Outdoor Stand-Alone Weatherproof Keypads

### Quick User Programming Guide



(SK-2323-SDQ shown)



(SK-1323-SPQ shown)

Model Number	2 Relay Outputs	Backlit Keys	Proximity Reader
--------------	-----------------	--------------	------------------

#### Mullion-Style Keypads

SK-2323-SDQ	✓	✓	
SK-2323-SPQ	✓	✓	✓

#### Sealed-Environment Keypads

SK-1323-SDQ	✓	✓	
SK-1323-SPQ	✓	✓	✓

For complete programming instructions, please see page 10 of the User Manual.

## Programming Tips

- Program new Master Code immediately.
- Program the Output #1 access mode immediately, or the keypad will only accept user cards.
- Take note of the keypad status LEDs—
  - **Right LED Green:** Standby
  - **Left LED Solid Red/Right LED Solid Orange:** Programming Mode
  - **Right LED Flashing Orange:** Awaiting code/card entry
- If unsure of which mode the keypad is in, press **#** until the right LED is green. The keypad is now in the standby mode. Enter the master code twice to return to Programming Mode.
- For complete programming instructions, see page 10 of the User Manual.

## Programming the Master Code

1. Enter Programming Mode by entering the Master Code twice.  
(Default Master Code is **12345**)
2. Enter **\*3**.
3. Enter the new 5-digit Master Code twice.

**Example:** If the desired new Master Code is **54321**, enter:

**5 4 3 2 1 5 4 3 2 1**

4. Exit Programming Mode by pressing **#**.

## Setting the Output #1 Access Mode\*

**DEFAULT: User card only. To use codes, you MUST set mode to **01** or **02**.**

1. Enter Programming Mode by entering the Master Code twice.
2. Enter **\*0**.
3. Enter one of the following:

**00** **User card ONLY (DEFAULT)**

**01** **Either user card OR user code**

**02** **User card AND user code**

**Note:** The Output #1 Access Mode must be programmed in order for the SK-2323-SPQ and SK-1323-SPQ to accept user codes.

4. Exit Programming Mode by pressing **#**.

\*SK-2323-SPQ and SK-1323-SPQ only.

## Programming Output #1

Each Output #1 user can be programmed to have a user code and a user card.\*

---

### 1.1 User Code Only

1. Enter Programming Mode by entering the Master Code twice.
  2. Enter a user ID number. ( 0 0 0 to 9 9 9 )
  3. If the left LED is red, previous user data exists. Clear it by entering \* \* .  
The keypad will beep in confirmation and the left LED will turn green.
  4. Enter a new 5-digit user code.
  5. To program the next user, repeat from step 2 in section 1.1, 1.2, or 1.3.
  6. Exit Programming Mode by pressing # .
- 

### 1.2 User Card Only\*

1. Enter Programming Mode by entering the Master Code twice.
  2. Enter a user ID number. ( 0 0 0 to 9 9 9 )
  3. If the left LED is red, previous user data exists. Clear it by entering \* \* .  
The keypad will beep in confirmation and the left LED will turn green.
  4. Swipe a new user card.
  5. Return to Programming Mode by pressing # .
  6. To program the next user, repeat from step 2 in section 1.1, 1.2, or 1.3.
  7. Exit Programming Mode by pressing # again.
- 

### 1.3 User Card and Code\*

1. Enter Programming Mode by entering the Master Code twice.
  2. Enter a user ID number. ( 0 0 0 to 9 9 9 )
  3. If the left LED is red, previous user data exists. Clear it by entering \* \* .  
The keypad will beep in confirmation and the left LED will turn green.
  4. Swipe a new user card.
  5. Enter a new 5-digit user code.
  6. To program the next user, repeat from step 2 in section 1.1, 1.2, or 1.3.
  7. Exit Programming Mode by pressing # .
- 

\*SK-2323-SPQ and SK-1323-SPQ only.

## Programming Output #2

Each Output #2 user may only have a user code OR a user card programmed.

---

### 2.1 Programming an Output #2 User Code

1. Enter Programming Mode by entering the Master Code twice.
  2. Enter **\*4**.
  3. Enter a user ID number. ( **00** to **09** )
  4. If the left LED is red, previous user data exists. Clear it by entering **\*\*** .  
The keypad will beep in confirmation and the left LED will turn green.
  5. Enter a new 5-digit user code.
  6. To program the next user, repeat from step 3 in section 2.1 or 2.2.
  7. Return to Programming Mode by pressing **#** .
  8. Exit Programming Mode by pressing **#** again .
- 

### 2.2 Programming an Output #2 User Card\*

1. Enter Programming Mode by entering the Master Code twice.
2. Enter **\*4** .
3. Enter a user ID number. ( **00** to **09** )
4. If the left LED is red, previous user data exists. Clear it by entering **\*\*** .  
The keypad will beep in confirmation and the left LED will turn green.
5. Swipe a new user card.
6. To program the next user, repeat from step 3 in section 2.1 or 2.2.
7. Return to Programming Mode by pressing **#** .
8. Exit Programming Mode by pressing **#** again.

---

\*SK-2323-SPQ and SK-1323-SPQ only.

**NOTICE:** The information and specifications printed in this manual are current at the time of publication. However, the SECO-LARM policy is one of continual development and improvement. For this reason, SECO-LARM reserves the right to change specifications without notice. SECO-LARM is also not responsible for misprints or typographical errors.

Copyright © 2010 SECO-LARM U.S.A., Inc. All rights reserved. This material may not be reproduced or copied, in whole or in part, without the written permission of SECO-LARM.

---

**SECO-LARM® U.S.A., Inc.**

16842 Millikan Avenue, Irvine, CA 92606

Tel: 800-662-0800 / 949-261-2999 Fax: 949-261-7326

Website: [www.seco-larm.com](http://www.seco-larm.com)

E-mail: [info@seco-larm.com](mailto:info@seco-larm.com)

 PICCN2

SK-x323-SxQ Addendum\_1008.docx

## Free Manuals Download Website

<http://myh66.com>

<http://usermanuals.us>

<http://www.somanuals.com>

<http://www.4manuals.cc>

<http://www.manual-lib.com>

<http://www.404manual.com>

<http://www.luxmanual.com>

<http://aubethermostatmanual.com>

Golf course search by state

<http://golfingnear.com>

Email search by domain

<http://emailbydomain.com>

Auto manuals search

<http://auto.somanuals.com>

TV manuals search

<http://tv.somanuals.com>