

For details, refer to...

1	Check the contents.	>> PC7501 Packing List (Back)
2	Register your PC7501.	>> PC7501 User Registration Tool (Start up the REG7501E.EXE in the \REGISTER\ENGLISH folder on the Renesas Debugger Package CD-ROM) or send a hardware tool user registration FAX sheet
3	Install an emulator debugger. Download the latest emulator debugger from http://www.renesas.com/en/tools	>> README.HTM on the Renesas Debugger Package CD-ROM
4	Setup hardware.	>> PC7501 User's Manual "Chapter 4 Setup (P.23)" and the user's manual of the emulation probe <i>For Troubleshooting... PC7501 User's Manual "5.2 Interface Connection Error (P.37)"</i>
5	Turn on the PC7501 in maintenance mode.	>> PC7501 User's Manual "4.4 Downloading Firmware (P.34)"
6	Start up the emulator debugger.	>> Emulator Debugger User's Manual (Online Help)
7	Make settings for the emulator debugger.	>> Emulator Debugger User's Manual (Online Help)
8	Download firmware.	>> PC7501 User's Manual "4.4 Downloading Firmware (P.34)" and Emulator Debugger User's Manual (Online Help) <i>For Troubleshooting... PC7501 User's Manual "5.3 Firmware Download Error (P.39)"</i>
9	Exit the emulator debugger, and turn off the PC7501.	
10	Execute the self-check.	>> User's Manual of each emulation probe
11	Start up the emulator debugger.	>> Emulator Debugger User's Manual (Online Help)
	For Troubleshooting...	PC7501 >> PC7501 User's Manual "Chapter 5 Troubleshooting (P.37)" Emulator debugger >> Emulator Debugger User's Manual (Online Help) Renesas Tool Homepage PC7501 Emulators Site >> http://www.renesas.com/eng/products/mpumcu/toolhp/pc7501/

PC7501 Packing List

- PC7501 emulator main unit	1
- AC adaptor (100-240 V, 50/60 Hz)	1
- AC power cable (3m)	1
- USB interface cable (1.9m)	1
- LPT parallel interface cable (1.9m, IEEE1284-A male to IEEE1284-C male cable)	1
- External trigger input/event output cable (50 cm)	1
- 160-pin flexible cable for connecting emulation probe (Preinstalled to PC7501)	1
- Converter board for connecting emulation probe M3T-FLX160-EPB (Preinstalled to PC7501)	1
- Oscillator board OSC-3 for 30 MHz (Preinstalled to PC7501)	1
- Renesas Debugger Package CD-ROM	1
- PC7501 User's Manual (English)	1
- PC7501 User's Manual (Japanese)	1
- Hardware tool user registration FAX sheet	1

This product package does not contain a LAN cable. Get a commercially available 10BASE-T cable.

If any of these items are missing or found faulty, please contact your local distributor.

Free Manuals Download Website

<http://myh66.com>

<http://usermanuals.us>

<http://www.somanuals.com>

<http://www.4manuals.cc>

<http://www.manual-lib.com>

<http://www.404manual.com>

<http://www.luxmanual.com>

<http://aubethermostatmanual.com>

Golf course search by state

<http://golfingnear.com>

Email search by domain

<http://emailbydomain.com>

Auto manuals search

<http://auto.somanuals.com>

TV manuals search

<http://tv.somanuals.com>