



The next level in bilevel

The VPAP[™] S is a compact bilevel device designed to deliver effective and comfortable therapy. VPAP S uses ResMed's patented Easy-Breathe motor to make breathing easier for patients with obstructive sleep apnea (OSA), noncompliant CPAP users and those who require additional ventilatory support.

Big performance in a small package

The system is exceptionally compact and convenient, making it ideal for travel or home use.

Featuring the Easy-Breathe motor, ResMed's new technology, VPAP S offers nearly silent therapy, so patients and their bed partners can sleep peacefully throughout the night. In fact, the VPAP S is 75% quieter than competitive bilevel devices.

The high-performance H4i[™] humidifier offers best-in-class humidification for comfortable therapy that is easy to use on a nightly basis.

Comfortable, effective treatment

In CPAP mode, optional EPR[™] (expiratory pressure relief) decreases pressure upon exhalation for more comfortable therapy. In S (spontaneous) mode, two treatment pressures are set for inspiration (IPAP) and expiration (EPAP).

In addition to traditional spontaneous bilevel therapy, VPAP S features ResMed's Vsync[™] leak management algorithm, TiControl[™] breath synchronization control, and trigger and cycle sensitivity to further synchronize with patients. Consequently, VPAP S provides unparalleled bilevel therapy treatment.

Rich data options

VPAP S is incredibly reliable and compatible with the S8 ResLink,[™] ResScan[™] and S8 ResTraxx.[™] Built-in ResScan data card capability makes objective measurement of treatment use and treatment effectiveness simple and straightforward, while enabling you to access data and update therapy settings.



RESMED



VPAP S FEATURES SUMMARY

Modes of operation

- S (Spontaneous)
- CPAP (with EPR)

Product features

- Simplified standard setting menu
- Vsync automatic leak management
- TiControl (Ti max/min)
- Adjustable breath trigger/cycle
- 24V DC input (via converter)
- Compact S8[™] design
- Easy-Breathe motor

Heated humidification

• Optional, fully integrated

Data storage

- Usage and treatment summary (day, week, month, six-month, year)
- Usage profile
- · Summary data storage
- Detailed data storage
- · Remote settings adjustment

Data transfer

- Direct download to PC
- ResLink via SmartMedia card
- ResScan Data Card
- · Live oximetry with ResLink
- Remote compliance monitoring via ResTraxx



TECHNICAL SPECIFICATIONS

Performance

Operating pressure range: 3 to 25 cm H_2O Maximum single fault pressure: 40 cm H_2O

Dynamic pressure characteristics

S mode: IPAP: 4 to 25 cm H_2 0; EPAP: 3 to 25 cm H_2 0 **CPAP mode:** 4 to 20 cm H_2 0

Sound pressure level

< 26 dB (tested in accordance with the requirements of ISO 17510-1:2002) Data storage

Data Storaye

Data includes usage, leak, pressure, AHI, AI, tidal volume, respiratory rate and minute ventilation

Via LCD menu: 365 sessions of summary data

Via ResLink: 365 sessions of summary data, 30 sessions of detailed data

Via ResScan Data Card: 180 sessions of summary data, two sessions of detailed data

Dimensions (L x W x H): 4.4" x 6.5" x 5.7" (112 mm x 164 mm x 145 mm)

Weight: 2.9 lb (1.3 kg)

Power supply

Input range 100–240VAC, 50–60Hz, 40VA (typical power consumption), < 100VA (maximum power consumption), 12–24DVC via ResMed DC 24V/50W converter

Environmental conditions

Operating temperature: 41°F to 97°F (+5°C to +35°C) Operating humidity: 10–95% non-condensing

Electromagnetic compatibility

Product complies with all applicable electromagnetic compatibility requirements (EMC) for residential, commercial and light industry environments according to IEC 60601-1-2.

Air filter

Two-layered, powder-bonded, polyester non-woven fiber

IEC 60601-1 classification

Class II (double insulated), Type CF

Note: The manufacturer reserves the right to change these specifications without notice.

PRODUCT CODES

VPAP S	26119
H4i with standard water chamber	26940
VPAP S + H4i	26120
S8 ResLink	22206
Oximeter Kit	1430050
S8 ResTraxx US	22204
S8 ResTraxx Canada	22221

ResMed Corp Poway, CA, USA +1 858 746 2400 or 1 800 424 0737 (toll free), ResMed Ltd Bella Vista, NSW, Australia +61 (2) 8884 1000 or 1 800 658 189 (toll free). Offices in Austria, Belgium, Brazil, China, Finland, France, Germany, Greece, Hong Kong, India, Ireland, Italy, Japan, Malaysia, Mexico, Netherlands, New Zealand, Norway, Portugal, Singapore, South Africa, Spain, Sweden, Switzerland, United Kingdom (see website for details). EPR, HumidAire, ResLink, S8, ResScan, ResTraxx, TiControl, and Vsync are trademarks of ResMed Ltd. H4i and VPAP are trademarks of ResMed Ltd and are registered in U.S. Patent and Trademark Office. @2008 ResMed. 1011085/1 08 10

Free Manuals Download Website <u>http://myh66.com</u> <u>http://usermanuals.us</u> <u>http://www.somanuals.com</u> <u>http://www.4manuals.cc</u> <u>http://www.4manuals.cc</u> <u>http://www.4manuals.cc</u> <u>http://www.4manuals.com</u> <u>http://www.404manual.com</u> <u>http://www.luxmanual.com</u> <u>http://aubethermostatmanual.com</u> Golf course search by state

http://golfingnear.com Email search by domain

http://emailbydomain.com Auto manuals search

http://auto.somanuals.com TV manuals search

http://tv.somanuals.com