



Spectacular Detail

High-resolution digital camera performance

- 4-megapixels CCD
- 1cm macros
- 3X Optical zoom + 3.6X Digital zoom / 10.8X zoom total
- Just 26.6mm slim

122222

- Flexible multi-angle monitor
- Multimedia capturing capability
- On board 8MB memory



Download from Www.Somanuals.com. All Manuals Search And Download.



Photo taken by Caplio RR1. Size:2272x1704pixels, Fine mode

Photo-real Clarity

My Photo Collection

Caplio RR1 is a stunning new high-resolution digital camera designed to deliver optimal performance. Discover astonishing photo-real clarity coupled with a powerful optical 3X zoom that produces superb print-outs. With impressive built-in multimedia functionality and multi-angle monitor flexibility, you'll truly appreciate it's compact dynamic character. Experience your best pictures with the Caplio RR1.

Reveal striking detail with ease

4-megapixels of expression!

The Ricoh Caplio RR1 comes equipped with a 4-megapixel CCD that delivers astonishing high-resolution, true-color photo clarity. Confidently print beautiful A3-size (11x17 inch) photos on your home printer and be amazed with the exquisite detail!



High quality trimming functionality

00000000000000000000

Trimming captured images is a breeze whether it is done directly in the LCD using the Cropping Function or on your PC. Take pictures without worrying about composition – simply adjust them later for various usages, such as postcards. And since they are originally taken at 4-megapixels, even trimmed and enlarged images are of brilliant quality!

Get in close... 1cm Macros!

The Caplio RR1 allows you to get in as close as about 1cm (0.4 inch) from a subject revealing striking detail without sacrificing definition. Take clear, crisp shots of your hobby collectables and accessories and let the details do the talking!

Photo Size:2





Download from Www.Somanuals.com. All Manuals Search And Download.

Photo taken by Caplio RR1. Size:2272x1704pixels. Fine mode

Multi-angle flexibility designed to capture the moment

Size Does Matter!

The Caplio RR1 is a cool, compact, lightweight digital camera that's only 26.6 mm thin. It's smooth, sleek metallic body and classy design allows you to comfortably carry it in a shirt pocket. Whether it's for business or pleasure, the Caplio RR1 it is ready when you are.

Flexible multi-angle monitor

Enjoy Caplio RR1's clear, large size LCD monitor that's as flexible as your shooting demands. This monitor rotates and swivels at angles both high and low - accurately displaying your subjects even at the most challenging positions.






taken by Caplio RR1. 272x1704pixels, Fine mode



Photo taken by Caplio RR1. Size:2272x1704pixels, Fine mode

Up to 10.8X powerful zoom!

Sometimes it is difficult to get close to your subjects. In these situations take advantage of Caplio's 3X, optical zoom lens equivalent to 35 to 105mm on a 35mm camera. What's more, obtain an outstanding 10.8X, 378mm range by combining this with its digital 3.6X zoom*!



Unique multimedia functionality

Shoot mini-movies!

Impress your colleagues and friends with your creative short movies. Ideal for capturing continuous movements such as your golf swing. The Caplio RR1 gives you approximately 11 minutes of footage on a 128MB SmartMedia[™] card.

Text mode conversion

In the Caplio RR1's "Text" mode extracting text from printed material or a whiteboard and converting them into black-and-white data is extremely simple. And with an adjustable density function for enhanced readability, it serves as an ideal tool for business usage!

Sound mode enriches data


In "Sound" mode Caplio RR1 turns into a convenient sound recorder that's great for interviews and meetings. You can also add convenient voice memos to captured images and text. Approximately 273 minutes of sound can be placed onto a 128MB SmartMedia[™] card.

Wide range of high performance functionality Caplio RR1 is an outstanding multimedia digital camera with tremendous highperformance functionality. Browse through these impressive additional wide range of features!

- 0.8 sec./frame continuous shooting
- Manual focusing capability



- Exposure compensation (adjustable ±2EV in 0.25EV steps)
 - 3 adjustable flash settings (soft, normal, strong)
- Manual white balancing adaptability
- Auto Bracketing exposure capability
- Long-time exposure of up to 8 seconds
- Additional shutter release button for vertical shooting
- Non-compressed mode for high-quality saving (TIFF)



Accessories Included

Soft Case Wrist Strap Lens Cap O AV Cable Rechargeable Lithium-ion Battery Battery Charger
Software CD (Win, Mac) OUSB Cable Instruction manual

Warranty card





RR1 Major Specifications

| ITEM | DESCRIPTIONS | | |
|-----------------------|---|--|--|
| RECORDING FORMAT | Still:JPEG (Exif 2.1), Non-Compressed:TIFF-YUV(Exif 2.1) | | |
| | DCF"Design rule for Camera File system", DPOF support | | |
| | Text:TIFF(G4 MMR system) | | |
| | Motion:AVI (Open DML Motion JPEG) | | |
| | Sound:WAV(Exif 2.1) | | |
| VIDEO SIGNAL METHOD | NTSC/PAL switchable | | |
| RECORDING MEDIUM | Internal 8MB / SmartMedia™(compatible with 4/8/16/32/64/128MB,3.3V) | | |
| CCD | 1/1.8-inch CCD, effective 3.95 million pixels (total 4.13 million pixels) | | |
| RESOLUTION | Still: 2272x1704/1120x840/640x480 | | |
| | Text: 2272x1704/1120x840 | | |
| | Motion: 288x216 | | |
| RECORDING MODE | STILL/TEXT/SOUND/STILL+SOUND/MOTION+SOUND/CONTINUOUS/TIME | | |
| | EXPOSURE/INTERVAL(time rapse from 30 sec. Intervals up to 3 hours) | | |
| PICTURE MODE | Fine/Normal/Economy, Non-Compressed | | |
| LENS | F:2.6-3.4, 10 glass elements in 7 groups | | |
| ZOOM | Optical 3x zoom f=7.3-21.9mm(35-105mm in 35mm camera format) | | |
| | Digital 1.4x/1.8x/3.6x zoom (640x480 only) | | |
| SHUTTER | Still: 8,4,2,1-1/2000sec. (mechanical/electronic shutter) | | |
| | Motion: 1/30-1/2000sec. (electronic shutter) | | |
| SHOOTING RANGE | 24cm(9.4in.) -∞/ Macro: 1cm(0.4in.) -24cm(9.4in.) | | |
| ISO SENSITIVITY | AUTO (equivalent to ISO150) /Selectable ISO (equivalent to 200/400/800) | | |
| MONITOR DISPLAY | 2.0" Low-temperature Polysilicon TFT LCD (approx. 200,000 pixels) | | |
| BUILT-IN FLASH | AUTO/ON/SLOW SYNCHRO/OFF/RED-EYE REDUCTION, | | |
| | Manual Strength Adjustment(SOFT/NORMAL/STRONG) | | |
| FOCUS | AUTO FOCUS/MANUAL FOCUS/FIXED FOCUS(2.5m/0.8ft.) | | |
| EXPOSURE MODE | Programmed AE, TTL-CCD method | | |
| | Photometric system:CENTERWEIGHT/SPOT/MULTI | | |
| EXPOSURE ADJUSTMENT | AUTO/MANUAL EXPOSURE COMPENSATION (+/- 2.0 EV in 1/4EV steps) | | |
| WHITE BALANCE | AUTO/DAYLIGHT/FLUORESCENT LIGHT/TUNGSTEN LIGHT/OVERCAST | | |
| SELFTIMER | Approx. 10sec. Delay | | |
| INTERFACES | PC : USB *1 | | |
| | Video Out, Audio Out | | |
| BATTERY | Rechargeable Lithium-Ion Battery | | |
| DIMENSIONS(W x D x H) | 135.4 x 74.0 x 26.6mm, 5.3 x 2.9 x 1inch (excluding projections) | | |
| WEIGHT | Approx. 270g(9.5oz.)(without battery) | | |

*1 Limited PCs with Windows 98/2000/Me pre-installed or Macintosh with Mac OS 8.6-9.1 (USB service 1.1 or later)

Software CD(Windows/Macintosh)

Optional Accessories

| System Requirements | WINDOWS | MACINTOSH |
|------------------------------|---|------------------------|
| OS | Windows 98, Windows 98 Second Edition | Mac OS 8.6/9.0.4/9.1*3 |
| | Windows Me, Windows 2000*2 | |
| CPU | Pentium [®] II processor or faster | Power PC |
| MEMORY SPACE | Windows 98/98SE : 32MB or more (96MB recommended) | 96MB or more |
| | Windows 2000 : 128MB or more (256MB recommended) | (128MB recommended) |
| | Windows Me : 64MB or more (96MB recommended) | |
| HARD DISK SPACE | 100MB or more | 100MB or more |
| FOR OPERATION | | |
| CONTENTS | | |
| Caplio Utility software (for | file transfer between a PC and the RR1)*4 | |
| USB driver*5 | | |
| TWAIN driver | | |
| MGI PhotoSuite | | |
| QuickTime 4.1.2 | | |
| | s not compatible with Windows 95/NT. s not compatible with Mac OS X. | |

⁴⁵ Ocamera control function.
⁴⁵ Limited PCs with Windows 98/2000/Me pre-installed or Macintosh with Mac OS 8.6-9.1 (USB service 1.1 or later).

Not compatible with Mac OS X. * Only USB connection is possible when connecting the RR1 to a PC. It is not compatible with serial connection. *"Caplio Utility software" is exclusive software for Caplio RR1.It is not compatible with Caplio RR10/RDC series.

Optional Accessories

| MODEL | | |
|--------|--|-----------|
| FS-B53 | PC card adapter | |
| FS-B10 | Floppy disk adapter | (3) |
| DB-20L | Rechargeable Lithium-Ion Battery | |
| BJ-1 | Battery Charger | -0 |
| DR-3 | Remote Control | QuickTime |
| AC-3 | AC Adapter | |
| | est Ricoh Sales Office about availability of the Optional Accessories. | PRINT |

Specifications are subject to change without notice.
Microsoft, Windows are either registred trademarks of Microsoft Corporation of the U.S. and/or other countries.
Macintosh and QuickTime are registered trademarks of Apple Computer, Inc. of the U.S.A.

and other countries. * PhotoSuite, the PhotoSuite logo and the MGI logo are registered trademarks of MGI

software Corp. All other trademarks mentioned herein are the property of their respective owners. * All screen shots and sample images shown in this catalog are simulated.



This brochure was printed on recycled paper.

Image Matching

MGI



RICOH COMPANY, LTD.

3-2-3,Shin-yokohama Kohoku-ku Yokohama-shi 222-8530 Janan Phone:045-477-1738 Fax:045-477-1797 http://www.ricoh.co.jp/r_dc

RICOH CORPORATION 5. Dedrick Place, West Caldwell, NJ 07006 U.S.A. Phone:888-742-6410 http://www.ricohzone.com RICOH EUROPE B.V. (PMMC EUROPE) Oberrather Straße 6, D-40472

Düsseldorf, Germany Phone:0211-6546-0 Fax:0211-6546-308 http://www.ricohpmmc.com RICOH UK LTD. (PMMC UK)

Ricoh House, 1 Plane Tree Crescent, Feltham, Middlesex, TW13 7HG, England Phone:0208-261-4000 Fax:0208-261-4220

RICOH FRANCE S.A. (PMMC FRANCE) 383, Avenue du Général de Gaulle - BP 307-931-13 Clamart Cédex, France Phone:01-4094-3267 Fax : 01-4094-3276 RICOH ESPANA, S.A. (PMMC SPAIN)

Av. Litoral Mar, 12-14, 08005 Barcelona, Spain Phone:093-295-7600 Fax:093-295-7605 RICOH EUROPE B.V. (PMMC BENELUX) Koolhovenlaan 35, 1119 NB Schiphol-Rijk, The Netherlands

Phone:020-5474111 Fax:020-5474540

RICOH PHOTO PRODUCTS(ASIA), LTD. Unit D, E&F, 24/F., China Overseas Building,139 Hennessy Road Wan Chai, Hong Kong Phone:2528-2823 Fax:2566-3647/2866-1985 RICOH AUSTRALIA PTY. LTD. 8 Rodborough Road, Frenchs Forrest, N.S.W. 2086 Phone:02-8977-1111 Fax:02-8977-1100

http://www.ricoh.com.au Download from Www.Somanuals.com. All Manuals Search And Download.

Printed in Japan 2001-09001

Free Manuals Download Website <u>http://myh66.com</u> <u>http://usermanuals.us</u> <u>http://www.somanuals.com</u> <u>http://www.4manuals.cc</u> <u>http://www.4manuals.cc</u> <u>http://www.4manuals.cc</u> <u>http://www.4manuals.com</u> <u>http://www.404manual.com</u> <u>http://www.luxmanual.com</u> <u>http://aubethermostatmanual.com</u> Golf course search by state

http://golfingnear.com Email search by domain

http://emailbydomain.com Auto manuals search

http://auto.somanuals.com TV manuals search

http://tv.somanuals.com