## **Ricoh SMFC210M**

Secure Fax
Secure Communication With
Total Color Functionality





Color



# Ricoh SMFC210M

# A secure color document communication system

Absolute communication security is the most important thing you need in a SecureFax. The RICOH® SMFC210M SecureFax delivers communication security and much, much more. It's the first SecureFax system to allow you to both transmit and receive full color documents. And it can also print, copy and scan documents in full color. All with the security features you need to accomplish your mission.



# **SecureFaxCopyScanPrintColor**

# **Secure Document Communication First**

The Ricoh SMFC210M SecureFax is designed to operate with the most secure systems of document transmission available today: Secure Terminal Equipment (STE) digital encryption devices, as well as Omni and Secetera Terminals.

- A touch-screen user interface controls all secure communications functions and dramatically simplifies programming and changing communication modes. Easy to understand hints prompt users to the proper communication mode to set their encryption equipment.
- Volatile RAM memory storage ensures that jobs are deleted immediately after job completion or transmission failure—there is no hard drive memory storage to compromise security.
- Secure information is sent directly to another secure fax, so only the intended recipient has access to the information.



The Ricoh SMFC210M SecureFax gives you the all-in-one capabilities needed for today's mission—copying, printing, scanning and secure faxing—to handle nearly all of your mission requirements in a single unit.

- No need to deploy separate printer, copier and scanner units with their individual supplies.
- Print at a rapid 31 ppm B&W or 8 ppm color and copy at up to 21 ppm B&W or 7 ppm color—all at up to 1200 dpi resolution.
- Capture even fine details by scanning documents in full color at up to 1200 x 2400 dpi resolution.
- Scan originals at 21 ppm B&W or 7 ppm full color through the 35-page Automatic Document Feeder.
- Minimize print interruptions through the optional 530-sheet paper tray.

# The Power of Color

Everyone knows that color can add impact and boost comprehension of any document. But there are also times when color is simply necessary for complete communication.

- The Ricoh SMFC210M SecureFax allows you to send and transmit at up to 100 x 100 dpi standard, 200 x 200 dpi detail, 300 x 300 dpi fine and 400 x 400 dpi super-fine.
- Ensure better comprehension of photos, satellite images, charts, graphs, wiring diagrams, floor plans and other critical color documents.

### **Fast and Convenient**

Speed is essential in any SecureFax system. With its advanced digital technology, the Ricoh SMFC210M SecureFax makes sure your secure communications are received and sent as rapidly as possible.

- Eliminate waiting with the up to 128 Kbps synchronous transmission speed and the 115.2 Kbps asynchronous transmission speed when used with an ISDN-based STE.
- Take the Ricoh SMFC210M SecureFax anywhere at a moment's notice thanks to its compact, transportable design.



The Ricoh SMFC210M SecureFax can be used to send and receive both color and B&W documents.



All-In-One (AIO) supply cartridges ensure fast, easy replacement and protect the system from toner leakage during transport.



Color touch screen control panel simplifies operation in an easy-to-understand user interface.

# **Ricoh SMFC210M Specifications**

#### **Secure Specifications**

Modes/Protocols Supported

Desktop Color Laser SecureFax Asynchronous -(2.4Kbps – 115.2Kbps) Ricoh Compatible – (2.4Kbps – 9.6Kbps) Synchronous MIL-STD-181-161D -(2.4Kbps - 128Kbps) Color Image Transfer -(2.4Kbps - 115.2Kbps)

#### **Physical Interfaces**

Secure Interface RS232/MIL-STD-188-114:DB25

female

Printer Interface IEEE 1284 Parallel, USB 2.0, Optional Interface 10/100 Base TX Ethernet

#### **SecureFax Compatibility**

80M/TE, 4800MD, 2000M/TE, **Ricoh SFX Series** 

3900M/MI, 5510MSD, Ricoh Secure PC Card

Other Manufacturers Ilex 750/760/795/895/890/6000.

Cryptek T10

STE, STU III, SWT, SCIP, KG84, Cryptographic Equipment KY57, KY58, PSC 5, Qsec 2700 ITU-T Group 3 facsimile products

#### **SecureFax Scanning Resolutions**

Standard 8 x 3.85 L/mm Asynch MIL STD

(200 x 100 dpi) Detail 8 x 7.7 L/mm (200 x 200 dpi)

Secure Color Image Transfer

Standard (100 x 100 dpi) (200 x 200 dpi) Detail (300 x 300 dpi) Fine Superfine (400 x 400 dpi)

#### **Main System**

Configuration Technology

Desktop Color Laser MFP Laser Beam Scanning & Electrophotographic Printing; Single Component Toner Development

8 ppm

Output Speed (Letter)

Printing Copying (ADF)

Color Monochrome 31 ppm Color 7 cpm Monochrome 21 cpm Multiple Copying 1 to 99

Warm-up Time

45 seconds or less First Print Time Color < 20 seconds Monochrome < 14 seconds First Copy Time < 30 seconds Color

Scan/Copy Resolution Original Type

**Output Size** 

Monochrome < 20 seconds 600 x 600 dpi / 600 x 300 dpi Sheets, Books, 3D objects Document Feeding Standard 35-sheet ADF 5.5" x 8.5" to 8.5" x 14"\*,

Envelopes

\*with optional legal tray Standard Paper 250 x 1

Capacity

Optional Paper 530 x 1 (Letter Tray) or 250 x 1 (Legal Tray) Supplies Maximum Paper 780 sheets Capacity

Acceptable Paper Sizes

Letter (8.5" x 11") Standard Trav

A4 (8.3" x 11.7") EXE (7.25" x 10.5") B5 (6.9" x 9.8") Optional Paper Tray Letter (8.5" x 11")

A4 (8.3" x 11.7") EXE (7.25" x 10.5") B5 (6.9" x 9.8")



Legal (8.5" x 14") Optional Legal Tray

A5 (5.8" x 8.3") HLT (5.5" x 8.5") Com10, C5, DL

Envelopes Via Standard Tray Only

Acceptable Paper Weights

16 lb - 55 lb Bond/110 lb Index Standard Tray

(60 - 210 gm2) Optional Letter Tray 16 lb – 28 lb Bond (60 - 105 gm2)

Optional Legal Tray 16 lb - 55 lb Bond/110 lb Index

(60 – 210 gm2) Acceptable Paper Types Plain paper, thick paper,

transparencies, labels, glossy, envelopes

Duplex Manual

**Output Tray Capacity** Zoom **Reduction Ratios** 

250 sheets face down 25% - 400% in 1% increments 50%, 70%, 78%, 83%, 85%, 91%, 94%, 97%

**Enlargement Ratios** 104%, 141%, 200%

#### **Print Controller (Standard)**

CPU Memory 128 MB RAM standard, 576 MB RAM maximum

Page Description Languages Print Resolution

Standard Interfaces Optional Interface Network Protocols Print Drivers/

**Operating Systems** 

Utilities

Scan Area

VR5500A @ 266 MHz (shared) Windows/Mac

Normal Mode 600 x 600 dpi Fine Mode 2400 dpi level IEEE 1284 Parallel, USB 2.0, 10/100Base-TX Ethernet TCP/IP, IPX/SPX, SMB Windows® 9x/Me/NT4.0/2000/XP Macintosh OS 9.1 – 9.2, OS X 10.2.4 or later

SmartDeviceMonitor for Admin/ Client, Web Image Monitor

#### Scanner (Standard)

Scanning Modes Full-color and 256-level grayscale TWAIN scanning

Via Platen Up to 1200 x 2400 dpi Scanning Resolution

(optical)

Up to 1200 x 600 dpi Via ADF

(optical) Maximum 9600 x 9600 dpi

(interpolated) Monochrome 21 originals

Scanning Speed per minute

Full-color 7 originals per minute Via Platen Up to 8.5" x 11.7' Via ADF

Width 5.8" – 8.5", Length 5.8" – 14" Scanner Utilities TWAIN Driver, Control Center Scanner Utility, OmniPage OCR, & Drivers

PaperPort 9.0SE Image Viewer **Protocol Support** TCP/IP, IPX/SPX, SMB

#### Facsimile G3

Super G3 Transceiver Туре Circuit PSTN, PBX

Number of Lines Compatibility ITU-T Group 3

#### Resolution 203 x 98 Standard Mode 203 x 192 Fine Mode

203 x 392 Superfine Mode Modem Speed 33.6Kbps with

Automatic Fallback to 2400bps Transmission

G3 3 seconds per page
(without JBIG compression) Speed\*, \*\* MH/MR/MMR/JBIG

Compression Method Via Platen Up to 11.7" in length **Document Size** 

Width 5.8" – 8.5", Via ADF Length 5.8" – 14"

8.2" (208mm) Maximum Scanning

Width

Scanning Speed 21 pages per minute SAF Memory Up to 400 pages

One-touch Dials 16 Speed Dial Locations 200

Auto Redial 1 time after 5 minutes Auto Answer At 0, 1, 2, 3 or 4 rings

PC Faxing Yes
\*Based on ITU-T Test Chart #1 in Standard mode.

\*\*Approximately 3 seconds per page at 33.6Kbps is dependent on optimal line quality. Customer performance may vary by

#### System Specifications

**Power Supply** AC 120 V, 50/60 Hz **Power Consumption** 

630 W Copying

Standby 170 W

Environment Temperature

0-40 C (32-104 F) Storage Operating 10-32 C (50-90 F) Humidity 10-90% (without Storage

condensation) Operating 20-80% (without

condensation)

Dimensions (WxDxH) 21 x 17.4 x 21 inches Weight

Approx. 79 lbs Includes paper cassette and toner cartridges

#### Regulatory and Other **Agency Approvals**

FCC 15 Class B, UL, cUL, CE, FCC Part 68 I/C J.I.T.C. MIL-STD Compliance Certification (Pending)

#### **Hardware Accessories**

530-sheet Paper Tray 250-sheet Legal Paper Tray 128 MB Memory Unit Type C 256 MB Memory Unit Type C

#### Consumables and Yields

Black Toner Cartridge 9,800 prints @ 5% coverage Cyan Toner Cartridge 6,500 prints @ 5% coverage 6,500 prints @ 5% coverage Magenta Toner Cartridge

Yellow Toner Cartridge 6,500 prints @ 5% coverage 60,000 developments Photoconductor Waste Toner Bottle 11,000 developments

The SMFC210M ships with starter toner cartridges with yields of 5,000 pages for Black and 3,000 pages for Cyan, Magenta and Yellow colors at 5% coverage.



Printed in U.S.A. on recycled paper because Ricoh cares.

Ricoh Americas Corporation, Five Dedrick Place, West Caldwell, NJ 07006
Ricoh® and the Ricoh logo are registered trademarks of Ricoh Company, Ltd. Windows and Windows 3.1/95/98/Me/NT 4.0/2000/XP are registered trademarks of Microsoft Corporation. All other trademarks are the property of their respective owners.

Specifications and external appearances are subject to change without notice.

CA-R2711

Ricoh Americas Corporation 8270 Willow Oaks Corporate Drive, Suite 150, Fairfax, VA 22031 Toll-free Phone: 1-800-876-5966; Phone: 1-703-698-6702 Fax: 1-703-698-8619; Email: Irv.Sentz@ricoh-usa.com Free Manuals Download Website

http://myh66.com

http://usermanuals.us

http://www.somanuals.com

http://www.4manuals.cc

http://www.manual-lib.com

http://www.404manual.com

http://www.luxmanual.com

http://aubethermostatmanual.com

Golf course search by state

http://golfingnear.com

Email search by domain

http://emailbydomain.com

Auto manuals search

http://auto.somanuals.com

TV manuals search

http://tv.somanuals.com