



CSI-100

Bidirectional Coaxial Interface Board Option Kit for KP-32

Features

The CSI-100 permits the use of existing, but unused 75 Ω video coaxial cable as an alternative to running new cable for a keypanel connection. The CSI-100 is a bidirectional; single-channel coaxial interface, which passes digital audio and control between KP-32 series keypanels, and CSI-200 coaxial interfaces connected to RTS intercom matrices. Installation of the CSI-100 is quick and simplified with no user settings. Existing KP-32 series keypanels can be retrofitted with the CSI-100 in about 15 minutes. In addition, KP-32 keypanels can be ordered with the CSI-100 option already installed.

CSI-100 Specifications

SNR @ +8 dBu (A-weighted)

>70 dB

THD+N @ +8 dBu (un-weighted)

<0.1%

Frequency Response

100 Hz - 20 kHz \pm 1dB

Operating Level

+8 dBu

Maximum Level

+20 dBu

Crosstalk

>70 dB

Coaxial Port

BNC Female, 75 Ω impedance

Power

Supplied by keypanel

Operating Temperature

-20° to 50°C (-4° to 122°F)

Storage Temperature

-40° to 85°C (-40° to 185°F)

Operating & Storage Humidity

0 to 95% non-condensing

Contact Information

Telex Communications, Inc.
12000 Portland Avenue South
Burnsville, Minnesota 55337
Telephone: 877-863-4169
Fax: 800-955-6831

Ordering Information

CSI-100
Bidirectional coaxial interface option kit
Catalog Number: 90027693000

Form Number: LIT000047000

Date: April, 2006

This specifications information is preliminary and is subject to change without notification.

Brand names mentioned are the property of their respective companies.

Free Manuals Download Website

<http://myh66.com>

<http://usermanuals.us>

<http://www.somanuals.com>

<http://www.4manuals.cc>

<http://www.manual-lib.com>

<http://www.404manual.com>

<http://www.luxmanual.com>

<http://aubethermostatmanual.com>

Golf course search by state

<http://golfingnear.com>

Email search by domain

<http://emailbydomain.com>

Auto manuals search

<http://auto.somanuals.com>

TV manuals search

<http://tv.somanuals.com>