

## Rollei dk4010

High performance and sophisticated 4 megapixels digital camera with 10x D-VarioApogon zoom lens and 6x digital zoom. Video and voice recording possible. Designed to meet the challenges of discriminating amateur photographers.

Cat. No. 22455

Bar Code 4021136224555

- Fast continuous shooting with high speed image processing at approx. 3.3 images/s without refocusing
- Extremely fast autofocus for up to 2 images/s using refocusing
- High-speed, high-performance 10x Rollei Apogon zoom lens (equivalent to 37 – 370 mm in 35mm photography)
- Electronic color viewfinder with high resolution (300,000 pixels), image information, eyesight correction
- E52 filter thread for supplementary lenses and filters



## Rollei dk4010



 **HighSpeed  
Imageprocessing**

B. Kamrath

## Specifications

### Sensor

1/2,7"

4.2 M pixels CCD

### Image resolution

2272 x 1704 pixels,

1600 x 1200 pixels,

1280 x 960 pixels,

640 x 480 pixels

### Video Clip, with sound

640 x 480 pixels,

320 x 240 pixels

30 and 15 fps

### Image storage

SD and MM Card

### Recording format

JPEG (EXIF 2.2), AVI

### Built-in microphone and loudspeaker

### Lens

D-VarioApogon zoom lens

5.7 – 57 mm f/2.8 – 3.1 HFT

(equivalent to approx. 37 – 370 mm  
in 35mm format)

### Zoom

10x optical,

6x digital

### Focus range

autofocus, 0.6 m to ∞

### Macro range

10 to 60 cm

### Shutter speed, automatically

1 s – 1/2000 s

(CCD controlled electronic  
program shutter)

### Film speed setting, auto

ISO 100, 200, 400, 800

### Aperture and shutter speed

10x aperture and shutter

speed steps

### Programs

Sport, Portrait, Night, Nightportrait

### Exposure compensation

auto, manual

+/-2.0 EV in 1/3 increments

### Drive

Single and continuous shooting

AF active continuous shooting:

2 Images/s

AF saved:

3.3 Images/s in high resolution

### White balance

auto, manual

light sunlight, cloudy, tungsten,

fluorescent, preset

### Flash

auto, off, Anti-red-eye auto,

Anti-red-eye fill-in, daylight fill-in

### Viewfinder

Ferroelectric Liquid Crystal,

ca. 300K pixels

### LC monitor

1.5" DayFine TFT colour monitor

(110K pixels)

### Self timer

2 s/10 s delay

### Interfaces

USB, Video (NTSC, PAL), Audio,

AC/DC

## PictBridge function

### Power Source

4x AA Alkali-Batteries,

4x AA rechargeable NiMH batteries,

AC adapter (optional)

### Tripod mount

1/4"

### Dimensions (w x h x d)

107 x 73 x 87,5 mm

### Weight

310 g

(without batteries and SD-card)

### System requirements

**PC, Windows 98/98SE/2000/  
ME/XP**

CD ROM-drive,

USB-interface

### Apple Macintosh,

**OS 9.0 or higher**

CD ROM-drive,

USB-interface

### Contents

Rollei dk4010, USB and video-

cable, 4x Alkaline batteries,

lens cap, strap, ACDSsee software,

CD-ROM with drivers and instruc-

tion manual, Quick Start Guide

Subject to change without notice.

## Free Manuals Download Website

<http://myh66.com>

<http://usermanuals.us>

<http://www.somanuals.com>

<http://www.4manuals.cc>

<http://www.manual-lib.com>

<http://www.404manual.com>

<http://www.luxmanual.com>

<http://aubethermostatmanual.com>

Golf course search by state

<http://golfingnear.com>

Email search by domain

<http://emailbydomain.com>

Auto manuals search

<http://auto.somanuals.com>

TV manuals search

<http://tv.somanuals.com>