To learn more about the Samsung SCX-4824FN / 4828FN or to find your nearest retailer, please visit: samsung.com

Samsung Electronics Co., Ltd. Samsung Main Building 250, 2-Ka, Taepyung-Ro, Chung-Ku, Seoul, Korea 100-742





imagine an optimized simplicity

Samsung Monochrome Laser Multi-function Printers SCX-4824FN / 4828FN



Imagine a multifunction printer that meets your business needs. The SCX-4824FN and SCX-4828FN is optimized simplicity, yet provides professional features increasing productivity and efficiency with duplex and Direct USB. A harmonious balance for any office. With the Samsung SCX-4824FN and SCX-4828FN its not that hard to imagine.





1. Printer Language

 PCL5e, PCL6, PS3 (SCX-4828FN Only)
 Support variable office printing environments and documents

2. High Performance & All-in-One

24 ppm / 28 ppm
 Sufficient speed for professional workgroup

3. Compact & Corner-less Design

- Simple & Stylish
 A design that is harmonious to any office with stylish and a less machine look
- 4. ADF • 50 Sheets / 30 Sheets
- 5. Compass Navigation • Simple Menu
- A design enhancement that indicates 'Job in Progress'

Control Panel Components



 1. ID Copy
 2. Direct USB
 3. Display Screen
 4. Status
 5. Fax
 6. Copy
 7. Scan
 8. Menu
 9. Number Keypad

 10. Address book
 11. On Hook Dial
 12. Redial / Pause
 13. Stop / Clear
 14. Start

6. Direct USB SCX-4828FN Only

 Convenient feature that enables users to print or to scan directly from USB

7. Support for Various Paper Size Maximum Paper handling Versatility with customizable paper input sizes

8. Quiet MFP

Lowest noise level among its class
 Work in peace and tranquility

9. Casette

- 250 Sheets Standard CST
- (Available Optional CST 250)
- Maximum of 500 Paper Input Capacity.

10. Compact B2B LMFP

- Small Size (W x D x H) 445 x 411 x 395 mm (17.53" x 16.16" x 15.56")
- Smart spacing, Efficient utilization of office

Versatile and Feature Rich

- Versatile and Convenient Features

• Versatile 5-in-1

Versatility is the key to these convenient 5-in-1 laser multifunction Printers. With all the functions you have asked for in one central device, you can print, copy, scan, fax and PC-fax conveniently and easily. The SCX-4824FN/28FN delivers high performance and maximum speed versatile enough for a professional workgroup.




Intuitive and Ease of Use

- Intuitive and Simple Operation

• Innovative Compact Design

Multifunction Printers are convenient but take up a lot of space. The SCX-4824FN/28FN features a compact design that will fit into any workspace. At $445 \times 411 \times 395$ mm, its neat size and sleek design give you the performance you need without the bulk.



• Efficient Duplex + ADF

Convenient features increase your daily office efficiency. The 50-sheet automatic document feeder (30-sheet ADF on SCX-4824FN) saves time and speeds up copying and scanning, while giving you more control over the process. The SCX-4828FN model features duplex printing, saving time and reducing paper consumption.

Page1 Page1

Convenient Direct USB

The ultimate modern convenience – direct USB. Now your employees can disconnect from the PC and freely print and scan at SCX-4828FN. Just connect a USB storage device and print the contents. Or scan and save directly to USB without needing a PC.




Customizable Paper Formats

The SCX-4824FN/28FN is prepared for global business with a customizable paper size tray that can handle international paper formats. Compatible paper sizes include A6, A4, A5, letter, legal, folio, oficio, executive, ISO B5, JIS B5, 3x5, monarch, No. 10, DL, C5 and C6. This versatile feature allows your business to be prepared for the future.

Support of any size from A6 to Legal. Paper format is completely customizable unlike the competition.

A6, A4, A5, Letter, Legal, Folio, Oficio, Executive, ISO B5, JIS B5, 3"x5", Monarch, No.10, DL, C5, C6





Get everyone at work onboard quickly with simple and easy to use GUI screens. Reduce training and troubleshooting time with simple intuitive menus and buttons. The IT department can keep the user manuals because no one will need to read them to be able to print, copy, scan and fax simply and quickly.





Less Trouble and Stress

- Efficient And Trouble Free

Fast FPOT

Everyone wants fast printouts, but if the first page out of the printer takes too long, waiting can be very stressful. The SCX-4828FN boasts a fast frist page print time of 15.5 seconds in the sleep mode. That means that even if you are just printing one page, the results will be quick and stress free.



• Durable Max. Monthly Duty

When choosing a printer, most businesses look at speed and output quality. But another important factor is the maximum monthly duty cycle. In other words, the maximum number of pages a printer can generate each month. The SCX-4824FN/28FN produces a high rate of 50,000 pages a month, ensuring the availability along with the productivity of the Samsung MFP.



Comfortable Look and Feel - Appeal And Design

Unique Corner-less Organic Design

Samsung is known for stylish innovative design. The SCX-4824FN /28FN adds in another element - organic design. The overall concept is softer, rounder and more natural, adding a comforting appeal to your workspace.



Blue Compass Navigation

The innovative Blue Compass Navigation, with its signature Samsung blue glow, keeps you updated on the progress of the current task and helps you navigate the menu. The Blue Compass Navigation is easy to use and adds a striking focal point to the menu.

The Blue Compass Navigation helps you Navigate for accessing variety functions.

Clockwise circular motion indicating task progress



Tranguil Printing

Your business can work in peace and tranquility, even when printing multiple jobs, thanks to the SCX-4824FN/28FN guiet print levels. They have the lowest noise levels of their class, at just 49-52 dBA for printing and copying. That is quieter than a normal conversation or a telephone dial tone. Enjoy productivity and peace at the same time.





SPECIFICATIONS



Differences	SCX-4824FN	SCX-4828FN	
PRINT			
Speed (Mono) *	Up to 24 ppm	Up to 28 ppm in A4 (30 ppm in Letter),	
		Up to 14 ipm in A4 (14.5 ipm in Letter)	
First Page Out Time (Mono)	9.5 seconds (From Ready mode)	8.5 seconds (From Ready mode)	
Resolution	Up to 1200 x 12	00 dpi effective output	
Emulation	PCL5e, PCL6	PCL5e, PCL6, PostScript 3	
Duplex	Manual	Built-in	
COPY	TVICI ICCI	Duit in	
	Lip to 24 com	Up to 28 cpm in A4 (30 cpm in Letter)	
Speed Decel tion	Up to 24 cpm		
Resolution		200 dpi effective output	
First Page Out Time (Mono)		From Ready mode)	
Zoom Rate		en), 25 ~ 100% (ADF)	
Multy Copy		99 pages	
Duplex Copy	N/A	Built-in	
Copy Features	ID Copy, 2-up, 4-up, Poster Cop	y, Clone Copy, Collation Copy, Auto-fit	
SCAN			
Compatibility	TWAIN Standard, WIA Standard (Windows XP only)		
Method	Color CIS		
Resolution (Optical)	Up to 600 x 600 dpi	Up to 1,200 x 1,200 dpi (Platen)	
Resolution (Enhanced)	Up to 4,8	00 x 4,800 dpi	
Scan to	PC	PC, E-mail, USB Memory	
FAX			
Compatibility	ITU	G3, ECM	
Modem Speed	33.6 Kbps		
Resolution	Standard : 203 x 98 dpi, Fine / Photo : 203 x 196 dpi, Super Fine : 300 x 300 dpi, Color : Up to 200 x 200 dpi		
Memory		3.2 MB (Approx. 260 pages at ITU-T #1 Chart)	
Auto Dial		Speed dial : 200 Locations	
Fax Feature	Junk Fax barrier, Fax Forward to Fax,	Junk Fax barrier, Fax Forward to Fax / E-mail,	
	Broadcasting up to 209 locations	Broadcasting up to 209 locations	
PAPER HANDLING			
Input Capacity and Types		Tray, 1-sheet Manual Tray	
Output Capacity and Types	100-sheet Face Down		
		150-sheet Face Down	
Media Size		~ 216 x 356 mm (8.5" x 14")	
Media Size Media Type			
Media Size		~ 216 x 356 mm (8.5" x 14")	
Media Size Media Type	Plain, Thin, Recycled, C 30-sheet	~ 216 x 356 mm (8.5" x 14") HP, Label, Card, Thick, Bond	
Media Size Media Type ADF Capacity	Plain, Thin, Recycled, C 30-sheet	~ 216 x 356 mm (8.5" x 14") HP, Label, Card, Thick, Bond 50-sheet	
Media Size Media Type ADF Capacity ADF Document Size	Plain, Thin, Recycled, C 30-sheet Width : 142 ~ 216 mm (5.6" ~ 8.5	~ 216 x 356 mm (8.5" x 14") HP, Label, Card, Thick, Bond 50-sheet	
Media Size Media Type ADF Capacity ADF Document Size GENERAL	Plain, Thin, Recycled, C 30-sheet Width : 142 ~ 216 mm (5.6" ~ 8.5 2 line x	~ 216 x 356 mm (8.5" x 14") HP, Label, Card, Thick, Bond 50-sheet 5"), Length : 148 ~ 356 mm (5.8" ~ 14")	
Media Size Media Type ADF Capacity ADF Document Size GENERAL LCD	Plain, Thin, Recycled, C 30-sheet Width : 142 ~ 216 mm (5.6" ~ 8.5 2 line x 128 MB	 ~ 216 x 356 mm (8.5" x 14") HP, Label, Card, Thick, Bond 50-sheet 5"), Length : 148 ~ 356 mm (5.8" ~ 14") 16 characters 	
Media Size Media Type ADF Capacity ADF Document Size GENERAL LCD Memory / Storage	Plain, Thin, Recycled, C 30-sheet Width : 142 ~ 216 mm (5.6" ~ 8.5 2 line x 128 MB Windows 2000 / 2003 Server / XP / V	 ~ 216 x 356 mm (8.5" x 14") HP, Label, Card, Thick, Bond 50-sheet 50, Length : 148 ~ 356 mm (5.8" ~ 14") 16 characters (Max. 384 MB) ista Various Linux OS, Mac OS X 10.3~10.5 	
Media Size Media Type ADF Capacity ADF Document Size GENERAL LCD Memory / Storage OS Compatibility Interface	Plain, Thin, Recycled, C 30-sheet Width : 142 ~ 216 mm (5.6" ~ 8.5 2 line x 128 MB Windows 2000 / 2003 Server / XP / V Hi-Speed USB 2.0	 ~ 216 x 356 mm (8.5" x 14") HP, Label, Card, Thick, Bond 50-sheet 5"), Length : 148 ~ 356 mm (5.8" ~ 14") 16 characters (Max. 384 MB) ista Various Linux OS, Mac OS X 10.3~10.5 Ethernet 10/100BaseTX 	
Media Size Media Type ADF Capacity ADF Document Size GENERAL LCD Memory / Storage OS Compatibility	Plain, Thin, Recycled, C 30-sheet Width : 142 ~ 216 mm (5.6" ~ 8.5 2 line x 128 MB Windows 2000 / 2003 Server / XP / V Hi-Speed USB 2.0, Less than 49 dBA (Printing),	 ~ 216 x 356 mm (8.5" x 14") HP, Label, Card, Thick, Bond 50-sheet 5"), Length : 148 ~ 356 mm (5.8" ~ 14") 16 characters (Max. 384 MB) ista Various Linux OS, Mac OS X 10.3~10.5 Ethernet 10/100BaseTX Less than 50 dBA (Printing), 	
Media Size Media Type ADF Capacity ADF Document Size GENERAL LCD Memory / Storage OS Compatibility Interface	Plain, Thin, Recycled, C 30-sheet Width : 142 ~ 216 mm (5.6" ~ 8.5 2 line x 128 MB Windows 2000 / 2003 Server / XP / V Hi-Speed USB 2.0 Less than 49 dBA (Printing), Less than 53 dBA (Copying),	 ~ 216 x 356 mm (8.5" x 14") HP, Label, Card, Thick, Bond 50-sheet 5"), Length : 148 ~ 356 mm (5.8" ~ 14") 16 characters (Max. 384 MB) ista Various Linux OS, Mac OS X 10.3~10.5 Ethernet 10/100BaseTX Less than 50 dBA (Printing), Less than 53 dBA (Copying), 	
Media Size Media Type ADF Capacity ADF Document Size GENERAL LCD Memory / Storage OS Compatibility Interface Noise Level	Plain, Thin, Recycled, C 30-sheet Width : 142 ~ 216 mm (5.6" ~ 8.5 2 line x 128 MB Windows 2000 / 2003 Server / XP / V Hi-Speed USB 2.0, Less than 49 dBA (Printing), Less than 53 dBA (Copying), Less than 26 dBA (Standby)	 ~ 216 x 356 mm (8.5" x 14") HP, Label, Card, Thick, Bond 50-sheet 5"), Length : 148 ~ 356 mm (5.8" ~ 14") 16 characters (Max. 384 MB) ista Various Linux OS, Mac OS X 10.3~10.5 Ethernet 10/100BaseTX Less than 50 dBA (Printing), Less than 53 dBA (Copying), Less than 26 dBA (Standby) 	
Media Size Media Type ADF Capacity ADF Document Size GENERAL LCD Memory / Storage OS Compatibility Interface Noise Level Duty Cycle, Monthly	Plain, Thin, Recycled, C 30-sheet Width : 142 ~ 216 mm (5.6" ~ 8.5 2 line x 128 MB Windows 2000 / 2003 Server / XP / V Hi-Speed USB 2.0 Less than 49 dBA (Printing), Less than 53 dBA (Copying), Less than 26 dBA (Standby) 50,0	 ~ 216 x 356 mm (8.5" x 14") HP, Label, Card, Thick, Bond 50-sheet 5"), Length : 148 ~ 356 mm (5.8" ~ 14") 16 characters (Max. 384 MB) ista Various Linux OS, Mac OS X 10.3~10.5 Ethernet 10/100BaseTX Less than 50 dBA (Printing), Less than 53 dBA (Copying), Less than 26 dBA (Standby) 000 pages 	
Media Size Media Type ADF Capacity ADF Document Size GENERAL LCD Memory / Storage OS Compatibility Interface Noise Level Duty Cycle, Monthly Dimension (W x D x H)	Plain, Thin, Recycled, C 30-sheet Width : 142 ~ 216 mm (5.6" ~ 8.5 2 line x 128 MB Windows 2000 / 2003 Server / XP / V Hi-Speed USB 2.0 Less than 49 dBA (Printing), Less than 53 dBA (Copying), Less than 26 dBA (Standby) 50,0 445.2 x 410.5 x 395.3 r	 ~ 216 x 356 mm (8.5" x 14") HP, Label, Card, Thick, Bond 50-sheet 5"), Length : 148 ~ 356 mm (5.8" ~ 14") 16 characters (Max. 384 MB) ista Various Linux OS, Mac OS X 10.3~10.5 Ethernet 10/100BaseTX Less than 50 dBA (Printing), Less than 53 dBA (Copying), Less than 26 dBA (Standby) 100 pages nm (17.53" x 16.16" x 15.56") 	
Media Size Media Type ADF Capacity ADF Document Size GENERAL LCD Memory / Storage OS Compatibility Interface Noise Level Duty Cycle, Monthly Dimension (W x D x H) Weight (with CRU)	Plain, Thin, Recycled, C 30-sheet Width : 142 ~ 216 mm (5.6" ~ 8.5 2 line x 128 MB Windows 2000 / 2003 Server / XP / V Hi-Speed USB 2.0 Less than 49 dBA (Printing), Less than 53 dBA (Copying), Less than 26 dBA (Standby) 50,0 445.2 x 410.5 x 395.3 r	 ~ 216 x 356 mm (8.5" x 14") HP, Label, Card, Thick, Bond 50-sheet 5"), Length : 148 ~ 356 mm (5.8" ~ 14") 16 characters (Max. 384 MB) ista Various Linux OS, Mac OS X 10.3~10.5 Ethernet 10/100BaseTX Less than 50 dBA (Printing), Less than 53 dBA (Copying), Less than 26 dBA (Standby) 000 pages 	
Media Size Media Type ADF Capacity ADF Document Size GENERAL LCD Memory / Storage OS Compatibility Interface Noise Level Duty Cycle, Monthly Dimension (W x D x H) Weight (with CRU) CONSUMABLES	Plain, Thin, Recycled, C 30-sheet Width : 142 ~ 216 mm (5.6" ~ 8.5 2 line x 128 MB Windows 2000 / 2003 Server / XP / V Hi-Speed USB 2.0, Less than 49 dBA (Printing), Less than 53 dBA (Copying), Less than 26 dBA (Standby) 50,0 445.2 x 410.5 x 395.3 r 14.5	 ~ 216 x 356 mm (8.5" x 14") HP, Label, Card, Thick, Bond 50-sheet 5"), Length : 148 ~ 356 mm (5.8" ~ 14") 16 characters (Max. 384 MB) ista Various Linux OS, Mac OS X 10.3~10.5 Ethernet 10/100BaseTX Less than 50 dBA (Printing), Less than 53 dBA (Copying), Less than 26 dBA (Standby) 000 pages nm (17.53" x 16.16" x 15.56") Kg (32 lbs) 	
Media Size Media Type ADF Capacity ADF Document Size GENERAL LCD Memory / Storage OS Compatibility Interface Noise Level Duty Cycle, Monthly Dimension (W x D x H) Weight (with CRU)	Plain, Thin, Recycled, C 30-sheet Width : 142 ~ 216 mm (5.6" ~ 8.5 2 line x 128 MB Windows 2000 / 2003 Server / XP / V Hi-Speed USB 2.0, Less than 49 dBA (Printing), Less than 53 dBA (Copying), Less than 26 dBA (Standby) 50,0 445.2 x 410.5 x 395.3 r 14.5 Standard : Average Cartric	 216 x 356 mm (8.5" x 14") HP, Label, Card, Thick, Bond 50-sheet 5"), Length : 148 ~ 356 mm (5.8" ~ 14") 16 characters (Max. 384 MB) ista Various Linux OS, Mac OS X 10.3~10.5 Ethernet 10/100BaseTX Less than 50 dBA (Printing), Less than 53 dBA (Copying), Less than 26 dBA (Standby) i00 pages mm (17.53" x 16.16" x 15.56") Kg (32 lbs) Idge Yield 2,000 standard pages. 	
Media Size Media Type ADF Capacity ADF Document Size GENERAL LCD Memory / Storage OS Compatibility Interface Noise Level Duty Cycle, Monthly Dimension (W x D x H) Weight (with CRU) CONSUMABLES	Plain, Thin, Recycled, C 30-sheet Width : 142 ~ 216 mm (5.6" ~ 8.5 2 line x 128 MB Windows 2000 / 2003 Server / XP / V Hi-Speed USB 2.0 Less than 49 dBA (Printing), Less than 53 dBA (Copying), Less than 26 dBA (Standby) 50,0 Standard : Average Cartrid High Yield : Average cartridge Yield 5,000 standard	 216 x 356 mm (8.5" x 14") HP, Label, Card, Thick, Bond 50-sheet 5"), Length : 148 ~ 356 mm (5.8" ~ 14") 16 characters (Max. 384 MB) ista Various Linux OS, Mac OS X 10.3~10.5 Ethernet 10/100BaseTX Less than 50 dBA (Printing), Less than 53 dBA (Copying), Less than 26 dBA (Standby) 100 pages nm (17.53" x 16.16" x 15.56") Kg (32 lbs) Ige Yield 2,000 standard pages. I pages. (Ships with 2,000 pages Starter Toner Cartridge 	
Media Size Media Type ADF Capacity ADF Document Size GENERAL LCD Memory / Storage OS Compatibility Interface Noise Level Duty Cycle, Monthly Dimension (W x D x H) Weight (with CRU) CONSUMABLES	Plain, Thin, Recycled, C 30-sheet Width : 142 ~ 216 mm (5.6" ~ 8.5 2 line x 128 MB Windows 2000 / 2003 Server / XP / V Hi-Speed USB 2.0 Less than 49 dBA (Printing), Less than 53 dBA (Copying), Less than 26 dBA (Standby) 50,0 Standard : Average Cartrid High Yield : Average cartridge Yield 5,000 standard	 216 x 356 mm (8.5" x 14") HP, Label, Card, Thick, Bond 50-sheet 5"), Length : 148 ~ 356 mm (5.8" ~ 14") 16 characters (Max. 384 MB) ista Various Linux OS, Mac OS X 10.3~10.5 Ethernet 10/100BaseTX Less than 50 dBA (Printing), Less than 53 dBA (Copying), Less than 26 dBA (Standby) i00 pages mm (17.53" x 16.16" x 15.56") Kg (32 lbs) Idge Yield 2,000 standard pages. 	
Media Size Media Type ADF Capacity ADF Document Size GENERAL LCD Memory / Storage OS Compatibility Interface Noise Level Duty Cycle, Monthly Dimension (W x D x H) Weight (with CRU) CONSUMABLES	Plain, Thin, Recycled, C 30-sheet Width : 142 ~ 216 mm (5.6" ~ 8.5 2 line x 128 MB Windows 2000 / 2003 Server / XP / V Hi-Speed USB 2.0 Less than 49 dBA (Printing), Less than 53 dBA (Copying), Less than 26 dBA (Standby) 50,0 Hi-Speed Copying), Less than 26 dBA (Standby) Standard : Average Cartride High Yield : Average cartridge Yield 5,000 standard Declared cartridge yield in	 216 x 356 mm (8.5" x 14") HP, Label, Card, Thick, Bond 50-sheet 5"), Length : 148 ~ 356 mm (5.8" ~ 14") 16 characters (Max. 384 MB) ista Various Linux OS, Mac OS X 10.3~10.5 Ethernet 10/100BaseTX Less than 50 dBA (Printing), Less than 53 dBA (Copying), Less than 26 dBA (Standby) 100 pages nm (17.53" x 16.16" x 15.56") Kg (32 lbs) Ige Yield 2,000 standard pages. I pages. (Ships with 2,000 pages Starter Toner Cartridge 	
Media Size Media Type ADF Capacity ADF Document Size GENERAL LCD Memory / Storage OS Compatibility Interface Noise Level Duty Cycle, Monthly Dimension (W x D x H) Weight (with CRU) CONSUMABLES Yield	Plain, Thin, Recycled, C 30-sheet Width : 142 ~ 216 mm (5.6" ~ 8.5 2 line x 128 MB Windows 2000 / 2003 Server / XP / V Hi-Speed USB 2.0, Less than 49 dBA (Printing), Less than 53 dBA (Copying), Less than 26 dBA (Standby) 50,0 Hispeed Cartride High Yield : Average cartridge Yield 5,000 standard Declared cartridge yield in Single	 216 x 356 mm (8.5" x 14") HP, Label, Card, Thick, Bond 50-sheet 5"), Length : 148 ~ 356 mm (5.8" ~ 14") 16 characters (Max. 384 MB) ista Various Linux OS, Mac OS X 10.3~10.5 Ethernet 10/100BaseTX Less than 50 dBA (Printing), Less than 53 dBA (Copying), Less than 26 dBA (Standby) 00 pages nm (17.53" x 16.16" x 15.56") Kg (32 lbs) Ige Yield 2,000 standard pages. pages. (Ships with 2,000 pages Starter Toner Cartridge accordance with ISO/IEC 19752 	
Media Size Media Type ADF Capacity ADF Document Size GENERAL LCD Memory / Storage OS Compatibility Interface Noise Level Duty Cycle, Monthly Dimension (W x D x H) Weight (with CRU) CONSUMABLES Yield	Plain, Thin, Recycled, C 30-sheet Width : 142 ~ 216 mm (5.6" ~ 8.5 2 line x 128 MB Windows 2000 / 2003 Server / XP / V Hi-Speed USB 2.0, Less than 49 dBA (Printing), Less than 53 dBA (Copying), Less than 26 dBA (Standby) 50,0 Hispeed Cartride High Yield : Average cartridge Yield 5,000 standard Declared cartridge yield in Single	 216 x 356 mm (8.5" x 14") HP, Label, Card, Thick, Bond 50-sheet 5"), Length : 148 ~ 356 mm (5.8" ~ 14") 16 characters (Max. 384 MB) ista Various Linux OS, Mac OS X 10.3~10.5 Ethernet 10/100BaseTX Less than 50 dBA (Printing), Less than 53 dBA (Copying), Less than 26 dBA (Standby) 00 pages nm (17.53" x 16.16" x 15.56") Kg (32 lbs) Ige Yield 2,000 standard pages. I pages. (Ships with 2,000 pages Starter Toner Cartridge accordance with ISO/IEC 19752 e Cartridge 	
Media Size Media Type ADF Capacity ADF Document Size GENERAL LCD Memory / Storage OS Compatibility Interface Noise Level Duty Cycle, Monthly Dimension (W x D x H) Weight (with CRU) CONSUMABLES Yield Type Model Code	Plain, Thin, Recycled, C 30-sheet Width : 142 ~ 216 mm (5.6" ~ 8.5 2 line x 128 MB Windows 2000 / 2003 Server / XP / V Hi-Speed USB 2.0 Less than 49 dBA (Printing), Less than 53 dBA (Copying), Less than 26 dBA (Standby) 50,0 Hispeed USB 2.0 Windows 2000 / 2003 Server / XP / V Hispeed USB 2.0 Less than 49 dBA (Printing), Less than 53 dBA (Copying), Less than 26 dBA (Standby) 50,0 High Yield : Average cartridge Yield 5,000 standard High Yield : Average cartridge Yield 5,000 standard Declared cartridge yield in Singl MLT-D209S, MLT-D209L (M	 216 x 356 mm (8.5" x 14") HP, Label, Card, Thick, Bond 50-sheet 5"), Length : 148 ~ 356 mm (5.8" ~ 14") 16 characters (Max. 384 MB) ista Various Linux OS, Mac OS X 10.3~10.5 Ethernet 10/100BaseTX Less than 50 dBA (Printing), Less than 53 dBA (Copying), Less than 26 dBA (Standby) 00 pages nm (17.53" x 16.16" x 15.56") Kg (32 lbs) Ige Yield 2,000 standard pages. I pages. (Ships with 2,000 pages Starter Toner Cartridge accordance with ISO/IEC 19752 e Cartridge 	

Download from Www.Somanuals.com. All Manuals Search And Download.

SCX-4824FN



SCX-4824FN / 4828FN

Free Manuals Download Website <u>http://myh66.com</u> <u>http://usermanuals.us</u> <u>http://www.somanuals.com</u> <u>http://www.4manuals.cc</u> <u>http://www.4manuals.cc</u> <u>http://www.4manuals.cc</u> <u>http://www.4manuals.com</u> <u>http://www.404manual.com</u> <u>http://www.luxmanual.com</u> <u>http://aubethermostatmanual.com</u> Golf course search by state

http://golfingnear.com Email search by domain

http://emailbydomain.com Auto manuals search

http://auto.somanuals.com TV manuals search

http://tv.somanuals.com