

Specifications

Model		SCC-641(P)	SCC-643A(P)
Imaging Device	NTSC	1/4" Super HAD CCD 410K pixles	
	PAL	1/4" Super HAD CCD 470K pixles	
Effective Pixels		NTSC : 768(H)x494(V) / PAL : 752(H)x582(V)	
Scanning Method		2:1 Interlace	
Scanning Line	Horizontal	NTSC : 15.750Hz / PAL : 15.625Hz	
Frequency	Vertical	NTSC : 60Hz / PAL : 50Hz	
Synchronization Method		Internal/ Line lock	
Horizontal Resolution		480 TV Lines	
Signal Output		VBS 1.0Vp-p(75 ohm, composite)	
S/N Ratio		52dB	
Minimum Scene Illumination	Color	0.005(Sens up 128X,15IRE)Lux	
	B/W	-	0.0005(Sens up 128X,15IRE)Lux
Pan/Tilt	Manual Pan	Pan : 0.8°~90°/sec(64Step)	
	/Tilt Speed	Tilt : 0.8°~45°/sec(64Step)	
	Preset Pan/Tilt Speed	Pan : Max 240°/sec / Tilt : Max 150°/sec	
	Pan/Tilt Range	Pan : 360° Endless / Tilt : 0°~ 90°	
	Number of Preset	128 Presets	
	Number of Pattern	3 (30sec x 3)	
Lens	Zoom Ratio		220X (22X Optical Zoom, 10X Digital Zoom)
	Focal Length		3.6~79.2mm
	Aperature Ratio		F1.6(Wide), F3.8(Tele)
	Viewing Angle	Tele	2°3'(H) x 1°7'(V)
		Wide	47°9'(H) x 36°9'(V)
Functions	Sens Up		128X(Auto/Fix)
	Digital Effect		H-Mirror, Picture in Picture (D Zoom)
	White Balance		ATW/AWC/Manual
	BLC		On (zone setting, position designation)/ Off
	Privacy Zone		-
Input/Output	Image Output		BNC
	Remote Control		RS-485(Half duplex) / RS-422
	Address Range		1~128
	Alarm Input		4 NO/NC(5mA sink)
Operating Temperature		-10°C ~ +50°C	
Operating Humidity		Maximum 90% RH	
Power Requirement		AC24V	
Power Consumption		18W	
Weight		2.0Kg	
Dimensions		159.5mm(ø) x 177mm(D)	

Free Manuals Download Website

<http://myh66.com>

<http://usermanuals.us>

<http://www.somanuals.com>

<http://www.4manuals.cc>

<http://www.manual-lib.com>

<http://www.404manual.com>

<http://www.luxmanual.com>

<http://aubethermostatmanual.com>

Golf course search by state

<http://golfingnear.com>

Email search by domain

<http://emailbydomain.com>

Auto manuals search

<http://auto.somanuals.com>

TV manuals search

<http://tv.somanuals.com>