

# Split System Submittal Data



Building Life.

**System: 12KHS71 Indoor/Outdoor: KHS1271/CH1271**  
**Wall Mounted Heat Pump**

Job Name: \_\_\_\_\_  
 Location: \_\_\_\_\_  
 Engineer: \_\_\_\_\_  
 Submitted to: \_\_\_\_\_  
 Submitted by: \_\_\_\_\_  
 Reference: \_\_\_\_\_

Approval: \_\_\_\_\_  
 Date: \_\_\_\_\_  
 Construction: \_\_\_\_\_  
 Unit #: \_\_\_\_\_  
 Drawing #: \_\_\_\_\_



### General Data (at 115V)

Power	V/PH/Hz	115/1/60
Circuit Ampacity	(A)	20
Fuse Size, Max.	(A)	20

Compressor	DC Rotary Inverter	
No. used		1
R.L. Amps - L.R.	(A)	9.8/10.6-20
Crankcase Heater	(W)	20

Outdoor Unit		
Fan type		Propeller
Dia. (in.) - No. Speeds		15-3/4-1
Type Drive - No. Speeds		Direct - 3
No. Poles	(RPM)	8-750
No. Motors	(W)	30-1
CFM	(High)	1059
F.L. Amps	(A)	0.6

Coil Type	Aluminum Fin & Copper Pipe	
Fin Type - Pipe Type	Corrugated Plate - Inner Rifled	
Rows - F.P.I.		2-18.1
Face Area	(sq.ft.)	3.95
Tube Size	(in.)	5/16"

Indoor Unit		
Fan type		Cross Flow
Dia. & Length (in.) - No. Speeds	D3-11/6	L24-31/32-1
No. Speeds		3 & Auto
No. Poles	(RPM, High)	4-1250
No. Motors	(W)	14.8-1
CFM	(Hi/Med/Lo)	294/259/212
Indoor Sound Rating	(Hi) (dB-A)	36
F.L. Amps	(A)	0.346

Coil Type	Aluminum Plate Fin & Copper Tube	
Fin Type - Pipe Type	Slit Plate - Inner Rifled	
Rows - F.P.I.		2-19.5
Face Area	(sq.ft.)	2.02
Tube Size	(in.)	9/32"
Drain Connection Size	(in.)	23/32"

Refrigerant	R410A
Lbs. - R410a (outdoor unit)	2.43
Control	Electric Expansion Valve
Connection	Flare
Line Length, Max (ft.)	65
Lift Difference, Max (ft.)	23
Line Size	(in. O.D. Discharge) 1/4"
Line Size	(in. O.D. Suction) 3/8"

Dimensions	(in.)	H x W x D
Indoor Unit	(Uncrated) 11-7/32 x 32-15/32 x 7-7/16	
	(Crated) 13-25/32 x 35-7/16 x 10-1/32	
Outdoor Unit	(Uncrated) 21-9/16 x 28-11/32 x 10-7/16	
	(Crated) 23-5/8 x 33-11/16 x 14-1/4	

Weight	Indoor	Outdoor
Net	(lbs.) 19.8	77.2
Shipping	(lbs.) 24.3	83.8
Shipping Volume	(cu.ft.) 2.82	6.36

### Performance Data @ ARI Standard Conditions (230/208V)

Cooling		
Total Capacity	(BTU/H)	11,900 (3,000-11,900)
Sensible Capacity	(BTU/H)	9,100
Latent Capacity	(BTU/H)	2,800
SEER		17
Dehumidification	(Pints/H)	4.26
Amps	(A)	-/10.9 (2.5-10.9)
Power Inputs	(W)	-/1,090 (250-1,090)
Outdoor Sound Rating	(dB-A)	47

Heating		
Total Capacity	(BTU/H)	14,300 (3,000-14,300)
HSPF		9.3



## Free Manuals Download Website

<http://myh66.com>

<http://usermanuals.us>

<http://www.somanuals.com>

<http://www.4manuals.cc>

<http://www.manual-lib.com>

<http://www.404manual.com>

<http://www.luxmanual.com>

<http://aubethermostatmanual.com>

Golf course search by state

<http://golfingnear.com>

Email search by domain

<http://emailbydomain.com>

Auto manuals search

<http://auto.somanuals.com>

TV manuals search

<http://tv.somanuals.com>