



Nominal Capacity		600mAh	
Nominal Voltage		1.2V	
Charging Current	Standard	60mA	
	Quick	120mA	
	Fast	900mA	
Charging Time	Standard	14 to 16Hrs.	
	Quick	7 to 8Hrs.	
	Fast	about 1Hr.	
Ambient Temperature	Charge	Standard	0°C to +45°C [+32°F to 113°F]
		Quick	0°C to +45°C [+32°F to 113°F]
		Fast	0°C to +45°C [+32°F to 113°F]
	Discharge	-20°C to +60°C [-4°F to 140°F]	
		Storage	
Internal Impedance (Av.) (at 50% discharge)		9.5mΩ (at 1000Hz)	
Weight		18g/0.63oz	
Dimensions(D)×(H) (with tube)		17.0 <sup>0</sup> <sub>-0.5</sub> × 28.5 <sup>0</sup> <sub>-1</sub>	mm
		0.67 <sup>0</sup> <sub>-0.02</sub> × 1.12 <sup>0</sup> <sub>-0.04</sub>	inch

### Typical Characteristics


#### Charge




#### Discharge (at high rate)




#### Charge




#### Discharge (at high rate)



#### Discharge (at low rate)



#### Temperature (Charge & Discharge)



## Free Manuals Download Website

<http://myh66.com>

<http://usermanuals.us>

<http://www.somanuals.com>

<http://www.4manuals.cc>

<http://www.manual-lib.com>

<http://www.404manual.com>

<http://www.luxmanual.com>

<http://aubethermostatmanual.com>

Golf course search by state

<http://golfingnear.com>

Email search by domain

<http://emailbydomain.com>

Auto manuals search

<http://auto.somanuals.com>

TV manuals search

<http://tv.somanuals.com>