


SANYO Cadnica


Cell Type N-250AAAC Specifications




Nominal Capacity		250mAh	
Nominal Voltage		1.2V	
Charging Current	Standard	25mA	
	Quick	75mA	
	Fast	375mA	
Charging Time	Standard	14 to 16Hrs.	
	Quick	4 to 6Hrs.	
	Fast	about 1Hr.	
Ambient Temperature	Charge	Standard	0°C to +45°C [+32°F to 113°F]
		Quick	10°C to +45°C [+50°F to 113°F]
		Fast	0°C to +45°C [+32°F to 113°F]
	Discharge	-20°C to +60°C [-4°F to 140°F]	
Storage		-30°C to +50°C [-22°F to 122°F]	
Internal Impedance (Av.) (at 50% discharge)		24.0mΩ (at 1000Hz)	
Weight		11g/0.39oz	
Dimensions(D)×(H) (with tube)		10.5 $\begin{smallmatrix} 0 \\ -0.5 \\ -0.02 \end{smallmatrix}$ × 44.4 $\begin{smallmatrix} 0 \\ -1 \\ -0.04 \end{smallmatrix}$ mm 0.41 $\begin{smallmatrix} 0 \\ -0.02 \end{smallmatrix}$ × 1.75 $\begin{smallmatrix} 0 \\ -0.04 \end{smallmatrix}$ inch	

Typical Characteristics


Charge




Charge




Discharge (at low rate)




Discharge (at high rate)



Discharge (at high rate)



Temperature (Charge & Discharge)



Free Manuals Download Website

<http://myh66.com>

<http://usermanuals.us>

<http://www.somanuals.com>

<http://www.4manuals.cc>

<http://www.manual-lib.com>

<http://www.404manual.com>

<http://www.luxmanual.com>

<http://aubethermostatmanual.com>

Golf course search by state

<http://golfingnear.com>

Email search by domain

<http://emailbydomain.com>

Auto manuals search

<http://auto.somanuals.com>

TV manuals search

<http://tv.somanuals.com>