


Cell Type N-270AAS Specifications


Nominal Capacity		250mAh
Nominal Voltage		1.2V
Standard Charging Current		8.3mA
Charging Time		above 48Hrs.
Ambient Temperature	Charge	0°C to +80°C [+32°F to 176°F]
	Discharge	-20°C to +80°C [-4°F to 176°F]
	Storage	-30°C to +80°C [-22°F to 176°F]
Internal Impedance (Av.) (at 50% discharge)		36.0mΩ (at 1000Hz)
Weight		14g/0.49oz
Dimensions(D)×(H) (with tube)		14.5 ⁰ _{-0.5} × 30.3 ⁰ ₋₁ mm 0.57 ⁰ _{-0.02} × 1.19 ⁰ _{-0.04} inch

Typical Characteristics


Charge




Discharge (at very low rate)




Cell Capacity (at various discharge rate)




Discharge (at various temperature)



Discharge (at low rate)



Temperature (Charge & Discharge)



Free Manuals Download Website

<http://myh66.com>

<http://usermanuals.us>

<http://www.somanuals.com>

<http://www.4manuals.cc>

<http://www.manual-lib.com>

<http://www.404manual.com>

<http://www.luxmanual.com>

<http://aubethermostatmanual.com>

Golf course search by state

<http://golfingnear.com>

Email search by domain

<http://emailbydomain.com>

Auto manuals search

<http://auto.somanuals.com>

TV manuals search

<http://tv.somanuals.com>