

**TRC-6040**

## Desktop Microcassette Transcriber

- Microprocessor-Controlled for Fast and Accurate Operation
- Solenoid Transport Controls for Reliable Feather-Touch Operation with Reduced Mechanical and Electrical Noise to Ensure the Clearest Playback Possible for Transcription
- Cue Tone Index Search System Allows the User to Listen to Tape Contents at High Speed in Forward or Rewind for Quick Location of Recorded Materials in Private
- 3-Position Foot Control with Play, Automatic Variable Backspace and Fast Forward for Easy and Convenient Transcription Control as Well as to Maximize Transcription Efficiency
- High-Speed Erase Removes Recorded Materials Quickly; 60-Minute Tape in Only 110 Seconds
- 3-Digit LED Tape Counter Simplifies Location of Recorded Materials and Lighted Display Enhances Readability



### SPECIFICATIONS

|                                  |  |
|----------------------------------|--|
| <b>Model Number</b>              | <b>TRC-6040</b>                        |
| <b>Recording System</b>          | AC Bias                                |
| <b>Erasing System</b>            | DC Erase                               |
| <b>Tape Speed</b>                | 1"/sec, 0.5"/sec                       |
| <b>Fast Fwd. and Rewind Time</b> | 0.35% WRMS                             |
| <b>Wow and Flutter</b>           | 250-6300Hz                             |
| <b>Frequency Response</b>        | 40dB                                   |
| <b>S/N Ratio</b>                 | 700mW (max.)                           |
| <b>Output Power</b>              | AC Local Voltage                       |
| <b>Power Source</b>              | 2.6" Dia.                              |
| <b>Loudspeaker</b>               | Earphone Jack,                         |
| <b>Terminals</b>                 | Foot Switch Jack<br>8.7" x 1.8" x 6.3" |
| <b>Dimensions (WxHxD)</b>        | 1.6 lbs.                               |
| <b>Weight</b>                    | Headset, AC Adaptor, MC-60             |
| <b>Accessories</b>               | Tape, Foot Control                     |

#### SANYO Office Automation

21605 Plummer St.  
Chatsworth, CA 91311  
Phone: (818) 998-7322

www.sanyousa.com

**Microprocessor-Controlled** for Fast and Accurate Operation

**Solenoid Transport Controls** for Reliable Feather-Touch Operation with Reduced Mechanical and Electrical Noise to Ensure the Clearest Playback Possible for Transcription

**Cue Tone Index Search System** Allows the User to Listen to Tape Contents at High Speed in Forward or Rewind for Quick Location of Recorded Materials in Private

**3-Position Foot Control** with Play, Automatic Variable Backspace and Fast Forward for Easy and Convenient Transcription Control as Well as to Maximize Transcription Efficiency

**High-Speed Erase** Removes Recorded Materials Quickly; 60-Minute Tape Only 110 Seconds

**Variable Backspace Control** to Maximize Transcription Efficiency

**2-Speed Playback** Allows for Playback of 120 Minutes of Recorded Materials on a 60-Minute Tape

**Adjustable Volume and Tone Controls** to Optimize the Transcriber's Ability to Hear the Tape Clearly

**Adjustable Playback Speed** to Match Individual Typing Speed

**End-of-Tape Warning** Helps Avoid Loss of Materials and Time Wasted During Recording

**Full Auto Stop** in All Modes

**3-Digit LED** Tape Counter Simplifies Location of Recorded Materials and Lighted Display Enhances Readability

**Accessories** Include Foot Control, Headset, AC Adaptor and MC-60 Blank Microcassette Tape

### SPECIFICATIONS

|                                  |                            |
|----------------------------------|----------------------------|
| <b>Model Number</b>              | TRC-6040                   |
| <b>Recording System</b>          | AC Bias                    |
| <b>Erasing System</b>            | DC Erase                   |
| <b>Tape Speed</b>                | 1"/sec, 0.5"/sec           |
| <b>Fast Fwd. and Rewind Time</b> | 0.35% WRMS                 |
| <b>Wow and Flutter</b>           | 250-6300Hz                 |
| <b>Frequency Response</b>        | 40dB                       |
| <b>S/N Ratio</b>                 | 700mW (max.)               |
| <b>Output Power</b>              | AC Local Voltage           |
| <b>Power Source</b>              | 2.6" Dia.                  |
| <b>Loudspeaker</b>               | Earphone Jack,             |
| <b>Terminals</b>                 | Foot Switch Jack           |
|                                  | 8.7" x 1.8" x 6.3"         |
| <b>Dimensions (WxHxD)</b>        | 1.6 lbs.                   |
| <b>Weight</b>                    | Headset, AC Adaptor, MC-60 |
| <b>Accessories</b>               | Tape, Foot Control         |

Because its products are subject to continuous improvements, SANYO reserves the right to modify product design and specifications without notice and without incurring any obligations © 2000 SANYO Office Automation

# SANYO

Office Automation

21605 Plummer St.  
Chatsworth, CA 91311  
Phone: (818) 998-7322

www.sanyo-usa.com

## Free Manuals Download Website

<http://myh66.com>

<http://usermanuals.us>

<http://www.somanuals.com>

<http://www.4manuals.cc>

<http://www.manual-lib.com>

<http://www.404manual.com>

<http://www.luxmanual.com>

<http://aubethermostatmanual.com>

Golf course search by state

<http://golfingnear.com>

Email search by domain

<http://emailbydomain.com>

Auto manuals search

<http://auto.somanuals.com>

TV manuals search

<http://tv.somanuals.com>