PLC-XW250/200

XGA Ultraportable Multimedia Projector



ULTRA-COMPACT, FULLY PORTABLE XGA DESIGN

Not much larger than a laptop PC, the PLC-XW250/200 weighs less than 5.7 pounds and delivers true XGA picture quality in a versatile, go-anywhere system. Also the PLC- XW250/200 may be ceiling or inverse mounted for enhanced versatility.

COMPLETE EASY AUTO SET UP FUNCTION, SMART AUTO INPUT SEARCH AND AUTO VERTICAL KEYSTONE CORRECTION

PLC- XW250/200 provides "Auto Set Up Function" that corrects keystone shaped distortion by searching for an input signal and detecting projector incline, therefore reducing set up time. PLC- XW250/200 automatically compensates for keystone picture distortion. Auto Keystone Correction, Auto Input Search and Auto PC Adjustment make it a really smart projector.

Wired LAN (RJ-45) for projector control

This model is equipped with Wired LAN (RJ-45) that allows you to manage and control the projector via Network. It is possible to check the operating time of lamp and manage the warning notification by email. Power ON/OFF and switching of the input signal can be controlled. You can save a lot of time in manage and control.

Environment friendly power consumption in standby mode: 0.4w The power consumption is reduced in standby mode to 0.4w. Caring for the environment is required due to global warming and CO2 reduction. The standby power consumption is reduced by 84% compared to the previous model.

DUAL D-SUB15 INPUTS

The PLC-XW250/200 offers excellent flexibility via a pair of D-Sub 15 input terminals. Using an optional adapter cable, it can even accept component video signals. One of the D-Sub 15 terminals can even be switched between input and monitor output for greater programming flexibility.

BLACK BOARD / COLOR BOARD MODE

What could be more right for education? A black board mode. The PLC-XW250/200 are compatible with four variously colored (red, blue, green, and yellow) projection surfaces via 'Color Board Mode'. without a screen.





PRESENTATION TECHNOLOGIES 21605 Plummer Street Chatsworth, CA 91311 Ph: 888-337-1215 (toll-free) Fax: 818-717-2719 www.sanyoprojectors.com

Specifications

| Resolution | XGA |
|----------------------------|-------------------------------------------------------|
| Brightness (typical) | 2600(XW250) / 2200(XW200) ANSI lumens |
| Uniformity | 85% |
| Panel System | 0.55" TFT Poly x3 |
| Number of Pixels | 2,359,296 |
| Contrast Ratio (Full on / | 2,339,290 |
| off) | 500:1 |
| Image Size | 40" - 300" |
| Aspect Ratio | 4:3 |
| Projection Lamp (s) | 220W UHP |
| • | H sync : 15 ~ 100 kHz , |
| Scanning Frequency | V sync : 50 ~ 100 Hz |
| Dot Clock | 140MHz |
| Fan Noise | 29 dBA (Eco) |
| Voltage | 100V~240V |
| BTU Rating | 723(Eco) |
| Power Consumption | 212W (Eco) |
| . p | UXGA*/WXGA*/SXGA+*/SXGA*/XGA/SVGA/ |
| Input signal compatibility | VGA / MAC, 480i, 480p, 575i, 575p, 720p, 1035i and |
| . 5 | 1 080i (*:compression) |
| Color System | PAL / SECAM / NTSC / NTSC4.43 / PAL-M/ N |
| Projection Lens (inch) | F 2.00 - 2.15 f 0.72" - 0.87" |
| Throw Ratio | 1.62 - 1.92 |
| Throw Distance (feet) | 4.3' - 38.7' |
| Zoom / Focus | manual |
| Zoom Ratio | 1:1.2 |
| Up / Down Ratio | 6:1 |
| Digital Keystone | A. I. 20 I. A. A. I. A. |
| Correction | Auto ±30 deg (Vertical) |
| Digital Zoom | 16x - 1/4x |
| Speaker Output | 1W |
| Weight (lbs.) | 5.5 lbs |
| Dimensions (inch) W,H,D | 13.1" x 3.4" x 9.7" |
| Replacement Lamp | 610 345 2456 |
| Replacement Remote | 645 099 3213 |
| | D-sub15 x 1 : Analog RGB Input |
| Computer Terminal | (Component and S-video input with conversion cable) |
| | D-sub15 x 1 : Analog RGB Input or Monitor out |
| Video Terminal | RCA x 1 : Composite video |
| Audio | Mini-Jack (stereo) x 1 : Input (for Computer & Video) |
| | Mini-Jack (stereo) x 1 : Output (variable audio out) |
| Communication Terminal | RJ-45 (LAN) D-sub 9pin (RS 232 C) |
| Included Accessories | Quick reference guide, Owner's manual (CD-ROM), |
| | CD-ROM read me note, CD-ROM (PJ-Net Manager |
| | application software), PIN code Label, Lamp |
| | replacement label, UL cable card, Warranty card, |
| | Power cord, Remote control, AAA Battery x 2, Lens |
| Ontional Assessment | cap, Strap for lens cap, VGA cable |
| Optional Accessories | POA-CACOMPVGA, POA-CAVGAS, POA-CASCART |
| User Maintenance | Clean air filters, replace lamp assembly |
| Warranty | Three years parts and labor; 90 days original lamp; |
| ····· | Quick Repair Program under warranty |

Because its products are subject to continuous improvement, SANYO reserves the right to modify product design and specifications without notice and without incurring any obligations.



Rear Back Panel

Free Manuals Download Website

http://myh66.com

http://usermanuals.us

http://www.somanuals.com

http://www.4manuals.cc

http://www.manual-lib.com

http://www.404manual.com

http://www.luxmanual.com

http://aubethermostatmanual.com

Golf course search by state

http://golfingnear.com

Email search by domain

http://emailbydomain.com

Auto manuals search

http://auto.somanuals.com

TV manuals search

http://tv.somanuals.com