

# CINEMA ULTRA II LCR AND ULTRA II SUR

## CINEMA ULTRA II LCR AND CINEMA ULTRA II SUR

Enjoy unprecedented home theater and multi-channel music performance from in-wall speakers with the new Sonance Cinema Ultra II LCR and SUR in-wall speakers. Both speakers carry THX Ultra II Certification to provide superior 7.1-channel Surround EX home theater performance (not to mention best in class 5.1-channel performance)!

The Cinema Ultra 2 LCR (sold 1 each) is perfect for the front Left, Center and Right channels in a home theater system. The LCR features a rotatable midrange tweeter array for directional sound field optimization. The Cinema Ultra 2 SUR (sold in pairs) provides a spacious sound field with superior polar response by incorporating a rotating midrange / tweeter array so you can adjust the sound field for best diffuse surround sound (e.g. deflecting sound field off of walls, etc).

In developing both the Cinema Ultra 2 LCR and SUR, Sonance engineers have taken great steps to insure superior performance regardless of wall cavity variances by including an integrated backbox and integrated mounting system (not to mention installation is a breeze!) The Cinema Ultra 2 LCR and SUR also feature low resonance MDF baffles for peak performance.

## FEATURES & SPECIFICATIONS



### Features:

- THX Ultra II certified
- Integrated back box
- Integrated mounting system, Rotolock®
- Low profile flat grilles

### Specifications:

#### Cinema Ultra 2 LCR

Tweeter: 3/4" (19mm) silk dome, shielded magnet  
 Midrange: Two - 3.0" (76mm) one piece black aluminum cones with rubber surrounds, shielded magnets  
 Woofer: 8" (203mm) one piece black aluminum cone with a rubber surround, shielded magnet  
 Frequency Response: 70Hz - 20kHz +/- 3dB  
 Impedance: 6 ohms nominal, 4 ohms minimum  
 Power Handling: 5 - 200 Watts  
 SPL: 90 dB  
 Grille: Aluminum  
 Adjustments : Rotating Midrange / Tweeter Array  
 Dimensions (W x H x D): 11-9/16" x 20-1/4" x 3-7/8"  
 (294mm x 514mm x 98mm)  
 Cutout Dim (W x H): 10-1/4 x 18-3/4"  
 (260mm x 476mm)  
 Shipping Weight: 18 lbs (8.2 KG) each  
 Sold 1 Each

- Low resonance MDF baffle
- Rotating midrange tweeter array on LCR and SUR
- Midrange and woofer feature low mass one piece cones

#### Cinema Ultra 2 SUR

Tweeter: Two - 3/4" (19mm) silk domes  
 Midrange: Two - 3.0" (76mm) one piece black aluminum cones with a rubber surround  
 Woofer: 8" (203mm) one piece black aluminum cone with a rubber surround  
 Frequency Response: 40Hz - 20kHz +/- 3dB  
 Impedance: 6 ohms nominal, 4 ohms minimum  
 Power Handling: 5 - 200 Watts  
 SPL: 90 dB  
 Grille: Aluminum  
 Adjustments: Rotating Midrange / Tweeter Array  
 Dimensions (W x H x D): 11-9/16" x 20-1/4" x 3-7/8"  
 (294mm x 514mm x 98mm)  
 Cutout Dim (W x H): 10-1/4 x 18-3/4"  
 (260mm x 476mm)  
 Shipping Weight: 29 lbs (13.2 KG) per pair  
 Sold in Pairs



The Leader in Architectural Audio™

[www.sonance.com](http://www.sonance.com)

Sonance • 212 Avenida Fabricante • San Clemente, CA 92672-7531 • (800) 582-7777 (949) 492-7777 • FAX (800) 538-5151 (949) 361-5151  
 ©2003 Sonance, all rights reserved. 8.03

## Free Manuals Download Website

<http://myh66.com>

<http://usermanuals.us>

<http://www.somanuals.com>

<http://www.4manuals.cc>

<http://www.manual-lib.com>

<http://www.404manual.com>

<http://www.luxmanual.com>

<http://aubethermostatmanual.com>

Golf course search by state

<http://golfingnear.com>

Email search by domain

<http://emailbydomain.com>

Auto manuals search

<http://auto.somanuals.com>

TV manuals search

<http://tv.somanuals.com>