

Hi-Scan
1080i

Image not available.

DRC Digital
Reality
Creation **CineMotion**
reverse 3-2 pull down technology**TruSurround™**
with **SRS** **MID** Multi
Image
Driver**HDMI™**
HIGH-DEFINITION MULTIMEDIA INTERFACE

- 16:9 Hi-Scan 1080i™ Display
- HD MICROFOCUS™ CRT and Lens System
- DRC™ (Digital Reality Creation™) MultiFunction Circuitry
- MID™ X (Multi Image Driver X) Circuitry
- CineMotion® Reverse 3-2 Pulldown Technology
- Twin-View™ Two Tuner Picture and Picture
- 3 D Digital Comb Filter
- Flash Focus® Auto and Manual Convergence

HD MICROFOCUS™ CRT and Lens System incorporates smaller phosphor particles and a thinner phosphor layer than Sony's previous MICROFOCUS picture tubes, to achieve a 28% reduction in beam spot size. This translates directly into sharper focus, higher contrast and a brighter image, for a picture of stunning clarity.

DRC™ Digital Reality Creation™ Multi-function Circuitry analyzes a 480i NTSC image and creates a digital bit mapped pattern in real time. The original NTSC signal is mapped in real time, replaced with an HD representative, and then discarded. Because DRC™ processes video signals in real time, it creates an image with 4X the density of the original signal. Resolution is increased both vertically and horizontally.

KP-51/57WS520

Hi-Scan® Projection Television

Features

Video

- Auto Channel Program
- Caption Vision (CC)
- Channel Label
- Channel Skip/Add
- Clock/Timer Two Event
- Energy Star® Compliant
- Favorite Channel With Preview
- Picture Freeze
- Picture Jump
- On Screen Display (English/Spanish/French)
- Program Palette™ Presets (Vivid/Movie/Standard/Sports)
- Scrolling Channel Index™ System
- Sleep Function
- Speed Surf™ Channel Selection
- V Chip Parental Control
- Video Label
- Wide Mode (Normal/Full/Zoom/Wide Zoom)
- XDS (Extended Data Service)
- Manual/Auto Flash Focus™ Convergence
- Auto Pedestal Clamp
- Auto White Balance
- Dynamic Focus™ Circuitry
- Dynamic Picture™ Processor Circuitry
- Auto 16:9 Enhanced Mode
- ID1 Detection (Auto)
- Trinitone® Color Temperature

Audio

- Auto SAP
- MTS Stereo
- Steady Sound® Auto Volume Control With BBE® Audio Effect
- Auto Mute (Tuner)
- Audio Output (Variable/Fixed)
- TruSurround® SRS® Audio
- 2 Speaker System (20W X 2)

Specifications

General

- Power Requirements AC 120V 60Hz
- Power Consumption In Operation: 260W
- In Standby: <1W

- KP-51WS520: 171 lbs. 15.3oz (78 kg)
- KP-57WS520: 195 lbs. (88.5 kg)
- KP-51WS520: 47 1/8 " x 53 1/2" x 25 3/4" (1194 x 1325 x 650mm)
- KP-57WS520: 52 1/4 " x 54 1/4" x 27 1/4" (1326 x 1377 x 675mm)

UPC Codes

- TBD

©2004 Sony Electronics Inc. All rights reserved. Features and specifications are subject to change without notice. All trademarks referenced herein are trademarks of Sony or their respective owners.

SONY

Sony Electronics Inc.
1 Sony Drive
Park Ridge, NJ 07656
For more information:

<http://www.sony.com/dn>

Supplied Accessories

- Instruction Manual
- Remote Control
- AA Battery (2)

Weights & Measures

Free Manuals Download Website

<http://myh66.com>

<http://usermanuals.us>

<http://www.somanuals.com>

<http://www.4manuals.cc>

<http://www.manual-lib.com>

<http://www.404manual.com>

<http://www.luxmanual.com>

<http://aubethermostatmanual.com>

Golf course search by state

<http://golfingnear.com>

Email search by domain

<http://emailbydomain.com>

Auto manuals search

<http://auto.somanuals.com>

TV manuals search

<http://tv.somanuals.com>