

speco technologies™

17" Color LCD A/V Monitor with TV Tuner & Remote Control

Built-in TV Tuner



Includes remote control

VM-TV17LCD

This 17" color active matrix TFT liquid crystal display provides a superior quality picture with a depth of less than 3 inches. The VM-TV17LCD includes a TV tuner and has a multitude of inputs including A/V, antenna/cable, VGA and S-Video.

Features

- Built-in TV tuner with IR remote control
- High contrast color TFT LCD display supports resolution up to 1280 x 1024 @75Hz
- Compatible with IBM VGA, IBM SXGA and Macintosh standards
- Imbedded audio system provides excellent sound performance
- A/V, S-Video, VGA and antenna/cable inputs
- Power management system conforms to VESA DPMS standards
- Supports DDC 1/2B for Plug & Play compatibility
- Advanced OSD control for picture quality adjustment
- Detachable stand for wall-mounting applications (accessory mount required)

Package Includes:

17" TFT LCD TV/Monitor with stand	Built-in TV tuner
Multi-function remote control	15 pin D-sub signal cable
RCA sound card cable	AC power cable
Power adapter	User's manual
Warranty	

Specifications subject to change

For more information contact us at:

Speco Technologies 200 New Highway, Amityville, NY 11701 Web: www.specotech.com
Toll Free: 1-800-645-5516 In Metro NY: 631-957-8700 Fax: 631-957-9142 or 631-957-3880



VM-TV17LCD

17" Color LCD A/V
Monitor with TV Tuner &
Remote Control

Specifications

Max Resolution	1280(H) x 1024(V) (SXGA)
LCD Display	17" Active Matrix TFT LCD Panel
Pixel Pitch	0.264(H) x 0.264(V) mm
Contrast Ratio	400:1
Brightness	350 cd/m2
Response Time	Tr 15ms; Tf 10ms
Display Color	16.777M
Angle Viewing:	
Left/Right	±85°
Up/Down	±85°
PC Interface	RGB analog or digital, 0.7v peak to peak
Video Sync	TTL positive or negative
Display Mode	TV, A/V, VGA, SVGA, XGA, SXGA
Frequency	(Horizontal) 31.5-80KHZ (Vertical) 56-75 HZ
Signal Connectors	A/V, S-Video, "F" connector for TV, D-sub 15-pin
Front Controls	Auto adjust with LED, OSD Menu, +/- Adjustment
OSD Menu	Contrast, Brightness, Auto Adjust, Clock, Phase, H-Position, V-Position, Input: (PC, TV, A/V, S-Video)
Power Adapter Included	AC Input: 100-240V~1.8A, 50-60Hz DC Input: 12V/4.0A
Operating Conditions	Temperature: 32°F to 122°F Humidity: 20% ~ 95%
Certification	BSMI, FCC (DOC), CE-B, UL, TUV/GS
Weight	11 lbs.
Dimensions	16.25"(H) x 16.30"(V) x 7.68"(D)
Remote Control	Multi function remote control included



For more information contact us at:

Speco Technologies 200 New Highway, Amityville, NY 11701 Web: www.specotech.com
Toll Free: 1-800-645-5516 In Metro NY: 631-957-8700 Fax: 631-957-9142 or 631-957-3880

Free Manuals Download Website

<http://myh66.com>

<http://usermanuals.us>

<http://www.somanuals.com>

<http://www.4manuals.cc>

<http://www.manual-lib.com>

<http://www.404manual.com>

<http://www.luxmanual.com>

<http://aubethermostatmanual.com>

Golf course search by state

<http://golfingnear.com>

Email search by domain

<http://emailbydomain.com>

Auto manuals search

<http://auto.somanuals.com>

TV manuals search

<http://tv.somanuals.com>