

B/W Extension Speaker Camera



CVC-225ES

Features	Benefits
Concealed Camera	Discreet installation for sensitive areas
Working Speaker	Helps conceal the fact that there is a camera installed
Fully Assembled	Quick installation without the need for adjustments

Specifications

Dimensions	2.5"L x 4.25"W x 4.25"H
Electronic Shutter	Auto 1/50-1/100,000 second
Housing	Black composite plastic housing
Humidity	Within 95% RH
Image Device	1/3" B/W CCD image sensor
Lens	3.6mm wide angle lens, Hor. 72°, Vert. 53°
Minimum Illumination	0.02 lux
Number of Pixels	512 horizontal x 492 vertical
Operating Temperature	14°F - 122°F
Outputs	Video - RCA with BNC adapter, Power, - DC jack
Power Consumption	150 mA
Power Requirements	Regulated 12V DC power supply included (UL and CSA listed)
Resolution	Horizontal 420 lines
Scanning Frequency	Horizontal 15.75 kHz, Vertical 60 Hz
Scanning System	EIA standard 525 lines 60 fields/second
Video Output Level	1.0 Vp-p 75 ohm
Video S/N Ratio	Greater than 48 dB
Weight	2 lbs.

Package Includes:

CVC-225ES	Instructions	Mounting Hardware
Power Supply	Warranty	

Specifications subject to change

For more information contact us at:

Speco Technologies 200 New Highway, Amityville, NY 11701 Web: www.specotech.com
 Toll Free: 1-800-645-5516 In Metro NY: 631-957-8700 Fax: 631-957-9142 or 631-957-3880

CVC-225ES

Free Manuals Download Website

<http://myh66.com>

<http://usermanuals.us>

<http://www.somanuals.com>

<http://www.4manuals.cc>

<http://www.manual-lib.com>

<http://www.404manual.com>

<http://www.luxmanual.com>

<http://aubethermostatmanual.com>

Golf course search by state

<http://golfingnear.com>

Email search by domain

<http://emailbydomain.com>

Auto manuals search

<http://auto.somanuals.com>

TV manuals search

<http://tv.somanuals.com>