

CVC-185DC

B/W Dome Camera



Our 1/3" B/W CCD dome camera with smoked housing can be mounted on the ceiling and offers unobtrusive surveillance. It can be rotated 360 degrees for maximum viewing angle and tilted +/-90°. It features .02 lux sensitivity with 420 lines of resolution and a 3.6mm wide angle lens with built-in electronic shutter. A 12V DC power supply is included.

Specifications

Resolution	420 line horizontal
Image Device	1/3" B/W CCD image sensor
Minimum Illumination	.02 lux
Electronic Shutter	Auto 1/60-1/100,000 seconds
Lens/Angle of View	3.6mm wide angle lens, Hor. 72°, Vert 53°
Lens Options	2.5, 6, 8, 12mm, 16mm
Video Output Level	1.0 Vp-p, 75 ohm
Video S/N Ratio	Greater than 48 dB
Output/Connections	Video - BNC, Power - DC jack
Operation Temperature	14° F to 113° F
Power Consumption	110 ma
Power Requirements	Regulated 12V DC power supply included (UL and CSA listed)
Scanning Frequency	Hor. 15.75 kHz Vert. 60 Hz
Scanning System	EIA standard 525 lines 60 fields/second
Dimensions	4"W x 2.5"H
Housing	ABS plastic/black
Weight	10.5 oz

Specifications subject to change



For more information contact us at:

Speco Technologies 200 New Highway, Amityville, NY 11701 Web: www.specotech.com
Toll Free: 1-800-645-5516 in Metro NY: 631-957-8700 Fax: 631-957-9142 or 631-957-3880

Free Manuals Download Website

<http://myh66.com>

<http://usermanuals.us>

<http://www.somanuals.com>

<http://www.4manuals.cc>

<http://www.manual-lib.com>

<http://www.404manual.com>

<http://www.luxmanual.com>

<http://aubethermostatmanual.com>

Golf course search by state

<http://golfingnear.com>

Email search by domain

<http://emailbydomain.com>

Auto manuals search

<http://auto.somanuals.com>

TV manuals search

<http://tv.somanuals.com>