

speco technologies®

Platinum Series 60 & 120 Watt 70V Stereo Professional Amplifiers



PL-60SA & PL-120SA

Features

The UL listed, 60 watt PL-60SA and 120 watt PL-120SA amplifiers destroy the barriers of high-end, full stereo sound for commercial applications, making 70-volt stereo sound a reality. Incorporating both left and right channel RCA inputs and left and right 70-volt speaker line outputs, Speco Technologies raises the bar for sound fidelity in commercial establishments that demand it because of premium content subscription services or requirement for better sound atmosphere.

Even more innovative is the selector switch that ties into each input (XLR microphone, left and right channel RCA inputs and telephone paging inputs) that allows each source to be sent selectively to the right, left or both channel speaker output lines thus making this a multi-source, multi-zone unit.

Feature rich including XLR MIC connector with priority paging, RCA input terminals, 600-ohm input for telephone paging, RCA and Music on Hold outputs and 24V DC input for backup power supply. This amplifier series is supported by a 5-year limited warranty and shows why Speco Technologies is an innovator in the commercial sound marketplace.

Specifications

PL-60SA Specifications

- 60 Watts RMS
(2 Lines of Speaker Outputs;
30 Watts per channel)
- XLR Connector with priority paging
- Left and right channel pair RCA inputs
- RCA pair output
- 600-ohm telephone paging input
- Music on Hold feature
- 24V DC battery input for emergency power
- Separate volume controls for auxiliary
by each channel
- Master volume and bass and treble controls
- 3.5" H x 16.9" W x 11.6" D
- UL & CSA listed

PL-120SA Specifications

- 120 Watts RMS
(2 Lines of Speaker Outputs;
60 Watt per channel)
- XLR Connector with priority paging
- Left and right channel pair RCA inputs
- RCA pair output
- 600-ohm telephone paging input
- Music on Hold feature
- 24V DC battery input for emergency power
- Separate volume controls for auxiliary
by each channel
- Master volume and bass and treble controls
- 3.5" H x 16.9" W x 11.6" D
- UL & CSA listed

Specifications subject to change

For more information contact us at:

Speco Technologies 200 New Highway, Amityville, NY 11701 Web: www.specotech.com
Toll Free: 1-800-645-5516 In Metro NY: 631-957-8700 Fax: 631-957-9142 or 631-957-3880

Free Manuals Download Website

<http://myh66.com>

<http://usermanuals.us>

<http://www.somanuals.com>

<http://www.4manuals.cc>

<http://www.manual-lib.com>

<http://www.404manual.com>

<http://www.luxmanual.com>

<http://aubethermostatmanual.com>

Golf course search by state

<http://golfingnear.com>

Email search by domain

<http://emailbydomain.com>

Auto manuals search

<http://auto.somanuals.com>

TV manuals search

<http://tv.somanuals.com>