

INSTALLATION INSTRUCTIONS


CERAMIC WASHERLESS TWIN HANDLE KITCHEN FAUCET With or Without Spray



Use this diagram to familiarize yourself with the various parts of the faucet assembly. Make sure you have all the illustrated parts before you begin installation.

If you are putting in a new sink, it is easier to mount the faucet, drain and any other accessories **before** installing the sink into the countertop.

- Observe all local plumbing codes.
- Carefully inspect the valve parts for any damage.
- Flush all piping thoroughly before installing.
- Shut off hot & cold water supplies.
 - Do not use plumber's putty or thread sealants on mounting nuts or coupling nuts.



E045000

5/99




TWIN HANDLE KITCHEN FAUCET

Items you need

NOTE: OTHER TOOLS MAY BE NEEDED TO REMOVE OLD FAUGET


Adjustable wrench, Phillips and flathead screwdrivers, and Teflon tape.

Remove old faucet




Turn off both water supplies.

terriove old raucei



If your faucet has a spray, place hole guide down through hole at extreme right of sink top. Add mounting nut to underside and FINGER tighten firmly.

Install faucet



4 Position faucet assembly on sink with shanks extending through their appropriate holes.



Flush lines


Turn on water supplies and check for leaks. With faucet off remove aerator. Turn on hot and cold to flush lines and faucet. Operate spray. Turn off faucet and replace aerator

OPTIONAL MATERIALS:


- Supply stops (2) Some installations may require stops to be installed.
- Supply tubing (2) and fittings will need to be provided.

NOTE: Do not use supply tubes w/metal formed ends with non-metallic shanks.


You may need the above materials.



2 Disconnect supply lines.



Insert spray hose down through hose guide and up through center hole in sink and putty plate.



6 Connect hot & cold supply lines onto faucet shanks with coupling nuts. FINGER tighten securely.

5 Fasten faucet to sink with

mounting nuts supplied.

spray outlet by rotating faucet NOTE: Do not use supply tubes body. Tighten securely with w/metal formed ends with nonwrench. metallic shanks. Download from Www.Somanuals.com. All Manuals Search And Download.



Position putty plate. Apply Teflon tape to spray outlet on body. Attach spray hose to spray outlet by rotating faucet body. Tighten securely with wrench.

Sterling Limited Lifetime Warranty

Sterling Plumbing Group, Inc. ("Sterling") warrants this faucet to be free of manufacturing defects and to be drip free for as long as you own your home. Damage due to improper installation, maintenance or handling are not considered manufacturing defects and are not covered by this warranty. Labor, shipping and installation costs or other charges incidental to warranty service are to be borne by the original purchaser. This warranty is valid for the original purchaser only.


Sterling will, at its election, repair or replace a faucet where Sterling's inspection discloses any such defects occurring in normal residential usage.

To obtain warranty service return the defective part(s) to your cooperating retail seller or send them to our Customer Service Department, P.O. Box 427, Sheridan, AR 72150. Refer any questions to our Customer Service Department at 1-800-245-2207.


IMPLIED WARRANTIES INCLUDING THAT OF MERCHANTABILITY AND FIT-NESS FOR A PARTICULAR PURPOSE ARE EXPRESSLY LIMITED TO ONE YEAR FROM DATE OF PURCHASE. STERLING DISCLAIMS ANY RESPONSIBILITY FOR SPECIAL, INCIDENTAL OR CONSE-QUENTIAL DAMAGES. Some states do not allow limitations on how long an implied warranty lasts, or the exclusion or limitation of special, incidental or consequential damages, so these limitations or exclusions may not apply to you. This warranty gives you special legal rights. You may also have other rights which vary from state to state

This is our exclusive written warranty.

For more information on Sterling Faucets, please call 1-800-STERLING.



Basin wrench for removing old faucet.



Remove mounting nuts, lift off faucet.



Free Manuals Download Website

http://myh66.com

http://usermanuals.us

http://www.somanuals.com

http://www.4manuals.cc

http://www.manual-lib.com

http://www.404manual.com

http://www.luxmanual.com

http://aubethermostatmanual.com

Golf course search by state

http://golfingnear.com

Email search by domain

http://emailbydomain.com

Auto manuals search

http://auto.somanuals.com

TV manuals search

http://tv.somanuals.com