

Model 2310HD

LCD Screen	23-inch diagonal TFT Active Matrix
Resolution	1366 x 768 WXGA
Aspect Ratio	16:9
Active Area	508.1 x 285.7 mm
Contrast Ratio	700:1
Response Time	8 milliseconds
Viewing Angle	160° by 140°
Input Connectors:	Antenna/CATV (NTSC, ATSC, QAM)
НДМІ	HDMI Input x1
Video Composite	S-Video x1 and Composite Video x1 L/R Audio Inputs x2
Video Component	YCbCr/YPbPr x1 (supports HDTV inputs at 480i, 480P, 567i, 576P, 720P and 1080i) and audio L/R channels x1
PC	15-pin D-sub VGA
RS232 Serial	Full-featured command set with discrete on/off, input select and volume control
Input Power	100-240 VAC, 50-60 Hz 2.2A Max
Audio	10-watt x 2 channels, water-resistant speakers L/R Audio output connector inside rear cover
Operating Temp.	-24° to 122° F. (-31° to 50° C.) *
Non-op. Temp. (Off-mode with power applied)	-24° to 140° F. (-31° to 60° C.)
Accessories Included	Water-resistant remote control with lithium battery Removable table top stand
TV Dimensions	23.51 in. W x 16.27 in. H x 4.90 in. D
Weight	22 lbs., 25 lbs. with table top stand
Shipping Dimen- sions	30.31 in. W x 19.49 in. H x 8.86 in. D
Shipping Weight	28 lbs.
Warranty	One-year, in-factory, parts and labor

^{*}Temperature range is for operation in shaded location.



Model 2310HD

Super Bright 23" LCD Screen, HD Ready

All-weather enclosure protects internal components from rain, dirt, insects and scratches

Dual-fan airflow system keeps unit cool and dry in temperatures up to 122 degrees F.


Internal thermostatically-controlled heater protects TV in temperatures as low as -24 degrees F.

Innovative watertight cable entry system with passthrough design keeps cables dry and allows for easy hook-ups

Optional wall mounts and deck planter poles are weatherized and include stainless steel hardware

SunBriteTV Model 2310HD

(All dimensions are in inches)



TV Dimensions are: 23.51 in. W x 16.27 in. H x 4.90 in. D

Height dimension with table top stand is 17.14 in. TV with optional wall mount measures 7.60 in. when folded flush against the wall.

Optional Accessories

SB-CM20	Ceiling mount with tilt and swivel includes adjustable extension column that provides 5" to 11" above unit to ceiling. Also includes 4" x 4" designer ceiling
	plate. Meets VESA standards.
SB-WM23	Articulating wall mount with tilt, swivel, pan and extends up to 9″ from wall. Meets VESA standards.
SB-DP20X	Deck/Planter pole (requires purchase of wall mount). Special order item.
SB-FMT23	RadioFM™ transmits audio from TV to FM radio
SB-DC23	OutdoorTV dust cover

Specifications may be subject to change.

866.357.8688

www.sunbritetv.com

5069 Maureen Lane, Unit A • Moorpark, CA 93021 Patent pending. All rights reserved. (C) 2008 SunbriteTV LLC

Free Manuals Download Website

http://myh66.com

http://usermanuals.us

http://www.somanuals.com

http://www.4manuals.cc

http://www.manual-lib.com

http://www.404manual.com

http://www.luxmanual.com

http://aubethermostatmanual.com

Golf course search by state

http://golfingnear.com

Email search by domain

http://emailbydomain.com

Auto manuals search

http://auto.somanuals.com

TV manuals search

http://tv.somanuals.com