



DVR4-Pro-Net™

Networkable 4 Channel DVR



Your home, office & business safety net!





Swann



- Networkable DVR for remote viewing over the web
- Set & forget with pre-installed, 160GB hard drive
- State of the art features including motion detection, alerts, on-screen programming
- Nannycam, monitor office, oversee yard, deter theives & more
- High resolution MPEG4 switchable to MIPEG video format

160GB HDD included

MPEG4/MJPEG DVR Technology

• Compression format providing crystal clear images with real time performance

Multiplex

• Allow live display, record, playback, backup and network operation at the same time

Long-Recording Hours

• 500GB HDD can record more than 170 days (4CH, CIF Best Quality, 15IPS)

Backup Function

• Support network remote recording & backup

Remote Surveillance

- Remote surveillance with the licensed software AP and IE browser
- Web surveillance with 5 users simultaneously

High Quality yet Unbeatable Value!

Intelligent Motion Trigger Recording

- With advanced settings for motion detection, scheduled motion detection recording (4 different adjustable factors for the motion detection sensitivity) and convenient search function, customized security environment is achieved
- Alarm triggered recording will send alerts with images to the designated e-mails and FTP address
- Support pre-alarm recording (8Mb)

Covert Recording

• A mask replaces the live image with a blank screen, and the monitor shows nothing but recording is still on

AV Support

- Support I audio-in, I audio-out to record sounds
- Support VGA converter (optional)

General

- Support multi-language OSD
- System auto recovery after power reconnected
- Support daylight-saving function
- Support manual / timer / motion / alarm / remote recording functions
- Watermark function ensures authentication of the recorded images
- Support TCP/IP, PPPoE, DHCP and DDNS network connection





DVR4-Pro-Net™

Networkable 4 Channel DVR

Your home, office & business safety net!





Baby Sitters



Entrance









Lobby







Product Specifications Video System: Video Compression Format: Video Input:

Video Loop Out:

Video Output:

Maximum Recording Rate

Adjustable Recording Speed

Image Quality Setting Hard Disk Storage

HDD Quick Cleaning

Recording Mode Refresh Rate Audio I/O Motion Detection Area Motion Detect Sensitivity

Pre-alarm Recording Backup Device

NTSC / PAL (switchable) Frame: MIPEG; CIF: MPEG4

4 Channels

Composite video signal I Vp-p 75Ω BNC

Composite video signal I Vp-p 75Ω BNC

Main Monitor Output:

Composite video signal I Vp-p 75Ω BNC

Call Monitor Output:

Composite video signal I Vp-p 75Ω BNC Frame: 720×480 pixels with 30 IPS <NTSC> / 720×576 pixels with 25 IPS

<PAI>

CIF: 352×240 pixels with 120 IPS <NTSC> / 352×288 pixels with 100 IPS

<PAL>

Frame: 30, 15, 7, 3 IPS < NTSC> / 25, 12, 6, 3 IPS < PAL>

CIF: 120, 60, 30, 15 IPS < NTSC> /

100, 50, 25, 12 IPS < PAL> Best, High, Normal and Basic

IDE type, ATA66, supported HDD*I, support HDD capacity over 400GB Quick clean up the "index system"

of the recorded files. 250GB under 2 seconds

Manual / Timer / Motion / Alarm / Remote 120 IPS for NTSC / 100 IPS for PAL I audio input, I audio output (Mono)

16 × 12 grids per camera for all channels 4 adjustable variables with precise calculation

for motion detection Yes (8Mb)

Network remote backup

Web Transmitting / Compression Format Ethernet

Web Interface Remote Alarm Notification

Network Connection

PTZ control

Dwell Time (Sequential Channel Switch)

Alarm I/O

Digital Zoom

Key Lock

Video Loss Detection

Camera Title Video Adiustable

Date Display Format

Power Source

Power Consumption

Operating Temperature Dimensions (mm)

System Recovery

Optional Peripheral

Package Contents

- 4 x Security Stickers
- Manual
- Power Supply • BNC to RCA Cable
- BNC Connecters

Motion IPEG

10/100 Base-T. Support remote control and

live view via Ethernet

Support licensed software AP and IE browser

E-mail images, and upload images to

FTP site's specific account

Support TCP/IP, PPPoE, DHCP and DDNS function

Support PELCO-D protocol

Programmable with adjustable dwell time

4 inputs. I output

2x digital zoom (live mode)

Support up to 6 letters

Hue / Color / Contrast / Brightness

YY/MM/DD, DD/MM/YY, MM/DD/YY, and Off

DC 19V

10°C~ 40°C (50°F~104°F)

343mm (W) \times 59mm (H) \times 223mm (D)

System auto recovery after power reconnected

VGA converter

Installed Seagate HDD carries 5 year warranty











Free Manuals Download Website

http://myh66.com

http://usermanuals.us

http://www.somanuals.com

http://www.4manuals.cc

http://www.manual-lib.com

http://www.404manual.com

http://www.luxmanual.com

http://aubethermostatmanual.com

Golf course search by state

http://golfingnear.com

Email search by domain

http://emailbydomain.com

Auto manuals search

http://auto.somanuals.com

TV manuals search

http://tv.somanuals.com