

TEAC 52x32x52 CD-RW

Internal IDE Drive & External USB 2.0 Drive



52x32x52 CD-RW Drive

Internal IDE Drive for Windows

External USB 2.0 Drive for Windows

- Writes to CD-R Media at 52X
- Rewrites to CD-RW Media at 32X
- 52X Max. CD-ROM Performance
- Supports Buffer Underrun Prevention
- Fast CD 100ms Access Time
- Creates Custom Data and Audio CDs
- Supports Leading Recording Software

TEAC's internal 52x32x52 CD-RW drive and external USB 2.0 CD-RW drive delivers TEAC superior reliability, high performance and easy-to-use software bundle. They both write to CD-R at 52X, rewrites to CD-RW at 32X and reads data at a maximum 52X speed. In addition, both drives rip audio CDs at a 52X speed, reads data at 52X and delivers a 100ms average access time, resulting in an unsurpassed performance.

TEAC's 52x32x52 CD-RW both internal IDE and external USB 2.0 drive's blazing-fast write performance which makes either the ideal choice for either home or office users who demand the latest in optical storage technology and TEAC reliability and quality. The external USB drive is hot swappable utilizing USB 2.0/1.1 interface. For optimum results, both drive's buffer underrun prevention technology suspends recording until the buffer is refilled to prevent bad discs even while multitasking.

TEAC's 52x32x52 CD-RW drives are ideal for both integration and upgrades. Both drives supports Data, Music, Photo and Video CD recording applications and is available in both white or black color bezels. The retail kits come complete with installation hardware, CD recording software, user's manual and is ready for quick and easy installation.

Drive Specifications

Models:	Int: CD-W552G Ext: CD-WE552G
Interface:	Int: IDE/ATAPI Ext: USB versions 2.0 and 1.1
Data Transfer Rate:	Write: 52X Max. Rewrite: 32X Max. Read: 52X Max.
Video Playback (VCD):	32X Max.
Digital Audio Extraction:	48X Max.
Average Access Time:	100msec (Random Access)
Data Buffer Size:	2MB
Buffer Management:	Buffer Underrun Prevention
Write Methods:	Track at Once; Disc at Once; Multi-Session and Incremental
Read Compatibility:	Audio CD; CD-ROM Mode-1; CD-ROM XA Mode-2 (Form1, Form2); Super Video CD; CD-Extra/CD Plus; CD-TEXT; CD-I; Photo CD (Single and Multisession); CD-R; CD-RW (MultiRead)
Disc Size:	12cm and 8cm
Write Verification:	Running Optimum Power Control to Dynamically Adjust Laser Write Power
Logical Recording Format:	ISO 9660 and UDF Packet Writing
Drag and Drop Recording:	EasyWrite (Mount Rainier) Supported
Bezel Color:	Int: Black or White Ext: Black with black plastic casing
Disc Loading:	Int: Power Loading Tray Ext: Motorized Loading Tray
Features:	Built-in Headphone Jack, Volume Control Knob, Power Eject/Load Button, LED Indicator and RCA Jacks on Back Panel of external drive only
Power Requirements:	Int: +5 VDC, +12VDC Ext: 120VAC
Headphone Jack:	3.5mm Diameter Stereo Jack
Mounting Orientation:	Horizontal or Vertical
Agency Certification:	Int: UL, CSA, TUV, CE, FDA Ext: UL, CUL, FCC, FDA
MTBF:	Int: 70,000 POH Ext: 100,000 POH
Dimensions:	Int: 5.7"(W) x 1.63"(H) x 6.69"(D) Ext: 7.0" (W) x 2.13" (H) x 10.0" (D)
Weight:	Int: 2.0 lbs. Ext: 4.85 lbs



© 2003 TEAC America, Inc. All rights reserved. All trademarks and registered trademarks mentioned herein are the property of their respective companies.
TEAC America, Inc., 7733 Telegraph Road, Montebello, CA 90640 • Phone 323.726.0303, Fax 323.727.7652

www.teac.com/DSPD

DSPD-85811/8-03/DG-5M

Free Manuals Download Website

<http://myh66.com>

<http://usermanuals.us>

<http://www.somanuals.com>

<http://www.4manuals.cc>

<http://www.manual-lib.com>

<http://www.404manual.com>

<http://www.luxmanual.com>

<http://aubethermostatmanual.com>

Golf course search by state

<http://golfingnear.com>

Email search by domain

<http://emailbydomain.com>

Auto manuals search

<http://auto.somanuals.com>

TV manuals search

<http://tv.somanuals.com>