

Q U I C K C L A M P

THINBAND® Heater with Quick Clamp

Now...Install THINBAND Barrel Heaters In Seconds


Watlow set new standards in band heaters with THINBAND®. Now Watlow makes it even easier to install THINBAND heaters with the Quick Clamp option. The flexible one-piece design makes installation on plastics molding equipment faster and easier. Because it can be opened to the full diameter of the barrel without causing internal damage to the heater, the THINBAND heater can be installed on a barrel without removing other band heaters already in place or requiring a more expensive two-piece design.

And now with Quick Clamp, the THINBAND can be secured tightly in place in a matter of seconds. The spring-loaded clamp secures the heater tightly around the barrel with an easy flip of the lever.

Clearance Dimensions

Width Range in (mm)	# Quick Clamps	Distance Between Clamps in (mm)
1½ (38.1) to 2⅞ (69.3)	1	NA
2¾ (69.9) to 3⅞ (94.8)	2	½" (12.7)
3¾ (95.3) to 4⅞ (120.1)	2	1" (25.4)
4¾ (120.6) to 5⅞ (145.5)	3	½" (12.7)
5¾ (146.1) to 7 (145.5)	3	1" (25.4)

- Standard gap is ½ inch.
- If space for thermocouple is necessary, a maximum of 1¼ inch gap can be allowed between heater ends. Specify when ordering.




SAME DAY SHIPMENT
On selected stock

Contact your Authorized Watlow distributor for more details and ordering information.

Makes Changing Heaters A Snap!



- 1** THINBAND opens up to fit over barrel. No need to remove other heaters.
- 2** One easy flip of the latching lever and Quick Clamp shuts, completing installation.



- 3** Quick Clamp continuously tensions heater against barrel for improved heat transfer.
- THINBAND with Quick Clamp fits over barrels and snaps in place with easy flip of its latching lever.
 - Hot change-outs are completed in seconds.
 - No tools needed.
 - Spring-tensioned clamp keeps THINBAND heater tight against barrel—won't loosen over time.
 - Ideal for vertical applications.
 - Available on selected stock and made-to-order THINBAND barrel heaters—minimum four inch (100 mm) diameter, 1½ inch (38 mm) width.



12001 Lackland Road
St. Louis, Missouri 63146 USA
Phone: 314-878-4600
Fax: 314-878-2151
Internet: www.watlow.com
e-mail: info@watlow.com

Free Manuals Download Website

<http://myh66.com>

<http://usermanuals.us>

<http://www.somanuals.com>

<http://www.4manuals.cc>

<http://www.manual-lib.com>

<http://www.404manual.com>

<http://www.luxmanual.com>

<http://aubethermostatmanual.com>

Golf course search by state

<http://golfingnear.com>

Email search by domain

<http://emailbydomain.com>

Auto manuals search

<http://auto.somanuals.com>

TV manuals search

<http://tv.somanuals.com>