

Infusion Coffee Brewers



ICB-DV
(Airpot sold separately)

COMMON FEATURES

- Three brew buttons allow for 3 separate brewing profiles. Two programmable batch switches for full and half batches.
- Brews into 2.5 to 3.8 litre airpots and 1 and 1.5 gallon (3.8 and 5.7 L) baseless ThermoFresh® servers.
- Large sprayhead and BrewWISE® intelligence with pre-infusion and pulse brew for maximum flavor extraction. DBC grinder communicates with brewer through Smart Funnel®.
- Energy-saver mode reduces tank temperature during idle periods.
- Alphanumeric display communicates in English and Spanish. Display capable of showing English or metric measurements.
- Compatible with BUNNlink®.

ICB-DV FEATURES

- Brews 5.1 to 11.9 gallons (19.3 to 45 litres) of perfect coffee per hour.
- Large 3-gallon (11.36 litre) tank provides back-to-back brewing capacity at 208-240V applications.
- Dual voltage adaptable. Can operate at 120V/15amp or 208-240V/20amp.
- Includes overlay kits for customization of brewer interface.

ICB-TWIN FEATURES



- Brews up to 18.9 gallons (71.5 litres) of perfect coffee per hour.
- Large 5.6 gallon (21.2 litre) tank provides back-to-back brewing capacity

Models listed as 120/208V or 120/240V must be connected to 208V or 240V electrical service respectively. Please refer to the installation manual.

 International electrical configurations



ICB-Twin
(TF Server sold separately)

Infusion Coffee Brewers										
Model	Product #	Size		Funnel Type	Electrical			Brewing Capacity	Cord Attached	Agencies
		Dimension	Weight		Volts	Amps	Watts			
ICB-DV	36600.0000	26.01"H x 10.19" W x 22.42" D (66.1cm H x 25.9cm W x 57cm D)	47.5 lbs. (21.5 kg)	Smart Funnel	120	14	1700	5.1 gal. (19.3 L)	Yes	 
ICB-DV (black)	36600.0004				120/208	13.8	2900	8.9 gal. (33.7 L)		
					120/240	16.8	4050	11.9 gal. (45 L)		
ICB Twin	37600.0000	26.2"H x 20.0"W x 22.4"D (66.5cm H x 50.8cm W x 56.9cm D)	77 lbs. (34.9 kg)	Smart Funnel	120/240	25	6000	18.9 gal/hr (71.5 L/hr)		
	37600.0002				120/208	28				
ICB Twin (black)	37600.0004				120/240	25				

Infusion Coffee Brewers Tall



ICB-DV Tall
(TF Server sold separately)



ICB-Twin Tall
(TF Server sold separately)

COMMON FEATURES

- Designed to brew into 1 gallon and 1.5 gallon (3.8 and 5.7 litre) ThermoFresh® servers with base for easy transport of coffee to other locations.
- Easy Pulse interface allows automatic programming of pulse routine.
- BrewWISE® intelligence with pre-infusion and pulse brew for maximum flavor extraction. DBC grinder communicates with brewer through Smart Funnel®.
- Energy-saver mode reduces tank temperature during idle periods.
- Digital display in English/Spanish for easier programming and control. Advertising messages and machine status also displayed. Display capable of showing English or Metric measurements.
- Compatible with BUNNlink™.

ICB-DV TALL FEATURES

- Brews 5.1 to 11.9 gallons (19.3 to 45 litres) of perfect coffee per hour.
- Large 3-gallon (11.36 litre) tank provides back-to-back brewing capacity at 208-240V applications.
- Dual voltage adaptable. Can operate at 120V/15amp or 208-240V/20amp.
- Includes overlay kits for customization of brewer interface.



ICB-TWIN TALL FEATURES

- Brews up to 18.9 gallons (71.5 litres) of perfect coffee per hour.
- Large 5.6 gallon (21.2 litre) tank provides back-to-back brewing capacity

Models listed as 120/208V or 120/240V must be connected to 208V or 240V electrical service respectively. Please refer to the installation manual.

 International electrical configurations

Infusion Coffee Brewers Tall

Model	Product #	Size		Funnel Type	Electrical			Brewing Capacity	Cord Attached	Agencies
		Dimension	Weight		Volts	Amps	Watts			
ICB-DV Tall	36600.0005	34.4"H x 10.1"W x 19.9"D (87.4cm H x 25.7cm W x 50.5cm D)	51 lbs. (23.1 kg)	Smart Funnel	120	14	1700	5.1 gal. (19.3 L)	Yes	 
					120/208	13.8	2900	8.9 gal. (33.7 L)		
					120/240	16.8	4050	11.9 gal. (45 L)		
ICB Twin Tall	37600.0005	34.4"H x 22.6"W x 20.1"D (87.4cm H x 57.4cm W x 51.1cm D)	85.5 lbs. (38.8 kg)		25	6000	18.9 gal/hr (71.5 L/hr)			

AXIOM™ Airpot Brewers

Medium volume brewing solution featuring simple operation, precise extraction control and a variety of portable servers



AXIOM Twin APS
(airpots sold separately)



AXIOM-DV-APS
(airpot sold separately)

COMMON FEATURES

- For high lime areas, BrewLOGIC® technology calculates flow rate and adjusts brew time to maintain consistent pot levels.
- BrewWIZARD® technology simplifies brewer programming with a LCD display. Set brew level, cold brew lock-out and tank temperature from the front of the machine.
- Brews directly into 1.9 to 3 liter airpots.
- Convenient airpots keep coffee hot and fresh for hours.
- Ensures coffee brew quality with cold brew lock out capability.
- Electronic diagnostics and built in tank drain for ease of service.
- Coffee extraction controlled with programmable pre-infusion, pulse brew and digital temperature control.
- Hot water faucet.
- SplashGard® funnel deflects hot liquids away from the hand.
- Energy-saver mode reduces tank temperature during idle periods.

AXIOM-DV-APS FEATURES



- Easily convertible by flipping a switch to:
 - 120 volt, 12.5 amp
 - 120/208 volt, 13 amp
 - 120/240 volt, 15 amp
- Brews 4.2 to 7.5 gallons (15.7 to 28.4 litres) of perfect coffee per hour.

AXIOM-DV-APS FEATURES

- Brews 15 gallons (56.8 litres) of perfect coffee per hour.
- Twin brew head system.

Models listed as 120/208V or 120/240V must be connected to 208V or 240V electrical service respectively. Please refer to the installation manual.

 International electrical configurations
(Single airpot brewer models only)

AXIOM Coffee Brewers										
Model	Product #	Size		Funnel Type	Electrical			Brewing Capacity	Cord Attached	Agencies
		Dimension	Weight		Volts	Amps	Watts			
AXIOM-DV-APS	38700.0010	23.6"H x 9"W x 18.5"D (59.9cm H x 22.9cm W x 47cm D)	36 lbs. (16.3 kg)	Plastic Funnel	120	12.5	1500	4.2 gal. (15.9 L)	Yes	 
					120/208	13	2680	7.5 gal. (28.4 L)		
					120/240	15	3550	7.5 gal. (28.4 L)		
AXIOM Twin APS	38700.0013	23.5"H x 16"W x 17.7"D (59.7cm H x 40.6cm W x 44.9cm D)	64 lbs. (29 kg)	Stainless	120/240	26	6100	15 gal/hr (56.8 L/hr)		

SmartWAVE® Airpot Brewers

Low profile brewer featuring SmartWAVE technology, simple operation, and flexible server options



WAVE 15-S-APS (Silver)
(airpot sold separately)



WAVE 15-APS
(thermal carafe sold separately)



legs extended to accommodate 2.5L push-button airpot

Airpot/Carafe/Pitcher Usage Table

Brewer Position	BUNN Part #	Description	Brewer Height	Approx. Adjustment
Utilizing thermal carafe tray	36029.0001	1.9L deluxe thermal carafe	16.9"	N/A
Utilizing thermal carafe tray	40163.0000	1.9L economy thermal carafe	16.9"	N/A
LP feature (Lowest)	39430.0000	1.9L thermal pitcher	16.9"	N/A
LP feature (Lowest)	32125.0000	2.5L lever-action airpot	16.9"	N/A
Extend legs	32130.0000	3.0L lever-action airpot	17.5"	.6"
Extend legs	28696.0002	2.2L push-button airpot	18"	1"
Extend legs	13041.0001	2.5L push-button airpot	18.5"	1.5"

COMMON FEATURES

- Brews 3.9 gallons (14.8 litres) of perfect coffee per hour.
- Brew into 1.9L thermal carafe brewer utilizing the slide-out booster tray.
- Adjustable legs to accommodate up to 3.0L lever action and 2.5L push button BUNN airpots (refer to usage table).
- SmartWAVE® technology increases turbulence in the brew funnel.
- Convenient airpots keep coffee hot and fresh for hours and are easily transported to remote serving areas.
- Ensures coffee brew quality with cold brew lock out capability.
- Hot water faucet.
- SplashGard® funnel deflects hot liquids away from the hand.
- Energy-saver mode reduces tank temperature during idle periods.



STANDARD VERSION

- Four-digit LED read-out for simple programming.
- Utilize the same LED read-out for brewer status (Ready, Heating, Brewing).
- 13 pulse brew routine selections adjust strength profile in conjunction with the BrewMETER®.

SILVER VERSION

- Analog switches accompanied by red/green LED for programming.
- Red/green LED provide brewer status (ready, heating, brewing).
- Choice of three pulse brew routines to adjust your flavor profile.

SmartWAVE Low Profile Airpot Brewers

Model	Product #	Size		Funnel Type	Electrical			Brewing Capacity	Cord Attached	Agencies
		Dimension	Weight		Volts	Amps	Watts			
WAVE 15-APS	39900.0000	16.9"H x 8.7"W x 17.1"D (43cm H x 22.2cm W x 43.5cm D)	24.2 lbs. (11 kg)	Black Plastic	120	11.3	1350	3.9 gal. (14.8 L)	Yes	 
WAVE 15-S-APS	39900.0001							6.4 gal. (24.2 L)		
WAVE-APS	39900.0003				120/240	9.5	2250	No		
WAVE-S-APS	39900.0004									

Airpot Brewers



CWTF Twin APS
(airpots sold separately)



CWTF APS-DV
(airpot sold separately)



CWTF APS
(airpot sold separately)

PRODUCT FEATURES

- Brews directly into 1.9 to 3 litre airpots.
- Hot water faucet with pourover feature.
- Digital timer enables users to make brew cycle adjustments from the front panel.
- Use BUNN paper filters - Product No. 20115.0000. Gourmet funnel requires BUNN paper filter 20100.0000.

CWTF-DV FEATURES

- Voltage converts easily by flipping a switch.

Models listed as 120/208V or 120/240V must be connected to 208V or 240V electrical service respectively. Please refer to the installation manual.



International electrical configurations
(Single airpot brewer models only)

CWTF and Twin Airpot Brewers

Model	Product #	Size		Funnel Type	Electrical			Brewing Capacity	Cord Attached	Agencies
		Dimension	Weight		Volts	Amps	Watts			
CWTF APS-DV	23001.0058	23 6"H x 9"W x 18.5"D (59.9cm H x 22.9cm W x 47cm D)	36 lbs. (16.3 kg)	Black Plastic	120	11.4	1370	3.9 gal/hr 14.6 L/hr	No	
					120/208		2340	6.7 gal/hr 25.3 L/hr		
					120/240	13.1	3100	7.5 gal/hr 28.4 L/hr		
	23001.0059		37 lbs. (16.7 kg)	Black Plastic and Stainless Steel	120	11.4	1370	3.9 gal/hr 14.6 L/hr		
					120/208		2340	6.7 gal/hr 25.3 L/hr		
					120/240	13.1	3100	7.5 gal/hr 28.4 L/hr		
CW15-APS (no faucet)	23001.0000 Pourover	23.6"H x 9"W x 18.5"D (59.9cm H x 22.9cm W x 47cm D)	28 lbs. (12.7 kg)	Black Plastic	120	11.4	1370	3.8 gal/hr 14.4 L/hr	Yes	UL LISTED NSF
	23001.0062 Pourover		29 lbs. (13.2 kg)	Black Plastic						
	23001.0003		38 lbs. (17.3 kg)	Stainless Steel						
CWTF15-APS	23001.0017	23.6"H x 9"W x 18.5"D (59.9cm H x 22.9cm W x 47cm D)	33 lbs. (15.0 kg)	Black Plastic	120	11.4	1370	3.8 gal/hr 14.4 L/hr	Yes	UL LISTED NSF
	23001.0006		37 lbs. (16.8 kg)	Gourmet Funnel						
	23001.0051		32 lbs. (14.6 kg)	Black Plastic						
CWTF20-APS	23001.0007	23.6"H x 9"W x 18.5"D (59.9cm H x 22.9cm W x 47cm D)	33 lbs. (15.0 kg)	Black Plastic	120	15	1850	5.1 gal/hr 19.3 L/hr	No	UL LISTED NSF
CWTF35-APS	23001.0008		37 lbs. (16.8 kg)	Gourmet Funnel						
	23001.0052		37 lbs. (16.8 kg)	Stainless Steel						
CWTF35-APS, SF	23001.0023	23.5"H x 16"W x 19.7"D (59.7cm H x 40.6cm W x 50.0cm D)	60 lbs. (27.3 kg)	Gourmet Funnel	120/240	26	6250	15 gal/hr 56.8 L/hr	No	UL LISTED NSF
CWTF Twin APS	23400.0041			Stainless Steel						
	23400.0046			Gourmet Funnel						

Thermal Carafe Coffee Brewers



CWTF15-TC
(thermal carafe
sold separately)



AXIOM-DV-TC
(thermal carafe
sold separately)



CWTF Twin-TC
(thermal carafe
sold separately)

AXIOM-DV-TC FEATURES

- Easily convertible by flipping a switch to:
 - 120 volt, 12.5 amp
 - 120/208 volt, 13 amp
 - 120/240 volt, 15 amp
- Brews 4.2 to 7.5 gallons (15.7 to 28.4 litres) of perfect coffee per hour.
- BrewWIZARD® technology simplifies brewer programming with a LCD display. Set brew level, pulse brew, cold brew lock-out and tank temperature from the front of the machine.

CWTF-TC FEATURES

- Accepts thermal carafe up to 8.5" tall (21.6cm) (sold separately).
- Use in quick-turn environment where high quality coffee is continuously refreshed.
- SplashGard® funnel deflects hot liquids away from the hand.



International electrical configurations

CWTF TWIN-TC BREWER FEATURES

- Accepts thermal carafe up to 8.5" (21.6 cm) tall (sold separately).
- Use in quick-turn environment where high quality coffee is continuously refreshed.
- All stainless steel construction.
- SplashGard® funnel deflects hot liquids away from the hand.
- Pourover feature.

Models listed as 120/208V or 120/240V must be connected to 208V or 240V electrical service respectively. Please refer to the installation manual.

Thermal Carafe Coffee Brewers

Model	Product #	Size		Electrical			Brewing Capacity	Funnel Type	Cord Attached	Agencies
		Dimension	Weight	Volts	Amps	Watts				
AXIOM-DV-TC	38700.0011	17.9" H x 9" W x 18.5" D (45.5cm H x 22.9cm W x 55.4cm D)	30 lbs. (13.6 kg)	120	12.5	1500	4.2 gal/hr (15.9 L/hr)	Black Plastic	Yes	
				120/208	13	2680	7.5 gal/hr (28.4 L/hr)			
				120/240	15	3550	7.5 gal/hr (28.4 L/hr)			
CW15-TC (no faucet)	23001.0040 Pourover	17.9" H x 9" W x 18.5" D (45.5cm H x 22.9cm W x 55.4cm D)	28 lbs. (12.7 kg)	120	11.4	1370	3.9 gal/hr (14.6 L/hr)	Stainless Steel	No	
CWTF15-TC	12950.0360		32 lbs. (14.5 kg)				7.5 gal/hr (28.4 L/hr)			
CWTF20-TC	12950.0380		31 lbs. (14.1 kg)	120	15.4	1850	5.3 gal/hr (19.9 L/hr)			
CWTF35-TC	12950.0379		32 lbs. (14.5 kg)	120/ 208-240	15	3550	7.5 gal/hr (28.4 L/hr)			
CWTF Twin-TC	23400.0047		17.2" H x 16" W x 22.5" D (43.7cm H x 41cm W x 57.2cm D)	64 lbs. (29.3 kg)	120/240	26	6250			15 gal/hr (56.8 L/hr)
CWTF-TC DV	23001.0069	17.9" H x 9" W x 18.5" D (45.5cm H x 22.9cm W x 55.4cm D)	29 lbs. (13.2 kg)	120	11.4	1370	3.9 gal/hr (14.6 L/hr)	Black Plastic		
				120/208	11.4	2340	6.7 gal/hr (25.3 L/hr)			
				120/240	13.1	3100	7.5 gal/hr (28.4 L/hr)			

Airpots and Thermal Carafes



Push-Button Airpot



Lever-Action Airpot



Thermal Carafe



Economy Thermal Carafe



Vacuum Pitcher

PUSH-BUTTON AIRPOT FEATURES

- Brew-through pump assembly
- Just close the lid after brewing – dispenses up to 4 ounces at the first pump.
- Glass insulation keeps beverage hot.

LEVER-ACTION AIRPOT FEATURES

- Stainless steel lining keeps coffee hot.
- Brew-through lid with lever-action for easy use.

THERMAL CARAFE FEATURES

- Holds 1.9 litres or 64 ounces (12 cups) of coffee or other hot beverage.
- Unbreakable stainless steel interior and exterior.
- Superior vacuum insulation keeps beverages hot for hours.
- Brew-through lid allows direct brewing.
- Fits on BUNN Thermal Carafe and Twin Thermal Carafe brewers.

See page 60 for universal airpot racks and coffee-isers.

Airpots & Thermal Carafes							
Model	Product #	Size		Liner	Quantity	Capacity	Agencies
		Dimension	Weight				
2.2 litre Push-Button Airpot	28696.0002	16.4" H x 6.1" W x 7.9" D (42cm H x 16cm W x 20cm D)	4.5 lbs. (2.04 kg)	Glass	single unit	2.2 litres (74 oz)	ETL
	28696.0000		24 lbs. (10.9 kg)		6 units/ case		
2.5 litre Push-Button Airpot	13041.0001	14.6" H x 6.3" W x 9" D (37cm H x 16cm W x 23cm D)	5 lbs. (2.3 kg)		single unit	2.5 litres (84 oz.)	
	13041.0101		25 lbs. (11.3 kg)		6 units/ case		
2.5 litre Lever-Action Airpot	32125.0000		5.3 lbs. (2.4 kg)	single unit			
	32125.0100		32 lbs. (14.6 kg)	6 units/ case			
3.0 litre Lever-Action Airpot	32130.0000	15.5" H x 6.3" W x 9" D (39.4cm H x 16cm W x 23cm D)	5.8 lbs. (2.6 kg)	single unit	3.0 litres (102 oz.)		
	32130.0100		35 lbs. (15.9 kg)	6 units/ case			
3.8 litre Lever-Action Airpot	36725.0000	(17.6" H x 6.3" W x 9" D) (44.7cm H x 16cm W x 23cm D)	7 lbs. (3.2 kg)	single unit	3.8 litres (128 oz)	NSF	
	36725.0100		41 lbs. (18.6 kg)	6 units/ case			
1.9 litre Thermal Carafe (Black Lid)	36029.0001	8" H x 6.4" W x 8.2" D (20.3cm H x 16.3cm W x 21cm D)	3.0 lbs. (1.36 kg)	Stainless Steel	single unit	1.9 litres (64 oz.)	
	36029.0000		34 lbs. (15.4 kg)		12 units/ case		
1.9 litre Thermal Carafe (Orange Lid)	36252.0001		3.0 lbs. (1.36 kg)		single unit		
	36252.0000		34 lbs. (15.4 kg)		12 units/ case		
1.9 litre Economy Thermal Carafe (Black Lid)	40163.0000	7.1" H x 6.6" W x 8.64" D (18cm H x 16.8cm W x 21.9cm D)	2.5 lbs. (1.1 kg)	Glass	single unit	1.9 litres (64 oz.)	NSF
	40163.0100		30 lbs. (13.6 kg)		12 units/ case		
1.9 litre Economy Thermal Carafe (Orange Lid)	40163.0001		2.5 lbs. (1.1 kg)		single unit		
	40163.0101		30 lbs. (13.6 kg)		12 units/ case		
1.9 litre Vacuum Pitcher (Black Lid)	27350.0001	11.3" H x 6.5" W x 5.5" D (28.7cm H x 16.5cm W x 14cm D)	3.0 lbs. (1.36 kg)	Glass	single unit		

Thermal Coffee Brewers, Servers and Stands



CWTF-TS
(Server sold separately)



TS Booster



TSR-1 and TSR-2
(shown with
TS servers no base)



TSR
(Raised)

PRODUCT FEATURES

- Pourover feature included on automatic brewer models.
- Internal stainless steel components.
- Hot water faucet available.
- SplashGard® funnel deflects hot liquids away from the hand.
- Holds up to 4" (10.16 cm) tall cup.
- Use BUNN paper filters – Product No. 20115.0000.

THERMAL SERVER FEATURES

- Convenient for keeping coffee hot and fresh for hours.
- Easily transported to remote locations.
- Depending on base, server can hold up to 6½" (16.51 cm) cup.

THERMAL SERVER RACK FEATURES

- Holds one or two 2.5 litre thermal servers without base.
- Made of durable, easy-to-clean plastic with drip trays to catch spills and keep serving areas clean.



International electrical configurations

Thermal Server Coffee Brewers

Model	Product #	Size		Electrical			Brewing Capacity	Cord Attached	Agencies
		Dimension	Weight	Volts	Amps	Watts			
CW15-TS (Pourover)	23000.0000	27.6" H x 9" W x 18.5" D (70.1cm H x 22.9cm W x 47cm D)	27 lbs. (12.3 kg)	120	11.4	1370	3.9 gal/hr. (14.6 L/hr)	Yes	
CWTF15-TS (Automatic w/faucet)	23000.0006		32 lbs. (14.6 kg)						

Thermal Servers and Stands

Model	Product #	Size		Capacity	Quantity	Agencies
		Dimension	Weight			
TS	23300.0007	19.6" H x 7.9" W x 8.7" D (49.8cm H x 20.1cm W x 22.1cm D)	6 lbs. (2.7 kg)	2.5 litres (84 oz.)	single unit	
	23300.0005		33 lbs. (15 kg)		6/case	
TSR (Raised)	23300.0009	21.8" H x 7.9" W x 8.9" D (55.4cm H x 20cm W x 22.6cm D)	6 lbs. (2.7 kg)		single unit	
TS (no base)	23300.0010	14.4" H x 7" W x 8.1" D (36.6cm H x 17.8cm W x 20.6cm D)	4 lbs. (1.8 kg)		6/case	
	23300.0006		25 lbs. (11.3 kg)			
BUNN Safety-Fresh® Lid (Kit)	22964.0000	n/a	1 lb. (.5kg)		single unit	
TSR-1	18008.6001	25" H x 7.5" W x 8.5" D (63.5cm H x 19.1cm W x 21.6cm D)	4.5 lbs. (2.1 kg)	1 Thermal Server w/out Base	n/a	
TSR-2	18008.6002	28.5" H x 7.5" W x 17" D (72.4cm H x 19.1cm W x 43.2cm D)	8 lbs. (3.6 kg)	2 Thermal Servers w/out Bases		
TS Booster	18010.6000	6" H x 9.25" W x 8.25" D (15.2cm H x 23.5cm W x 21cm D)	2 lbs. (.9 kg)	1 Thermal Server w/out Base		No Listing

Free Manuals Download Website

<http://myh66.com>

<http://usermanuals.us>

<http://www.somanuals.com>

<http://www.4manuals.cc>

<http://www.manual-lib.com>

<http://www.404manual.com>

<http://www.luxmanual.com>

<http://aubethermostatmanual.com>

Golf course search by state

<http://golfingnear.com>

Email search by domain

<http://emailbydomain.com>

Auto manuals search

<http://auto.somanuals.com>

TV manuals search

<http://tv.somanuals.com>