Limited 90-Day Warranty Information

Timex Audio Products, a division of SDI Technologies Inc. (hereafter referred to as SDI Technologies), warrants this product to be free from defects in workmanship and materials, under normal use and conditions, for a period of 90 days from the date of original purchase. Should service be required by reason of any defect or malfunction during the warranty period, SDI Technologies will repair or, at its discretion, replace this product without charge (except for a \$10.00 charge for handling, packing, return UPS/postage, and insurance). This decision is subject to verification of the defect or malfunction upon delivery of this product to the Factory Service Center listed below. The product must include proof of purchase, including date of purchase. The fee for service after the warranty period or without proof of purchase is \$30.00.

Before returning this product for service, please first replace the batteries (if applicable) with fresh ones, as exhausted or defective batteries are the most common cause of problems encountered.

- If service is still required:
- 1. Remove batteries (if applicable) and pack the unit in a well-padded, heavy corrugated box.
- 2. Enclose a photocopy of your sales receipt, credit card statement, or other proof of the date of purchase.
- 3. Enclose a check or money order payable to the order of SDI Technologies, Inc. for the sum of \$10.00 (or \$30.00 if after the warranty period or without proof of purchase).
- 4. Send the unit prepaid to the Factory Service Center listed below:

Consumer Repair Department

SDI Technologies Inc. Timex Audio Products Division 1330 Goodvear Drive El Paso TX 79936-6420

NOTE: This warranty is valid only if the product is used for the purpose for which it was designed. It does not cover (i) products which have been damaged by negligence, misuse or accident, or which have been modified or repaired by unauthorized persons; (ii) cracked or broken cabinets, or units damaged by excessive heat; (iii) damage to tape cassettes (if applicable); (iv) the cost of shipping this product to the Factory Service Center and its return to the owner.

This warranty is valid only in the United States of America and does not extend to owners of the product subsequent to the original purchaser. Any applicable implied warranties are also limited to 90 days, and SDI Technologies will not be liable for consequential damages. (Some states do not allow limitations on implied warranties or exclusion of consequential damages, so these restrictions may not apply to you.) This warranty gives you specific legal rights, and you may also have other rights which vary from state to state.

© 2007 SDI Technologies, Inc. All rights reserved TIMEX is a registered trademark of Timex Corporation the United States and other countries

T1233-122107-1

Printed in China

Installation and Maintenance

Installation

- 1. Remove the unit and all packing materials from the carton. You should save the packing materials in case unit needs to be returned for service. If you do not wish to save the materials, please dispose of them properly.
- Place the unit on a stable, level surface, close to an AC outlet, out of direct sunlight, and away from sources of dust, dirt, heat, water, moisture, vibration, and strong magnetic fields.
- 3. After activating the backup (see below) and reading the Maintenance notes, plug the AC cord into an outlet.

"Sure Alarm" Battery Backup Installation

It is recommended that 2 "AA" batteries be installed into the unit, as directed below, to activate the "Sure Alarm" battery backup feature. In the event that the AC power cord is disconnected or a power failure or other interruption occurs, the "Sure Alarm" system will maintain clock and alarm settings for the life of the batteries, ensuring that the alarm will sound at the set time (Note: while operating on battery power, all set alarms will sound as a buzzer). When power is restored, the clock will cease using battery power, and will again operate on AC power. The Battery Low Indicator flashes when there is not enough power to run the backup.

- 1. Use a Phillips screwdriver to remove the battery compartment door.
- 2. Install 2 "AA" batteries (alkaline batteries are recommended for longer life) into the battery compartment, making sure that the + and - polarities match up with the diagram printed inside the compartment.
- . Close the battery compartment door and tighten the screw. Gently return the clock radio to its upright position.

Maintenance


- 1. Place the unit on a level surface away from sources of direct sunlight or excessive heat.
- 2. Protect your furniture when placing your unit on a natural wood and lacquered finish. A cloth or other protective material should be placed between it and the furniture.
- 3. Clean your unit with a soft cloth moistened only with mild soap and water. Stronger cleaning agents, such as Benzine, thinner or similar materials can mar the surface of the case.
- 4. If the unit is not to be used for a prolonged period, such as a month or longer, remove the batteries to prevent possible corrosion. Should the battery compartment become corroded or dirty, clean the compartment thoroughly and replace the batteries.

A Consumer Guide to Product Safety

IMPORTANT SAFETY INSTRUCTIONS

This unit has been designed and manufactured to assure your personal safety. Improper use can result in potential electrical shock or fire hazards. Please read all the safety and operating instructions carefully before installation and use. Keep these instructions handy for future reference. Take special note, adhere to all warning, and always follow the instructions on the unit and in the instructions and service manuals. Water and Moisture - The unit should not be used near water. For example: near a bathtub, washbowl, kitchen sink, laundry tub, swimming pool or in a wet basement.

- Ventilation The unit should be situated so that its location or position does not interfere with
- or other appliances (including amplifiers) that produce heat.
- the operating instructions or as marked on the appliance.
- defeat the safety purpose of the polarized plug.
- area from where the cord exits the unit to where it is plugged into an AC outlet.
- or aerosol cleaners. Use a damp cloth for cleaning.
- to be left unused for a long period of time.
- spilled into the enclosure through openings.
- 10. Attachments Do not use attachments not recommended by the product manufacturer as they may cause hazards.
- as this can result in a risk of fire or electric shock.
- 13. Damage Require Service The unit should be serviced by qualified service personnel when: A. The power supply cord or plug has been damaged. B. Objects have fallen into or liquid has been spilled into the enclosure.
- The unit has been exposed to rain.
- D. The unit has been dropped or the enclosure damaged.
- 14. Servicing The user should not attempt to service the unit beyond that described in the user's
- 16. Antenna Do not connect to an external antenna.



Battery Compartment

its proper ventilation. For example, it should not be situated on a bed, sofa, rug or similar surface that may block ventilation openings. Also, it should not be placed in a built-in installation, such as a bookcase or cabinet that may impede the flow of air through the ventilation openings. Heat - The unit should be situated away from heat sources such as radiators, heat registers, stoves

Power Sources - The unit should be connected to a power supply only of the type described in

Grounding or Polarization - This product is equipped with a polarized alternating current line plug (a plug having one blade wider than the other). As a safety feature this plug will fit into the power outlet only one way. If you are unable to fit the plug fully into the outlet, try reversing the plug. If the plug still fails to fit, contact your electrician to replace your obsolete outlet. Do not

Power-Cord Protection - Power supply cords should be routed so that they are not likely to be walked on or pinched by items placed upon or against them. It is always best to have a clear

Cleaning - Unplug this product from the well outlet before cleaning. Do not use liquid cleaners

Non-Use Periods – The power cord of the unit should be unplugged from the outlet when it is

Objects and Liquid Entry - Care should be taken so that objects do not fall and liquids are not

11. Lightning - For added protection for this product during a lightning storm, or when it is left unattended and unused for long periods of time, unplug it from the wall outlet and disconnect the antenna or cable system. This will prevent damage to the product due to lightning and power-line

12. **Overloading** - Do not overload wall outlets, extension cords, or integral convenience receptacles

E. The unit does not appear to operate normally or exhibits a marked change in performance. operating instructions. All other servicing should be referred to qualified service personnel. . Safety Check - Upon completion of any service or repairs to this product, ask the service telchnician to perform safety checks to determine that the product is in proper operating condition.



The symbols above are located at the bottom of the cabinet.

CAUTION: To prevent electric shock, match wide blade of plug to wide slot. Fully insert.

ATTENTION: Pour éviter les choc électriques. Introduire la lame la plus large de la fiche dans la borne correspondante de la prises et pousser jusqu'au fond.

FCC Information


This device complies with part 15 of the FCC Rules. Operation is subject to the condition that this device does not cause harmful interference.

Note: The manufacturer is not responsible for any radio or TV interference cause by unauthorized modifications to this equipment. Such modification could void the user's authority to operate the equipment.



Model T1233


Auto-Se Digital Tuning Alarm Clock Radio



For additional information, online registration, and exclusive special offers please visit our website:

www.timexaudio.com

Controls and Indicators



Display with Indicators

This unit has four Radio Preset Buttons for quests to find local stations. It also includes 12

Place the paper insert that matches the programmed station into the clear

Programming the Preset Radio Stations

General Operating Instructions

- 1. Press the **Alarm Set Button**. The wake time on the display will flash.
- 2. Press the **Reverse/Tuning** or **Forward/Tuning button** to set the alarm time. Hold a tuning button for a few seconds to advance the time guickly.
- 3. For wake to buzzer, press the **Enter Button** to set the alarm wake time. The unit will beep twice and the Buzzer Alarm On Indicator will appear, showing that the buzzer alarm will sound at the set time.
- 4. For wake to radio, press one of the Radio Preset Buttons then Enter Button to set the alarm wake time. The unit will beep twice and the Radio Alarm On Indicator will appear, showing that the radio alarm will sound at the set time.
- . When the alarm sounds, press the **Snooze/Dimmer Bar** for a 9-minute Snooze time, or press the **Alarm On/Off Button** to shut off the alarm. The Alarm Off Indicator will appear.

Note: Pressing **Alarm On/Off Button** while alarm is sounding turns off alarm. The Alarm On/Off Button also selects alarm mode.

- 1. There are two ways to turn on the radio. Press one of the **Radio Preset Buttons** to listen to one of the preset stations, or press the **Power On/Off Button**. The radio frequency will appear on the display.
- 3. Press either the **Reverse/Tuning** or **Forward/Tuning Button** to find the station. Hold a tuning button for a few seconds to scan the dial quickly.
- 5. Press **Power On/Off Button** to shut off the radio.

Note:

- Extend the wire antenna for better FM reception.
- Keep Fluorescent lamps away from unit as they may cause interference with radio.

Playing the MP-3 / Aux Line-in

- . Connect your CD/ MP-3 Player or other device to the MP-3/Aux Line-in Plug.
- 2. Press the **MP-3/Aux Line-in Button**. 'AU' will appear on the display.
- 3. Turn the **Volume Control** to adjust the volume level.

Note: To avoid distortion of sound, always set the volume level of the auxiliary device to middle position, and adjust the desired volume level from the radio.

4. Press the **Power On/Off Button** to shut off unit. Remember to turn off your audio device, too.

Adjusting the Display Backlight

This alarm clock radio features an adjustable display backlight, with dim, medium, and bright settings. To select a backlight setting, press the **Snooze/Dimmer Bar** until desired brightness is reached.

Setting and Operating the Alarm

Playing the Radio

- 2. Set the AM or FM band by pushing the **Radio Band Button**.
- 4. Rotate **Volume Control** to adjust volume level.

Replace the clear cover together with paper insert on the top of black button.

Note: Each button cover is numbered 1-5, and must be placed on the black buttons in

numerical order.

Remove each

clear button

cover.

Replace the frame. Gently press around the frame to snap it

 \rightarrow

Free Manuals Download Website <u>http://myh66.com</u> <u>http://usermanuals.us</u> <u>http://www.somanuals.com</u> <u>http://www.4manuals.cc</u> <u>http://www.4manuals.cc</u> <u>http://www.4manuals.cc</u> <u>http://www.4manuals.com</u> <u>http://www.404manual.com</u> <u>http://www.luxmanual.com</u> <u>http://aubethermostatmanual.com</u> Golf course search by state

http://golfingnear.com Email search by domain

http://emailbydomain.com Auto manuals search

http://auto.somanuals.com TV manuals search

http://tv.somanuals.com