



## 9451-HP34CDNF Insulated Heater / Proofer



**SIZE:**

**E9451-HP34CDNF -**

67-9/16" High, 23-5/16" Wide, 33-7/8" Deep  
1716 mm High, 592 mm Wide, 860 mm Deep

**Toastmaster's 9451-HP34CDNF** - In locations where cabinets will be used primarily for holding with infrequent serving applications (gauged by door openings) or in situations with limited start-up budgets, the non-insulated cabinet would satisfy most requirements. In higher volume operations with more frequent serving applications the insulated cabinet would be the better choice as it delivers a faster recovery and greater consistency of temperature.

**CONSTRUCTION:**

- Aluminum construction
- Insulated
- Removable heating console

**CONTROLS:**

- Mechanical controls
- External solar powered digital thermometer

**LABORATORY CERTIFICATION AND APPROVAL**



**STANDARD FEATURES:**


- Air baffle and circulation air blower provide even heat distribution
- Aluminum construction
- Set of 5" swivel casters w/brakes
- Polycarbonate door
- Magnetic door gaskets
- Lift-off door
- Full length door handle
- Insulated

**OPTIONAL FEATURES:**

- Solid door

Toastmaster 9451-HP34CDNF Insulated Heater / Proofer

## 9451-HP34CDNF Insulated Heater / Proofer



**SPECIFICATIONS:**

**SERVICE CONNECTIONS:**

- Unit provided with 6 foot detachable cord and plug. NEMA 5-20P
- Removable console consisting of blower, three-way toggle switch, running lights to indicate heater (holding) or proofing mode, stainless steel water reservoir.
- Element controlled by 180 degrees thermostat. 1500 Watts in heating mode. 1500 Watts in proofing mode.

**ELECTRICAL:**

Amp Draw	120/1	208/3	240/1	240/3
	14	n/a	n/a	n/a

**LISTINGS:**

The 9451-HP34CDNF has C-ETL-US and NSF listings.



**CAPACITY:**

Heater/Proofer	18"x26" Full Size Sheet Pans	13"x18" Full Size Sheet Pans	Spacing
		34	

**DIMENSIONS:**

	Height	Width	Depth
<b>Exterior</b>	67-9/16"	23-5/16"	33-7/8"
<b>Interior</b>	51-3/4"	18-1/8"	27-1/2"

**DOOR SWING:**

- Door swings 270 degrees to the recessed side of the cabinet

**PACKING SIZE:**

72" High, 28" Wide, 40" Deep  
(1828 mm High, 711 mm Wide, 1016 mm Deep)

**SHIPPING WEIGHT:**

140 Pounds, FOB Menominee, MI 49858

**INTENDED FOR COMMERCIAL USE ONLY. NOT FOR HOUSEHOLD USE.**



Toastmaster, in line with its policy to continually improve its product, reserves the right to change materials or specifications without notice. Such revisions do not entitle the buyer to corresponding changes, improvements, additions, or replacements for previously purchased equipment.



**Toastmaster®** 5600 13th Street, Menominee, MI 49858 • [www.toastmastercorp.com](http://www.toastmastercorp.com)

Toll Free: 1-800-338-9886 • Telephone: 1-906-863-4401 • Fax: 1-906-863-5889

Download from [www.Somanuals.com](http://www.Somanuals.com). All Manuals Search And Download.

## Free Manuals Download Website

<http://myh66.com>

<http://usermanuals.us>

<http://www.somanuals.com>

<http://www.4manuals.cc>

<http://www.manual-lib.com>

<http://www.404manual.com>

<http://www.luxmanual.com>

<http://aubethermostatmanual.com>

Golf course search by state

<http://golfingnear.com>

Email search by domain

<http://emailbydomain.com>

Auto manuals search

<http://auto.somanuals.com>

TV manuals search

<http://tv.somanuals.com>