



# Sand Pro/Infield Pro® 2020 Specifications\*

SAND PRO/INFIELD PRO 2020, MODEL 08884									
<b>ENGINE</b>	Vanguard®, V-twin cylinder, 4-cycle, OHV, air-cooled, gas engine with cast iron sleeves. 16 hp (11.9 kW) at 3600 rpm. Displacement: 29.3 cu. in. (480 cc). Oil capacity: 1.75 quart (1.66 liter). Electronic ignition. Full pressure lubrication, oil filter.								
<b>AIR CLEANER SYSTEM</b>	Double air filtration, standard engine air filter plus remote mounted 3-phase Donaldson® air cleaner.								
<b>FUEL CAPACITY</b>	4.25 gallon (16.1 liter) of unleaded gasoline.								
<b>TRACTION DRIVE</b>	Direct driven hydrostatic variable displacement piston pump to 2 hydraulic motors for 2WD. Large engine intake hydraulic cooler. Foot pedal control, forward/reverse.								
<b>GROUND SPEED</b>	Infinitely variable 0-11 mph (17.7 km/h) forward; 4 mph (6.9 km/h) reverse.								
<b>HYDRAULIC OIL</b>	3 gallon (11.4 liter) system capacity. Nylon reservoir to reduce corrosion. 10 micron (nominal) replaceable cartridge.								
<b>TIRES/WHEELS</b>	Three 22 x 11.00-8 pneumatic tubeless tires on demountable, interchangeable wheels. Tire pressure: 4-6 psi (27.5 kPa). Smooth tire, sports field tire.								
<b>MAIN FRAME</b>	Tricycle vehicle with welded tubular steel frame construction. Mid-engine placement. Removable refuse box.								
<b>BRAKES</b>	Dynamic braking through the hydrostatic transmission and hand activated drum brakes mounted on each rear wheel.								
<b>STEERING</b>	Manual front wheel steering. 15" (38 cm) diameter steering wheel.								
<b>CONTROLS/GAUGES</b>	Hand operated choke, throttle, and hydraulic control for raising/lowering with float. Foot pedal controls traction forward/reverse speed. Gauges: hour meter.								
<b>SEAT</b>	High-back cushion seat w/drain hole. 4" front-back adjustment w/additional 1.75" mounting adjustment (arm rests optional).								
<b>ELECTRICAL FEATURES</b>	12-volt battery, 280 CCA, 12-volt electric starter. Dash mounted ignition switch with key. Neutral interlock switch, seat switch, parking break switch. Also provisions for light kit.								
<b>SOUND LEVEL</b>	82 dB(A) under normal operating conditions.								
<b>DIMENSIONS</b>	<table border="1"> <thead> <tr> <th>Width</th> <th>Length</th> <th>Height</th> <th>Wheelbase</th> </tr> </thead> <tbody> <tr> <td>58" (147 cm)</td> <td>76" (193 cm)</td> <td>45" (114 cm)</td> <td>41.25" (105 cm)</td> </tr> </tbody> </table>	Width	Length	Height	Wheelbase	58" (147 cm)	76" (193 cm)	45" (114 cm)	41.25" (105 cm)
Width	Length	Height	Wheelbase						
58" (147 cm)	76" (193 cm)	45" (114 cm)	41.25" (105 cm)						
<b>WEIGHT</b>	Net weight (full fluids): 650 lbs. (295 kg)								
<b>WARRANTY</b>	Two-year limited warranty. Refer to the Operator's Manual for further details. Briggs & Stratton® provides a two-year commercial engine warranty and a lifetime Magnetron® warranty.								

\*Specifications and design subject to change without notice.





# Sand Pro®/Infield Pro® 2020 Specifications\* (continued)

SAND PRO/INFIELD PRO ATTACHMENTS & ACCESSORIES													
<b>TOOTH RAKE, 08812</b>	72" (183 cm) width, with 3 rake sections, 27 prongs adjustable for depth and wear. Adjustable trowels, drawbar position for variable aggressiveness. Hydraulically raised for transport. Weights available for drag sections.												
<b>SPRING RAKE, 08813</b>	76" (193 cm) width, with 5 individual rake heads. Hydraulically raised for transport.												
<b>WEEDER/CULTIVATOR, 08815</b>	38" (97 cm) width, with 5 sets of double shovels. Mounted close to rear wheels for improved ground following and reduced gouging. Hydraulically lowered, spring raised. Operates independently of Tooth Rake and Spring Rake.												
<b>DOZER BLADE, 08821</b>	40" (102 cm) width, reversible blade. Loop handle for blade control with either hand. Transport lock-up with handle storage position. Side-to-side flex design for improved ground following. Optional 60" (152 cm) Blade also available.												
<b>DRAG MAT, 08850</b>	6.5' x 6' (1.9 m x 1.8 m) Keystone drag mat with transport stands. Used in conjunction with Hitch Kit to drag greens and tees.												
<b>SPIKER, 08856</b>	<p>Description: Spiker consists of 2 units each with 12 spiker blades and 11 hold down fingers. Each unit floats independently of the other and is hydraulically pressured into the ground and allowed to float up and down by means of a spring.            Blade: High carbon steel, .105" (.26 cm) thick. Special profile design for minimum disturbance of soil surface when spiking, 73/4 dia. (1.9 cm).</p> <p><b>Specifications:</b></p> <table border="0"> <tr> <td>Weight:</td> <td>280 lbs. (127 kg)</td> <td>Unit Working Width:</td> <td>57.6" (146 cm)</td> </tr> <tr> <td>Working Depth:</td> <td>1.25" (3.2 cm), max.</td> <td>Working lbs./Blade:</td> <td>23.1 lbs. (10.5 kg)/blade</td> </tr> <tr> <td>Blade Spacing:</td> <td>2.4" (6.1 cm)</td> <td></td> <td></td> </tr> </table>	Weight:	280 lbs. (127 kg)	Unit Working Width:	57.6" (146 cm)	Working Depth:	1.25" (3.2 cm), max.	Working lbs./Blade:	23.1 lbs. (10.5 kg)/blade	Blade Spacing:	2.4" (6.1 cm)		
Weight:	280 lbs. (127 kg)	Unit Working Width:	57.6" (146 cm)										
Working Depth:	1.25" (3.2 cm), max.	Working lbs./Blade:	23.1 lbs. (10.5 kg)/blade										
Blade Spacing:	2.4" (6.1 cm)												
<b>TURF TIRE, 95-5849</b>	22 x 11.00-8. Tire pressure: 4-6 psi (27.5 kPa).												
<b>FINISH GRADER, 08867</b>	<p>Consists of bar plow and scarifier. Adept at light ground maintenance and grooming. Hydraulically raised and lowered, with spring loading to regulate down pressure.</p> <p><b>Dimensions:</b></p> <table border="0"> <tr> <td>Weight:</td> <td>200 lbs. (91 kg)</td> <td>Length:</td> <td>10" (25 cm)</td> </tr> <tr> <td>Width:</td> <td>66" (168 cm)</td> <td>Height:</td> <td>10" (25 cm)</td> </tr> </table>	Weight:	200 lbs. (91 kg)	Length:	10" (25 cm)	Width:	66" (168 cm)	Height:	10" (25 cm)				
Weight:	200 lbs. (91 kg)	Length:	10" (25 cm)										
Width:	66" (168 cm)	Height:	10" (25 cm)										
<b>CYCLONE™ 1000 BLOWER, 08857</b>	2100 rpm fan generating 2850 cfm. PTO drive with single B section drive belt. Quick-attach with two pins and connect drive shaft. Clutch: Lever engagement back side belt tensioner. Weight 180 lbs. (82 kg).												

\*Specifications and design subject to change without notice. Products depicted in this literature are for demonstration purposes only. Actual products offered for sale may vary in design, required attachments and safety features. Consult your local Toro Distributor.

"Vanguard" and "Magnetron" are registered trademarks of the Briggs & Stratton Corporation.

"Donaldson" is a registered trademark of the Donaldson Company.

\*\*Must be used in conjunction with Finish Grader (08867).

The Sand Pro 2020 are manufactured in Tomah, WI ISO 9002 Certified Plant.



## Free Manuals Download Website

<http://myh66.com>

<http://usermanuals.us>

<http://www.somanuals.com>

<http://www.4manuals.cc>

<http://www.manual-lib.com>

<http://www.404manual.com>

<http://www.luxmanual.com>

<http://aubethermostatmanual.com>

Golf course search by state

<http://golfingnear.com>

Email search by domain

<http://emailbydomain.com>

Auto manuals search

<http://auto.somanuals.com>

TV manuals search

<http://tv.somanuals.com>