7,200 RPM 3.5-Inch SAS / SATA Enterprise Hard Disk Drives

TOSHIBA Leading Innovation >>>

High storage capacities, enterprise-class reliability, optimized power consumption and performance efficiencies.



MK1001TRKB MK2001TRKB MK1002TSKB MK2002TSKB

The Toshiba MKx001TRKB and MKx002TSKB series hard disk drives (HDDs) feature high storage capacities, enterprise-class reliability, enhanced power condition state technology, and performance efficiencies which are critical to business operations.

With a top storage capacity of 2TB¹, the Toshiba MKx001TRKB and MKx002TSKB HDDs utilize a traditional 3.5-inch form factor, enabling system builders to leverage 3.5-inch based storage chassis. The high-capacity, cost-effective models feature 7,200 RPM spin speed and leading-edge 6Gb/sec Serial Attached SCSI (SAS) and 3Gb/ sec Serial ATA (SATA) interfaces.

Both series leverage the expertise and history of Toshiba in enterprise-class storage and offer similar features as traditional enterprise-class drives including 24 x 7 operation, Error Correction (ECC), Rotational Vibration (RV) technology for multi-drive systems, 1.2 million hours MTBF, and a 5-year warranty.

The MKx001TRKB and MKx002TSKB series HDDs are designed to support enterprise applications where reliability, high capacity, and performance are required. Specific applications include SAN, NAS, DAS, cloud storage, data centers, entry level servers and tiered storage system architecture.

- Lowest Cost Per GB Enterprise Storage Option
- 6Gb/sec Serial Attached SCSI (SAS) and 3Gb/sec (SATA) Interfaces
- Enhanced Power Condition State Technology
- Rotational Vibration (RV) Technology for Multi-drive Systems
- 5-Year Warranty

7,200 RPM 3.5-Inch SAS / SATA Enterprise Hard Disk Drives

| Series Overview | | | | | |
|--|---|--|----------------------------------|--------------------|--|
| Drive Capacity | 1TB ¹ | 2TB ¹ | 1TB ¹ | 2TB ¹ | |
| Drive Interface | Serial Attached SCSI (SAS-2) | | Serial ATA, Revision 2.6 (ATA-8) | | |
| Number of Platters (disks) | 2 | 4 | 2 | 4 | |
| Number of Data Heads | 4 | 8 | 4 | 8 | |
| RoHS Compliant | Yes | | | | |
| Transfer Rate to Host | SAS 6 Gb/s SATA 3 Gb/s | | | | |
| Performance | | | | | |
| Track-to-track Seek | | 1ms | | | |
| Average Seek Time | 9.5ms | | | | |
| Rotational Speed | 7,200 RPM | | | | |
| Average Latency | 4.17ms | | | | |
| Buffer Size | 16 | 16MB 64MB | | | |
| Power Requirements | | | | | |
| Voltage | | 5V (+/- 5%) | | | |
| Spin up (start) Power | 12V (+/-5%) @ 2.4A (peak) | | | | |
| Read/Write Power | 13 watts | | | | |
| Low Power Idle | 7 watts | | | | |
| Standby Power | 1.5 watts | | | | |
| Physical Size | | | | | |
| Dimensions (W) x (D) x (H) | 101.6 mm (4.00 in) x 147 mm (5.79 in) x 26.1 mm (1.03 in) | | | | |
| Weight | 800 g (28.2 oz) | | | | |
| Environmental | | | | | |
| Temp - Operating | | 5° to 55°C (41° to 131°F) | | | |
| Temp - Non-Operating | -40° to 70°C (-40° to 158°F) | | | | |
| Vibration - Operating | 7.35 m/s² (0.750 | G) (from 5 to 300Hz), | , 2.45 m/s² (0.25G) (1 | from 300 to 500Hz) | |
| Vibration - Non-Operating | | 49 m/s ² (5.0G) (from 5 to 500Hz) | | | |
| Shock - Operating | 686 m/s² (70G), 2ms | | | | |
| Shock - Non-Operating | 2,940 m/s² (300G), 2ms | | | | |
| Acoustics | | | | | |
| Acoustics (idle) | | 30 dB | | | |
| Acoustics (seek) | | 34 dB | | | |
| Reliability | | | | | |
| | 1,200,000 hours | | | | |
| Mean Time Between Failure (MTBF) | 5 years POH | | | | |
| Mean Time Between Failure (MTBF) Component Life | | 5 vear | s POH | | |

Visit us at: www.toshibastorage.com

Subject to Change: While Toshiba has made every effort at the time of publication to ensure the accuracy of the information provided herein, product specifications, configurations, prices, system/component/options availability are all subject to change without notice. Product image may represent design model.

© 2011 Toshiba America Information Systems, Inc. All rights reserved.

¹One Terabyte (1TB) = 1,000 Gigabytes (GB). One Gigabyte (1GB) means 10° = 1,000,000,000 bytes using powers of 10. A computer operating system, however, reports storage capacity using powers of 2 for the definition of 1GB = 2^{30} = 1,073,741,824 bytes, and therefore shows less storage capacity. Available storage capacity will also be less if the computer includes one or more pre-installed operating systems, pre-installed software applications, or media content. Actual formatted capacity may vary.

Free Manuals Download Website <u>http://myh66.com</u> <u>http://usermanuals.us</u> <u>http://www.somanuals.com</u> <u>http://www.4manuals.cc</u> <u>http://www.4manuals.cc</u> <u>http://www.4manuals.cc</u> <u>http://www.4manuals.com</u> <u>http://www.404manual.com</u> <u>http://www.luxmanual.com</u> <u>http://aubethermostatmanual.com</u> Golf course search by state

http://golfingnear.com Email search by domain

http://emailbydomain.com Auto manuals search

http://auto.somanuals.com TV manuals search

http://tv.somanuals.com