### 7,200 RPM

### 2.5-Inch SATA Hard Disk Drives



High Performance and Lower
Power Consumption Across Broad
Line of Capacity Points



MK1661GSYN MK2561GSYN MK3261GSYN MK5061GSYN MK6461GSYN

Designed for optimal performance and high durability, the Toshiba MKxx61GSYN series of 7,200 RPM hard disk drives deliver 160 to 640GB¹ of storage capacity in the 2.5-inch form factor. The MKxx61GSYN family of Serial ATA drives offers extreme power efficiency and superior operating acoustics over 3.5-inch drives for today's high-end notebook PCs, gaming laptops, and mobile workstations as well as Energy Star® all-in-one and slimline desktop PCs.

Toshiba couples greater power efficiency of the MKxx61GSYN drives with other environmentally-conscious solutions including RoHS-compliance and utilization of components that reduce PVC (polyvinyl chloride) and BFRs (brominated flame retardants) as well as meet halogen-free<sup>2</sup> standards.

An optional free-fall sensor responds to drop events and securely locks the recording heads in place off the media before system impact. This provides an additional level of ruggedness and durability to the MKxx61GSYN drives and is particularly suitable for mobile applications.

- Up to 640GB¹ of Storage Capacity
- Optimal Performance at 7,200 RPM
- Serial ATA 3.0 Gb/sec, Revision 2.6 / ATA-8
- 16MB Cache Buffer
- Optional Free-fall Sensor

# Hard Drive

# 7,200 RPM

# 2.5-Inch SATA Hard Disk Drives



Series Overview	MK1661GSYN	MK2561GSYN	MK3261GSYN	MK5061GSYN	MK6461GSY	
Drive Capacity	160GB <sup>1</sup>	250GB <sup>1</sup>	320GB <sup>1</sup>	500GB <sup>1</sup>	640GB <sup>1</sup>	
Drive Interface	Serial ATA 3.0 Gb/sec, Revision 2.6 (ATA-8)					
Number of Platters (disks)	1	1	1	2	2	
Number of Data Heads	1	2	2	4	4	
RoHS Compliant		Yes				
Transfer Rate to Host			3 Gb/sec			
Performance						
Track-to-track Seek			1ms			
Average Seek Time			12 ms			
Rotational Speed			7,200 RPM			
Average Latency			4.16ms			
Buffer Size			16MB			
Power Requirement	nts					
Voltage			5V (+/-5%)			
Spin up (start) Power			5.5 watts			
Seek Power			2.3 watts			
Read/Write Power			2.1 watts			
Low Power Idle			0.8 watts			
Standby Power			0.16 watts			
Sleep Power			0.13 watts			
Physical Size						
Dimensions (W) x (D) x (H)		69.85 mm (2.75") x 100 mm (3.94") x 9.5 mm (0.37")				
Weight	98 g (3.46 oz)	98 g (3.46 oz)	98 g (3.46 oz)	115 g (4.06 oz)	115 g (4.06 oz)	
Environmental						
Temp - Operating		5° to 55°C (41° to 131°F)				
Temp - Non-Operating		-40° to 65°C (-40° to 149°F)				
Vibration - Operating		9.8 m/s <sup>2</sup> (1.0G) 5 to 500 Hz				
Vibration - Non-Operating		49 m/s <sup>2</sup> (5.0G) 15 to 500 Hz				
Shock - Operating		3,185 m/s <sup>2</sup> (325G) 2ms				
Shock - Non-Operating		8,820 m/s² (900G) 1ms				
Acoustics						
Acoustics Acoustics (idle)	23 dB	23 dB	23 dB	26 dB	26 dB	

Limited Warranty

### Visit us at: www.toshibastorage.com

Subject to Change: While Toshiba has made every effort at the time of publication to ensure the accuracy of the information provided herein, product specifications, configurations, prices, system/component/options availability are all subject to change without notice. Product image may represent design model.

 $\ensuremath{\texttt{©}}$  2012 Toshiba America Electronic Components, Inc. All rights reserved.

3 years (from date of purchase)

MKXX61GSYN 09/2012

 $<sup>^{1}</sup>$  One Gigabyte (1 GB) means  $10^{9}=1,000,000,000$  bytes using powers of 10. A computer operating system, however, reports storage capacity using powers of 2 for the definition of 1 GB =  $2^{30}=1,073,741,824$  bytes, and therefore shows less storage capacity. Available storage capacity will also be less if the computer includes one or more pre-installed operating systems, pre-installed software applications, or media content. Actual formatted capacity may vary.

<sup>&</sup>lt;sup>2</sup>Products are considered "Halogen-free" when each homogeneous material in the product consists of a maximum bromine or chlorine concentration of 900 parts per million for weight percentage. Group VIIA halogens, fluorine, iodine and astatine, are not restricted in the industry-standard, ENV0199 description. Toshiba also restricts concentrations of red phosphorus and antimony trioxide in its Halogen-free HDD products.

Free Manuals Download Website

http://myh66.com

http://usermanuals.us

http://www.somanuals.com

http://www.4manuals.cc

http://www.manual-lib.com

http://www.404manual.com

http://www.luxmanual.com

http://aubethermostatmanual.com

Golf course search by state

http://golfingnear.com

Email search by domain

http://emailbydomain.com

Auto manuals search

http://auto.somanuals.com

TV manuals search

http://tv.somanuals.com