

The Biggest Thing in Little LCD Monitors

LCD-501 LCD-501X3



LCD- 501X3
Triple 19" Rack Mount

Active Matrix 5" Color LCD Monitor



LM-BR-501
Unit in Brass Flush Mount Kit



LCD- 501

- Wide operating power range (10 ~ 30VDC)
- Picture on demand/power saving feature
- Front mounted stereo headphone jack for private listening (no built-in speakers)
- Slim space saving design
- For color and B&W applications
- Compact and light weight for easy installation or mobile use
- Low power consumption
- Case made of durable ABS plastic
- Active matrix technology allows wide viewing angle
- Active matrix technology eliminates distortion
- Front controls for color, brightness and audio volume
- A/C adaptor, Part No. AC-2000, included

Optional Accessories

BB-5000	Metal bracket for Anton-Bauer battery
BP-563	Rechargeable 2600mAH battery pack provides approximately 5 hrs. of operation
DC-12	Car Cord
DC-12D	Dual Car Cord
HS-1	Hot Shoe mount
LM-BR-501	Brass Flush Mount Kit (see above) Requires rear access to install. Dimensions (WH): 5.82" x 5.43" Installer's cut-out: 5.15"(W) x 4.44"(H)
MB-1	Desk Stand
MB-72M	Metal Mounting Bracket
RM-501	EIA Rack Mount Panel, black metal (shown above) 19"(W) x 5.3"(H) x 0.8"(D) (occupies 3 RU) Holds 3 monitors.
WM-1	Wall mount bracket

- Display: 5" TFT LCD active matrix
- Back Light: CCFT
- Input Signal: NTSC/PAL (auto switching)
- Resolution: 600(H) x 234(V) dots
- Active Area: 102.6(H) x 73.9(V)
- Dot Pitch: 0.171(H) x 0.316(V)
- Brightness rating: 240 cd/m² (Nit)
- Number of Pixels: 140,400
- Contrast Ratio: 120:1
- Viewing angle L/R/T/B: 55°/55°/15°/35°
- Pixel Configuration: Stripe
- Power Requirement: 12VDC (1A, + pin)
- Operating Power Range: 10 ~ 30 VDC
- Power Consumption: 7 W (max.)
- Input Signal Level: 1.0V P-P (positive) 75 Ohm
- Audio Input Level: 1.0V P-P
- Audio output: 0.3 W
- Audio Input Impedance: 10K ohm
- Audio Band Width: 15 KHz
- Dimensions (WHD): 146 x 105 x 30.5mm / 5.7" x 4.1" x 1.2"
- Actual visible screen size(WH): 102 x 74mm / 4" x 2.9"
- Monitor Mounting: Mounting pad with ¼-20 threaded socket
- Operating temperature: 50 ~ 104°F or 10 ~ 40°C, 85% RH max.
- Storage temperature: -4 ~ 140°F or -20 ~ 60°C, 85% RH max.
- DIN Cable Connections: RCA video IN
RCA right audio IN
RCA left audio IN
2.1 DC IN jack
- LCD-501 Weight: Net: 363g / 12.8oz.
Gross: 1.2 kg. / 2.7 lbs.
- LCD-501X3 Weight: Net: 2.4 kg / 5.3 lbs.
Gross: Est. 5.3 kg. / 11.8 lbs.

GSA Schedule For LCD-501X3 only.
GS-07F-0069L, SIN: 246-42(1), 246-50

Specifications subject to change without notice ©2008 ToteVision 10K
Available through:

Free Manuals Download Website

<http://myh66.com>

<http://usermanuals.us>

<http://www.somanuals.com>

<http://www.4manuals.cc>

<http://www.manual-lib.com>

<http://www.404manual.com>

<http://www.luxmanual.com>

<http://aubethermostatmanual.com>

Golf course search by state

<http://golfingnear.com>

Email search by domain

<http://emailbydomain.com>

Auto manuals search

<http://auto.somanuals.com>

TV manuals search

<http://tv.somanuals.com>