

10.4" Color LCD with Component Input

LCD-1048HDM



Active Matrix 10.4" Color LCD Monitor in Metal Case

Tempered glass helps to protect display panel.

Screw-down DC feature provides additional security for power connection.

Composite video BNC input provides security for video connection.

Durable metal case helps monitor to withstand severe conditions in the field.

- 3mm thick tempered glass helps to protect display panel from damage in the field.
- HD compatible (supports 480p/i, 720p, 1080p/i)
- RS-232 serial control provided
- Composite video BNC IN/OUT capability
- Underscan capability
- On-screen display controls, with front controls for power, Select, Menu, and Volume Up/Down.
- Wireless remote control provided.
- Hot key on remote control allows easy toggeling between composite, S-Video, component, & PC inputs
- Rear IR jack allows direct connection for use with IR repeater systems
- Speaker output on board allows screw down connection for R/L audio
- Built-in amplifier provides ample power to drive right and left stereo 8 ohm speakers
- Made of durable metal with black powder coating.
- Built-in interface and proper cable exiting for wall arm mounting, VESA 75mm compliant
- Response time: 15/25 ms (rising/falling)
- SPS included, 100~240 VAC


- Display: 10.4" TFT LCD active matrix
- Back Light: 2 x CCFT
- Input Signal: [Composite, component, & S-Video, NTSC/PAL auto sensing] analog RGB
- Dot Pitch: 0.206 (H) x 0.206 (V)mm
- Resolution: 1024(H) x 768(V) [700 lines for CCTV] or
- Number of Pixels: 786,432 dots
- Brightness Rating: 350 cd/m² (Nit)
- Colors: 262,144
- Contrast Ratio: 500:1
- Viewing Angle L/R/T/B: 90/90/90/90 degrees
- Pixel Configuration: RGB Vertical Stripe
- Audio output: 5W x 2, 8 ohm
- Dimensions including BNC jack (WHD): 247 x 215 x 58mm / 9.7" x 8.5" x 2.3"
- Actual visible screen size (WH): 210 x 158mm / 8.3" x 6.2"
- Operating temperature: 50~104°F or 10~40°C
- Storage temperature: 14~158°F or -10~70°C
- Power requirement/consumption: 12VDC, 2A, negative ground/24W
- Rear Terminal Connections: 15-pin mini D-sub, 4-pin RS-232, S-Video, component (RCA x 3), 3.5 PC audio IN, RCA x 2 and BNC composite IN/OUT, RCA L/R audio IN, 3.5 audio line OUT, 3.5 IR IN, L/R screw down speaker connectors, 2.1mm DC jack and screw down DC connector
- LCD-1048HDM Weight: Net: 2.4 kg. / 5.3 lbs. Gross: 3.7 kg. / 8.05 lbs

Optional Accessories

- DC-1500 Factory approved car cord
- HM-400 Under-cabinet hinge mount
- WM-31 Wall mount bracket (fixed)
- WM-302 Wall mount with swing arm & 4-way adjustable



HM-400



WM-302

Free Manuals Download Website

<http://myh66.com>

<http://usermanuals.us>

<http://www.somanuals.com>

<http://www.4manuals.cc>

<http://www.manual-lib.com>

<http://www.404manual.com>

<http://www.luxmanual.com>

<http://aubethermostatmanual.com>

Golf course search by state

<http://golfingnear.com>

Email search by domain

<http://emailbydomain.com>

Auto manuals search

<http://auto.somanuals.com>

TV manuals search

<http://tv.somanuals.com>