



**Tripp Lite**  
1111 West 35th Street  
Chicago, IL 60609 USA  
Telephone: +(773) 869 1234  
E-mail: [saleshelp@tripplite.com](mailto:saleshelp@tripplite.com)

## Model #: N201-010-YW

### 10-ft. Yellow Cat6 Gigabit Snagless Patch Cable

#### Highlights

- Premium cabling for Category 6, Category 5e and Category 5 applications rated for 550 MHz/1 Gbps communications
- Designed to meet Category 6 specifications; reduces cross-talk and return loss
- IEC 802.3ab
- PVC 4-pair stranded UTP
- All cables feature boots with integral strain-relief and RJ45 (Male) connectors



#### Description

With Tripp Lite's new category 6 molded patch cables you can stay ahead of the game by using this high-speed cable to distribute data, voice and video. These cables deliver stable performance up to 550MHz. Each comes UL verified meets EIA/TIA Cat6 TIA/EIA-568-B-2.1 draft 9 standards. Constructed with high-quality copper wire and a staggered-pin plug design, near-end crosstalk levels are kept to a minimum. Designed for use in category 6, category 5e and category 5 applications. Cat6 cables are available in a variety of colors with a snagless boot preventing cable snags. Tripp Lite warrants this product to be free from defects in materials and workmanship for life.

#### System Requirements

- For 1000 Base-T (1Gbps Ethernet), 10/100 Base-T (Ethernet), 100 Mbps TPDDI, 155 Mbps ATM, ISDN, voice and Token Ring TYPE 3 applications as well as EIA/TIA applications.



#### Package Includes

- 10-ft. Cat6 Yellow Gigabit Patch Cord Snagless Molded

#### Features

- Meets category 6 cabling standards
- Premium cabling for category 6, category 5e and category 5 applications
- Length: 10 ft./Color: Yellow/Connectors: RJ45 male
- Drastically reduce impedance & structural return loss compared to standard 100MHz wire
- High-quality copper wire and a staggered-pin plug design to keep near-end crosstalk levels to a minimum
- Feature molded connectors with integral strain relief
- Snagless design protects the locking tabs on the RJ45 connectors from being damaged or snapped off during installation
- PVC 4-pair stranded UTP
- Deliver stable performance up to 550MHz/1 Gbps communication
- Meets most current industry standards including IEEE 802.3ab, IEEE 802.5, ANSI/EIA/TIA 568, ISO/IEC 11801 and ETL (category 6 draft 11)
- Available in other colors and lengths
- Warranted to be free from defects in materials and workmanship for life

#### Specifications

<b>OVERVIEW</b>	
<b>Intended Application</b>	Computer Networking
<b>PHYSICAL</b>	
<b>Color</b>	Yellow
<b>Style</b>	Cat6/6e/6a
<b>Length</b>	10 ft.
<b>CONNECTIONS</b>	
<b>Connector A</b>	 RJ45 (MALE)
<b>Connector B</b>	 RJ45 (MALE)
<b>CERTIFICATIONS</b>	
<b>Certifications</b>	RoHS-Compliant

## Related Items

<b>Patch Cables</b>		
N201-003-GN	3-ft. Green Cat6 Gigabit Snagless Patch Cable	Qty: [optional]
N201-003-GY	3-ft. Gray Cat6 Gigabit Snagless Patch Cable	Qty: [optional]
N201-005-BL	5-ft. Blue Cat6 Gigabit Snagless Patch Cable	Qty: [optional]
N201-007-BL	7-ft. Blue Cat6 Gigabit Snagless Patch Cable	Qty: [optional]
N201-010-BL	10-ft. Blue Cat6 Gigabit Snagless Patch Cable	Qty: [optional]
N201-014-BL	14-ft. Blue Cat6 Gigabit Snagless Patch Cable	Qty: [optional]
N201-025-BL	25-ft. Blue Cat6 Gigabit Snagless Patch Cable	Qty: [optional]

More information, including related products, owner's manuals, and additional technical specifications, can be found online at [www.tripplite.com/en/products/model.cfm?txtModelID=3112](http://www.tripplite.com/en/products/model.cfm?txtModelID=3112).

©2009 Tripp Lite. All Rights Reserved.

## Free Manuals Download Website

<http://myh66.com>

<http://usermanuals.us>

<http://www.somanuals.com>

<http://www.4manuals.cc>

<http://www.manual-lib.com>

<http://www.404manual.com>

<http://www.luxmanual.com>

<http://aubethermostatmanual.com>

Golf course search by state

<http://golfingnear.com>

Email search by domain

<http://emailbydomain.com>

Auto manuals search

<http://auto.somanuals.com>

TV manuals search

<http://tv.somanuals.com>