



Model #: PDU1415

Basic PDU / Power Distribution Unit - Safe, reliable power distribution for critical networking equipment



Highlights

- 24 inch PDU supports vertical, horizontal or wallmount installation
- 14 NEMA 5-15R outlets
- 15 foot AC input cord with NEMA 5-15P plug
- 15A circuit breaker
- Switchless design

Description

Tripp Lite's PDU1415 AC power distribution unit offers 120 volt, 15 amp capacity in a 24 inch mountable housing. Detachable mounting flanges are configurable for vertical or horizontal power distribution in a variety of applications. Supports 0U vertical mounting in the cable management area of most rack enclosures. Unfiltered electrical pass-through without a power switch makes PDU1415 ideal for distributing alternate waveform UPS or generator power in rack enclosures, network closets and more. Includes 14 NEMA5-15R outlets, 15-ft. AC power cord, 15 amp circuit breaker, grounding lug and rugged all-metal case design.

PLUG/OUTLETS - Input: NEMA 5-15P/Output: 14 NEMA5-15R

ELECTRICAL - 120V AC, 50/60Hz, 15A (Requires NEMA 5-15R wall receptacle)

FORMAT - 24 inch mountable strip format

Applications

Multi-outlet power distribution unit is the ideal means of powering multiple loads in racks, wallmount and other applications, such as
internetworking, PC systems, telecommunications, audio/video, security, sound reinforcement and more. Ideal for distribution of UPS,
generator or commercially derived AC power to protected equipment.

Package Includes

- PDU1415 power strip
- Instruction manual with warranty information

Features

- Corded AC power distribution unit with 15 amp capacity and 14 AC receptacles
- Versatile all-metal 24 inch cabinet with detachable mounting flanges supports horizontal or vertical mounting in equipment racks, network closets and wallmount applications
- Unfiltered electrical pass-through reliably distributes alternate waveform AC power from UPS or generator to supported equipment
- 14 NEMA5-15R output receptacles accept common NEMA5-15 equipment plugs
- 15 foot AC cord NEMA5-15P plug connection
- Switch-free design prevents the potential for accidental shutoff of connected loads
- 15 amp electrical capacity with circuit breaker

Specifications

Voltage compatibility 120V 50 / 60Hz 50 / 60Hz	SYSTEM OVERVIEW	
Frequency compatibility 50 / 60Hz		
OUTPUT Output watts 1800 Output nominal voltage 120V Outed quantity / type 14 NEMA 5-15R Overload protection 15A INPUT Maximum input amps Input cornection type NEMA 5-15P Input cord length 15 ft. Recommended Electrical Service 120V Switches No switch PHYSICAL Shipping weight (lbs) Shipping Dimensions 2.75 x 27.25 x 8.25 Khipping Dimensions 7 x 69.2 x 21 (HWD/Icm) 7 x 69.2 x 21 Unit weight (lbs) 4.6 Unit weight (kg) 2.1 Unit Dimensions (HWD/Im) 4.45 x 65.4 x 5.7 Material of construction Stell Form factors supported Vertical or horizontal mounting supported in wallmount applications, racks and a variety of other surface types Style Rackmount, Vertical Rackmount, Wallmount/Under-Counter CERTIFICATIONS CERTIFICATIONS		
Output watts 1800 Output nominal voltage 120V Overload protection 15A INPUT Maximum input amps Maximum input amps 15A Input connection type NEMA 5-15P Input cond length 16 ft. Recommended Electrical Service 120V Service No switch PHYSICAL Shipping weight (lbs) Shipping weight (kg) 2.4 Shipping Dimensions 2.75 x 27.25 x 8.25 (HWD/nn) 7 x 69.2 x 21 Unit weight (kg) 2.6 Unit bimensions (HWD/m) 1.75 x 25.75 x 2.25 Unit Dimensions (HWD/m) 4.45 x 65.4 x 5.7 Material of construction Steel Form factors supported Vertical or horizontal mounting supported in wallmount applications, racks and a variety of other surface types Style Rackmount, Vertical Rackmount, Wallmount/Under-Counter CERTIFICATIONS Certifications Tested to UL60950-1 (USA) and CAN/CSA C22.2 No. 60950-1-03 (Canada)		50 / 60Hz
Output nominal voltage 120V Outlet quantity / type 14 NEMA 5-15R Overload protection 15A INPUT Maximum input amps 15A Input connection type NEMA 5-15P Input cord length 15 ft. Recommended Electrical service 120V LEDS ALARMS & SWITCHES No switch Switches No switch PHYSICAL Shipping weight (libs) Shipping Dimensions (HWD/in) 5.2 Shipping Dimensions (HWD/in) 7 x 69.2 x 21. HWD/om) 7 x 69.2 x 21 Unit weight (libs) 4.6 Unit weight (kg) 2.1 Unit Dimensions (HWD/in) 1.75 x 25.75 x 2.25 Unit Dimensions (HWD/cm) 4.45 x 65.4 x 5.7 Material of construction Steel Form factors supported Vertical or horizontal mounting supported in wallmount applications, racks and a variety of other surface types Style Rackmount, Vertical Rackmount, Wallmount/Under-Counter CERTIFICATIONS Reckmount, Vertical Rackmount, Wallmount/Under-Counter	OUTPUT	
Outlet quantity / type 14 NEMA 5-15R Overload protection 15A INPUT 15A Imput connection type NEMA 5-15P Input cord length 15 ft. Recommended Electrical services 120V Service No switch PHYSICAL Shipping weight (lbs) Shipping Dimensions (HWD/in) 2.75 x 27.25 x 8.25 Shipping Dimensions (HWD/cm) 7 x 69.2 x 21 Unit weight (kg) 2.4 Unit weight (kg) 2.1 Unit wild pling Dimensions (HWD/cm) 4.6 Unit wild pling Dimensions (HWD/cm) 1.75 x 25.75 x 2.25 Unit Dimensions (HWD/cm) 4.45 x 85.4 x 5.7 Material of construction Steel Form factors supported Vertical or horizontal mounting supported in wallmount applications, racks and a variety of other surface types Style Rackmount, Vertical Rackmount, Wallmount/Under-Counter CERTIFICATIONS Tested to UL60950-1 (USA) and CAN/CSA C22.2 No. 60950-1-03 (Canada)	Output watts	1800
Overload protection 15A INPUT	Output nominal voltage	120V
Maximum input amps 15A Input connection type NEMA 5-15P Input cord length 15 ft. Recommended Electrical Service 120V Switches No switch PHYSICAL Shipping weight (ibs) 5.2 Shipping Dimensions (HWD/ini) 7 x 69.2 x 21 Unit weight (kg) 2.1 Unit bimensions (HWD/im) 1.75 x 25.75 x 2.25 Unit Dimensions (HWD/im) 4.45 x 65.4 x 5.7 Material of construction Steel Form factors supported Vertical Rackmount, Wallmount/Under-Counter CERTIFICATIONS Certifications Tested to UL60950-1 (USA) and CAN/CSA C22.2 No. 60950-1-03 (Canada) WARRANTY	Outlet quantity / type	14 NEMA 5-15R
Maximum input amps 15A Input connection type NEMA 5-15P Input cord length 15 ft. Recommended Electrical 20V Service 120V LEDS ALARMS & SWITCHES Switches No switch PHYSICAL Shipping weight (lbs) 5.2 Shipping Dimensions (HWD/m) 2.75 x 27.25 x 8.25 (HWD/m) 1.75 x 25.75 x 2.25 Unit Dimensions (HWD/m) 1.75 x 25.75 x 2.25 Unit Dimensions (HWD/m) 4.45 x 65.4 x 5.7 Material of construction Steel Form factors supported Vertical or horizontal mounting supported in wallmount applications, racks and a variety of other surface types Style Rackmount, Vertical Rackmount, Wallmount/Under-Counter CERTIFICATIONS Certifications Tested to UL60950-1 (USA) and CAN/CSA C22.2 No. 60950-1-03 (Canada) WARRANTY	Overload protection	15A
Input cornection type NEMA 5-15P Input cord length 15 ft. Recommended Electrical 120V Service 120V IEDS ALARMS & SWITCHES Switches No switch PHYSICAL Shipping weight (lbs) 5.2 Shipping Dimensions (HWD/m) 2.75 × 27.25 × 8.25 Shipping Dimensions (HWD/m) 4.6 Unit weight (lbs) 4.6 Unit blimensions (HWD/m) 1.75 × 25.75 × 2.25 Unit Dimensions (HWD/m) 4.45 × 65.4 × 5.7 Material of construction Steel Form factors supported Vertical or horizontal mounting supported in wallmount applications, racks and a variety of other surface types Style Rackmount, Vertical Rackmount, Wallmount/Under-Counter CERTIFICATIONS Tested to UL60950-1 (USA) and CAN/CSA C22.2 No. 60950-1-03 (Canada) WARRANTY	INPUT	
Input cord length 15 ft. Recommended Electrical 20V Service 120V LEDS ALARMS & SWITCHES Switches No switch PHYSICAL Shipping weight (lbs) 5.2 Shipping Dimensions (HWD/in) 7 x 69.2 x 21 (HWD/in) Unit weight (lbs) 4.6 Unit weight (kg) 2.1 Unit Dimensions (HWD/in) 1.75 x 25.75 x 2.25 Material of construction Steel Form factors supported Vertical or horizontal mounting supported in wallmount applications, racks and a variety of other surface types Style Rackmount, Vertical Rackmount, Wallmount/Under-Counter CERTIFICATIONS Certifications Tested to UL60950-1 (USA) and CAN/CSA C22.2 No. 60950-1-03 (Canada) WARRANTY	Maximum input amps	15A
Recommended Electrical Service LEDS ALARMS & SWITCHES Switches No switch PHYSICAL Shipping weight (Ibs) 5.2 Shipping Dimensions (HWD/in) 7 x 69.2 x 21 Unit weight (Ibs) 4.6 Unit weight (Ibs) 1.75 x 25.75 x 2.25 Unit Dimensions (HWD/cm) 4.45 x 65.4 x 5.7 Material of construction Form factors supported Vertical or horizontal mounting supported in wallmount applications, racks and a variety of other surface types Style Rackmount, Vertical Rackmount, Wallmount/Under-Counter CERTIFICATIONS Certifications Tested to UL60950-1 (USA) and CAN/CSA C22.2 No. 60950-1-03 (Canada) WARRANTY	Input connection type	NEMA 5-15P
Service LEDS ALARMS & SWITCHES Switches No switch PHYSICAL Shipping weight (lbs) 5.2 Shipping Dimensions (HWD/in) Shipping Dimensions (HWD/cm) Unit weight (lbs) 4.6 Unit pimensions (HWD/in) 1.75 x 25.75 x 2.25 Unit Dimensions (HWD/cm) 4.45 x 65.4 x 5.7 Material of construction Steel Form factors supported Vertical or horizontal mounting supported in wallmount applications, racks and a variety of other surface types Style Rackmount, Vertical Rackmount, Wallmount/Under-Counter CERTIFICATIONS Certifications Tested to UL60950-1 (USA) and CAN/CSA C22.2 No. 60950-1-03 (Canada) WARRANTY	Input cord length	15 ft.
Switches No switch PHYSICAL Shipping weight (lbs) 5.2 Shipping Dimensions (HWD/in) 2.4 Shipping Dimensions (HWD/cm) 4.6 Unit weight (kg) 2.1 Unit Dimensions (HWD/cm) 4.5 x 5.75 x 2.25 Unit Dimensions (HWD/cm) 4.5 x 65.4 x 5.7 Material of construction Steel Form factors supported Vertical or horizontal mounting supported in wallmount applications, racks and a variety of other surface types Style Rackmount, Vertical Rackmount, Wallmount/Under-Counter CERTIFICATIONS Certifications Tested to UL60950-1 (USA) and CAN/CSA C22.2 No. 60950-1-03 (Canada)	Recommended Electrical Service	120V
Shipping weight (lbs) 5.2 Shipping weight (kg) 2.4 Shipping Dimensions (HWD/in) 2.75 x 27.25 x 8.25 Shipping Dimensions (HWD/cm) 7 x 69.2 x 21 Unit weight (lbs) 4.6 Unit weight (kg) 2.1 Unit Dimensions (HWD/cm) 1.75 x 25.75 x 2.25 Unit Dimensions (HWD/cm) 4.45 x 65.4 x 5.7 Material of construction Steel Form factors supported Vertical or horizontal mounting supported in wallmount applications, racks and a variety of other surface types Style Rackmount, Vertical Rackmount, Wallmount/Under-Counter CERTIFICATIONS Certifications Tested to UL60950-1 (USA) and CAN/CSA C22.2 No. 60950-1-03 (Canada) WARRANTY	LEDS ALARMS & SWITCHES	
Shipping weight (kg) Shipping Dimensions (HWD/in) Shipping Dimensions (HWD/cm) 7 x 69.2 x 21 Unit weight (kg) 2.1 Unit weight (kg) 2.1 Unit Dimensions (HWD/cm) Material of construction Steel Form factors supported Vertical or horizontal mounting supported in wallmount applications, racks and a variety of other surface types Style Rackmount, Vertical Rackmount, Wallmount/Under-Counter CERTIFICATIONS Certifications Tested to UL60950-1 (USA) and CAN/CSA C22.2 No. 60950-1-03 (Canada) WARRANTY	Switches	No switch
Shipping weight (kg) Shipping Dimensions (HWD/in) 2.75 x 27.25 x 8.25 Shipping Dimensions (HWD/cm) 7 x 69.2 x 21 Unit weight (lbs) 4.6 Unit weight (kg) 2.1 Unit Dimensions (HWD/cm) 4.45 x 65.4 x 5.7 Material of construction Steel Form factors supported Vertical or horizontal mounting supported in wallmount applications, racks and a variety of other surface types Style Rackmount, Vertical Rackmount, Wallmount/Under-Counter CERTIFICATIONS Certifications Tested to UL60950-1 (USA) and CAN/CSA C22.2 No. 60950-1-03 (Canada) WARRANTY	PHYSICAL	
Shipping Dimensions (HWD/in) 2.75 x 27.25 x 8.25 Shipping Dimensions (HWD/cm) 7 x 69.2 x 21 Unit weight (lbs) 4.6 Unit weight (kg) 2.1 Unit Dimensions (HWD/in) 1.75 x 25.75 x 2.25 Unit Dimensions (HWD/cm) 4.45 x 65.4 x 5.7 Material of construction Steel Form factors supported Vertical or horizontal mounting supported in wallmount applications, racks and a variety of other surface types Style Rackmount, Vertical Rackmount, Wallmount/Under-Counter CERTIFICATIONS Certifications Tested to UL60950-1 (USA) and CAN/CSA C22.2 No. 60950-1-03 (Canada) WARRANTY	Shipping weight (lbs)	5.2
Shipping Dimensions (HWD/cm) 7 x 69.2 x 21 Unit weight (lbs) 4.6 Unit weight (kg) 2.1 Unit Dimensions (HWD/cm) 1.75 x 25.75 x 2.25 Unit Dimensions (HWD/cm) 4.45 x 65.4 x 5.7 Material of construction Steel Form factors supported Vertical or horizontal mounting supported in wallmount applications, racks and a variety of other surface types Style Rackmount, Vertical Rackmount, Wallmount/Under-Counter CERTIFICATIONS Certifications Tested to UL60950-1 (USA) and CAN/CSA C22.2 No. 60950-1-03 (Canada)	Shipping weight (kg)	2.4
(HWD/cm) Unit weight (lbs) 4.6 Unit weight (kg) 2.1 Unit Dimensions (HWD/in) 1.75 x 25.75 x 2.25 Unit Dimensions (HWD/cm) 4.45 x 65.4 x 5.7 Material of construction Steel Form factors supported Vertical or horizontal mounting supported in wallmount applications, racks and a variety of other surface types Style Rackmount, Vertical Rackmount, Wallmount/Under-Counter CERTIFICATIONS Certifications Tested to UL60950-1 (USA) and CAN/CSA C22.2 No. 60950-1-03 (Canada) WARRANTY	Shipping Dimensions (HWD/in)	2.75 x 27.25 x 8.25
Unit Dimensions (HWD/in) 1.75 x 25.75 x 2.25 Unit Dimensions (HWD/cm) 4.45 x 65.4 x 5.7 Material of construction Steel Form factors supported Vertical or horizontal mounting supported in wallmount applications, racks and a variety of other surface types Style Rackmount, Vertical Rackmount, Wallmount/Under-Counter CERTIFICATIONS Certifications Tested to UL60950-1 (USA) and CAN/CSA C22.2 No. 60950-1-03 (Canada) WARRANTY	Shipping Dimensions (HWD/cm)	7 x 69.2 x 21
Unit Dimensions (HWD/in) 1.75 x 25.75 x 2.25 Unit Dimensions (HWD/cm) 4.45 x 65.4 x 5.7 Material of construction Steel Form factors supported Vertical or horizontal mounting supported in wallmount applications, racks and a variety of other surface types Style Rackmount, Vertical Rackmount, Wallmount/Under-Counter CERTIFICATIONS Certifications Tested to UL60950-1 (USA) and CAN/CSA C22.2 No. 60950-1-03 (Canada) WARRANTY	Unit weight (lbs)	4.6
Unit Dimensions (HWD/cm) 4.45 x 65.4 x 5.7 Material of construction Steel Form factors supported Vertical or horizontal mounting supported in wallmount applications, racks and a variety of other surface types Style Rackmount, Vertical Rackmount, Wallmount/Under-Counter CERTIFICATIONS Certifications Tested to UL60950-1 (USA) and CAN/CSA C22.2 No. 60950-1-03 (Canada) WARRANTY	Unit weight (kg)	2.1
Material of construction Form factors supported Vertical or horizontal mounting supported in wallmount applications, racks and a variety of other surface types Style Rackmount, Vertical Rackmount, Wallmount/Under-Counter CERTIFICATIONS Certifications Tested to UL60950-1 (USA) and CAN/CSA C22.2 No. 60950-1-03 (Canada) WARRANTY	Unit Dimensions (HWD/in)	1.75 x 25.75 x 2.25
Form factors supported Vertical or horizontal mounting supported in wallmount applications, racks and a variety of other surface types Style Rackmount, Vertical Rackmount, Wallmount/Under-Counter CERTIFICATIONS Certifications Tested to UL60950-1 (USA) and CAN/CSA C22.2 No. 60950-1-03 (Canada) WARRANTY	Unit Dimensions (HWD/cm)	4.45 x 65.4 x 5.7
Style Rackmount, Vertical Rackmount, Wallmount/Under-Counter CERTIFICATIONS Certifications Tested to UL60950-1 (USA) and CAN/CSA C22.2 No. 60950-1-03 (Canada) WARRANTY	Material of construction	Steel
CERTIFICATIONS Certifications Tested to UL60950-1 (USA) and CAN/CSA C22.2 No. 60950-1-03 (Canada) WARRANTY	Form factors supported	Vertical or horizontal mounting supported in wallmount applications, racks and a variety of other surface types
Certifications Tested to UL60950-1 (USA) and CAN/CSA C22.2 No. 60950-1-03 (Canada) WARRANTY	Style	Rackmount, Vertical Rackmount, Wallmount/Under-Counter
WARRANTY	CERTIFICATIONS	
	Certifications	Tested to UL60950-1 (USA) and CAN/CSA C22.2 No. 60950-1-03 (Canada)
Product Warranty Period Lifetime	WARRANTY	
	Product Warranty Period	Lifetime

More information, including related products, owner's manuals, and additional technical specifications, can be found online at www.tripplite.com/en/products/model.cfm?txtModelID=2952.

©2009 Tripp Lite. All Rights Reserved.

Free Manuals Download Website

http://myh66.com

http://usermanuals.us

http://www.somanuals.com

http://www.4manuals.cc

http://www.manual-lib.com

http://www.404manual.com

http://www.luxmanual.com

http://aubethermostatmanual.com

Golf course search by state

http://golfingnear.com

Email search by domain

http://emailbydomain.com

Auto manuals search

http://auto.somanuals.com

TV manuals search

http://tv.somanuals.com