



Tripp Lite
1111 West 35th Street
Chicago, IL 60609 USA
Telephone: +(773) 869 1234
E-mail: saleshelp@tripplite.com

Model #: HT706TV

Home/Business Theater Surge Suppressor - High-performance surge and line-noise protection for all components



Highlights

- 7 outlets / 6 ft. cord
- 1080 joule rating
- Coaxial surge protection
- \$50,000 [Ultimate Lifetime Insurance](#) (USA and Canada only)

Description

Tripp Lite's HT706TV Home/Business Theater Surge Suppressor provides high-performance protection--1080 joules--stopping damaging surges and filtering disruptive line noise so components perform at their peak! You can see and hear the difference: sharper, crisper video; deeper, fuller audio and longer component life spans. Perfect for small home/business theater installations: high-definition TVs, satellite and A/V receivers, DVD/CD players and more. 7 outlets (with transformer spacing) and 1-line coaxial protection safeguard an entire home/business theater system. \$50,000 [Ultimate Lifetime Insurance](#) coverage (USA & Canada only). Includes two diagnostic LEDs, 6 ft. cord with a right-angle plug and 6 ft. coaxial cable.

Applications

- Perfect for small home/business theater installations: high-definition TVs, satellite and A/V receivers, DVD/CD players and more

Package Includes

- HT706TV Home/Business Theater Surge Suppressor
- 6 ft. coaxial cable
- Instruction manual with warranty information

Features

- 1080 joules surge suppression rating with EMI/RFI line noise filtering help components perform at their peak (sharper, crisper video; deeper, fuller audio and longer component life spans)
- \$50,000 [Ultimate Lifetime Insurance](#) (USA & Canada only) covers connected components against surge damage...for life!
- 7 surge-protected NEMA 5-15R AC outlets safeguard an entire home/business theater system
- Widely-spaced outlets accommodate up to 4 transformers
- 1 set of Type F surge-protected coaxial connectors (with included 6 ft. coaxial cable) safeguard components on cable, satellite or antenna line
- 6 ft. cord with right-angle NEMA 5-15P plug provides convenient location anywhere within a home/business theater system
- 2 diagnostic LEDs alert user to protection and grounding status
- Keyhole slots provide convenient wall or cabinet mounting
- Illuminated master switch provides one-touch power control over all components. Integrated circuit breaker protects against dangerous system overload
- High-impact plastic housing (black) stands up to the most demanding environments

- UL and CSA listed
- Lifetime product warranty

Specifications

| | |
|-----------------------------------|--|
| OVERVIEW | |
| Intended Application | Audio/Video |
| SYSTEM OVERVIEW | |
| Voltage compatibility | 120 VAC |
| Frequency compatibility | 50/60 Hz |
| OUTPUT | |
| Output volt amp capacity (amps) | 15 |
| Output watts | 1800 |
| Outlet quantity / type | 7 NEMA 5-15R |
| Transformer accommodation | Accommodates 4 transformers |
| INPUT | |
| Input connection type | NEMA 5-15P |
| Input cord gauge, type | 14 gauge, SJT |
| Input cord length (ft.) | 6 ft. |
| Input cord length (m) | 1.8 |
| Recommended Electrical Service | 120V (110-125V) |
| Input plug features | Space-saving right angle input plug |
| LEDS ALARMS & SWITCHES | |
| Diagnostic LEDs | Built-in LEDs confirm protection and grounding status |
| Switches | Combination AC circuit breaker and 2 position red illuminated on/off power switch |
| SURGE / NOISE SUPPRESSION | |
| Protection modes | Includes full normal mode (H-N) and common mode (N-G / H-G) line surge suppression |
| AC suppression joule rating | 1080 joules |
| Clamping voltage (RMS) | 150V |
| AC suppression response time | < 1 ns |
| UL1499 let through rating | 330V - UL verified |
| EMI / RFI filtering | Up to 40 dB |
| DATALINE SURGE SUPPRESSION | |
| Telephone/DSL Protection | No |
| Cable (Coax) Protection | Yes |
| Cable (Coax) Protection Details | 1 line |
| Network (Ethernet) Protection | No |
| PHYSICAL | |
| Shipping weight (lbs) | 5.02 |
| Shipping weight (kg) | 2.28 |
| Shipping Dimensions (HWD/in) | 2 x 15 x 6 |

| | |
|--|--|
| Shipping Dimensions (HWD/cm) | 5.1 x 38.1 x 15.2 |
| Unit weight (lbs) | 1 |
| Unit weight (kg) | 0.45 |
| Unit Dimensions (HWD/in) | 1.5 x 14 x 2.75 |
| Unit Dimensions (HWD/cm) | 3.8 x 35.6 x 7 |
| Material of construction | Plastic |
| Integrated keyhole mounting tabs | Keyhole mounting slots allow desk or wall mounting |
| AC line cord color | Black |
| Style | Strip |
| CERTIFICATIONS | |
| UL1449 1998 Rev. (AC Suppression) | UL1449 |
| UL1363 (Power Tap) | UL1363 |
| UL497A (Communications) | UL497A |
| cUL / CSA (Canada) | CSA |
| Approvals | Exceeds IEEE 587 category A&B specifications |
| WARRANTY | |
| Product Warranty Period | Lifetime |
| Connected Equipment Coverage | \$50,000 |

More information, including related products, owner's manuals, and additional technical specifications, can be found online at www.tripplite.com/en/products/model.cfm?txtModelID=2811.

©2009 Tripp Lite. All Rights Reserved.

Free Manuals Download Website

<http://myh66.com>

<http://usermanuals.us>

<http://www.somanuals.com>

<http://www.4manuals.cc>

<http://www.manual-lib.com>

<http://www.404manual.com>

<http://www.luxmanual.com>

<http://aubethermostatmanual.com>

Golf course search by state

<http://golfingnear.com>

Email search by domain

<http://emailbydomain.com>

Auto manuals search

<http://auto.somanuals.com>

TV manuals search

<http://tv.somanuals.com>