



**Tripp Lite**  
1111 West 35th Street  
Chicago, IL 60609 USA  
Telephone: +(773) 869 1234  
E-mail: [saleshelp@tripplite.com](mailto:saleshelp@tripplite.com)

## Model #: SK6-0B

### 6-Outlet, Direct Plug-In Surge Suppressor (Black)



#### Highlights

- 6 outlets/direct plug-in
- 750 joule rating
- \$10,000 Ultimate Lifetime Insurance (USA & Canada only)

#### Description

The SK6-0B Surge Suppressor from DataShield by Tripp Lite is ideal for protecting audio/video devices and printers. This direct plug-in surge suppressor features 6 outlets and 750 joules of surge energy absorption. \$10,000 Ultimate Lifetime Insurance (USA & Canada only).

#### Applications

- Personal computers, CAD/CAM/CAE workstations, network nodes, file servers, point of sale terminals, audio/visual devices, and more.

#### Package Includes

- SK6-0B Surge Suppressor
- Warranty information
- Instruction manual

#### Features

- 6 outlets: direct plug-in
- Surge energy absorption: 750 joules; 27,000 amps
- Lifetime warranty with \$10,000 Ultimate Lifetime Insurance (USA & Canada only)

#### Specifications

OVERVIEW	
Intended Application	Computer Networking
SYSTEM OVERVIEW	
Voltage compatibility	120 VAC
Frequency compatibility	50/60 Hz
OUTPUT	
Output volt amp capacity (amps)	15
Output watts	1800

Outlet quantity / type	6 NEMA 5-15R
Transformer accommodation	Holds up to 4 large transformer plugs
<b>INPUT</b>	
Input connection type	NEMA 5-15P input plug
Input cord length (ft.)	No Cord
Recommended Electrical Service	120V
Input plug features	120V, 15A
<b>SURGE / NOISE SUPPRESSION</b>	
Protection modes	Includes full normal mode (H-N) and common mode (N-G / H-G) line suppression
AC suppression joule rating	750 joules
Clamping voltage (RMS)	150V
AC suppression response time	< 1ns
AC suppression surge current rating	27,000
UL1499 let through rating	330V - UL Verified
Immunity	Conforms to IEE 587/ANSI C62.41
<b>DATALINE SURGE SUPPRESSION</b>	
Telephone/DSL Protection	No
Cable (Coax) Protection	No
Network (Ethernet) Protection	No
<b>PHYSICAL</b>	
Unit weight (lbs)	.40
Unit weight (kg)	.181
Unit Dimensions (HWD/in)	10.75 x 4.5 x 2
Unit Dimensions (HWD/cm)	27.30 x 11.43 x 5.08
Material of construction	Plastic
Integrated keyhole mounting tabs	Direct plug-in suppressor mounts directly to a wall receptacle
Receptacle Color	Black
Style	Direct plug-in
<b>CERTIFICATIONS</b>	
UL1449 1998 Rev. (AC Suppression)	UL 1449
Approvals	Exceeds IEEE 587 category A&B specifications
<b>WARRANTY</b>	
Product Warranty Period	Lifetime
Connected Equipment Coverage	\$10,000

More information, including related products, owner's manuals, and additional technical specifications, can be found online at [www.tripplite.com/en/products/model.cfm?txtModelID=4162](http://www.tripplite.com/en/products/model.cfm?txtModelID=4162).



## Free Manuals Download Website

<http://myh66.com>

<http://usermanuals.us>

<http://www.somanuals.com>

<http://www.4manuals.cc>

<http://www.manual-lib.com>

<http://www.404manual.com>

<http://www.luxmanual.com>

<http://aubethermostatmanual.com>

Golf course search by state

<http://golfingnear.com>

Email search by domain

<http://emailbydomain.com>

Auto manuals search

<http://auto.somanuals.com>

TV manuals search

<http://tv.somanuals.com>