



**Tripp Lite**  
 1111 West 35th Street  
 Chicago, IL 60609 USA  
 Telephone: +(773) 869 1234  
 E-mail: [saleshelp@tripplite.com](mailto:saleshelp@tripplite.com)

## Model #: SWIVEL6

### Protect It! Surge Suppressor



#### Highlights

- 6 rotatable outlets
- Direct plug-in design
- 1200 joule rating
- Diagnostic LEDs
- \$20,000 [Ultimate Lifetime Insurance](#) (USA, Puerto Rico & Canada only)

#### Description

The SWIVEL6 offers reliable surge and line noise protection. Premium features include a compact, direct plug-in design for easy portability, six rotatable outlets for easier plug connection and removal and 1200 joules of surge absorption protection. Diagnostic LEDs alert you to potential wiring or protection faults before connected equipment is damaged. Lifetime warranty with \$20,000 [Ultimate Lifetime Insurance](#) (USA, Puerto Rico & Canada only).

#### Applications

- Ideal for any desktop, network or home computing application requiring AC protection.

#### Package Includes

- SWIVEL6 Surge Suppressor
- Instruction manual with warranty information

#### Features

- 6 rotatable outlets allow for easier plug connection and removal
- 1200 joule rating
- Direct plug-in design converts two outlets into six by plugging into any wall outlet
- Diagnostic LEDs alert you to potential wiring or protection faults before connected equipment is damaged
- Lifetime warranty with \$20,000 [Ultimate Lifetime Insurance](#) (USA & Canada Only)

#### Specifications

<b>OVERVIEW</b>	
Intended Application	Home/Office
<b>SYSTEM OVERVIEW</b>	
Voltage compatibility	120V AC
Frequency compatibility	60 Hz
<b>OUTPUT</b>	

Output volt amp capacity (amps)	15
Outlet quantity / type	6 NEMA 5-15R
Outlet orientation	Rotatable
<b>INPUT</b>	
Input connection type	NEMA 5-15P
Input cord length (ft.)	Direct plug-in
Recommended Electrical Service	120V (110-125V)
<b>LEDS ALARMS &amp; SWITCHES</b>	
Diagnostic LEDs	Built-in LEDs confirm suppressor "protected" (green) and "grounded" (red) status
<b>SURGE / NOISE SUPPRESSION</b>	
Protection modes	Includes full normal mode (H-N) and common mode (N-G / H-G) line surge suppression
AC suppression joule rating	1200 joules
Clamping voltage (RMS)	330
AC suppression response time	< 1 ns
UL1499 let through rating	330V - UL Verified
EMI / RFI filtering	Up to 20 dB
<b>DATALINE SURGE SUPPRESSION</b>	
Telephone/DSL Protection	No
Cable (Coax) Protection	No
Network (Ethernet) Protection	No
<b>PHYSICAL</b>	
Shipping weight (lbs)	0.37
Shipping Dimensions (HWD/in)	13 x 6 x 19
Unit weight (lbs)	0.26
Unit Dimensions (HWD/in)	10.5 x 6 x 14
Material of construction	Plastic
Receptacle Color	Black
Style	Direct Plug-in
<b>CERTIFICATIONS</b>	
UL1449 1998 Rev. (AC Suppression)	UL1449
cUL / CSA (Canada)	cUL
Approvals	RoHS
<b>WARRANTY</b>	
Product Warranty Period	Lifetime
Connected Equipment Coverage	\$20,000

More information, including related products, owner's manuals, and additional technical specifications, can be found online at [www.tripplite.com/en/products/model.cfm?txtModelID=3617](http://www.tripplite.com/en/products/model.cfm?txtModelID=3617).



## Free Manuals Download Website

<http://myh66.com>

<http://usermanuals.us>

<http://www.somanuals.com>

<http://www.4manuals.cc>

<http://www.manual-lib.com>

<http://www.404manual.com>

<http://www.luxmanual.com>

<http://aubethermostatmanual.com>

Golf course search by state

<http://golfingnear.com>

Email search by domain

<http://emailbydomain.com>

Auto manuals search

<http://auto.somanuals.com>

TV manuals search

<http://tv.somanuals.com>