

Model #: TLM306NC

Power It! Power Strip - Convenient multiple outlets for every application



Highlights

- 3 outlets
- Illuminated on/off switch with cover
- 15-amp circuit breaker
- 6 ft. power cord
- Rugged metal case
- Keyhole mounting slots

Description

Tripp Lite's Power It! TLM306NC power strip offers reliable, convenient and cost-effective power distribution for appliances, power tools, lighting and other electrical equipment. Includes 3 NEMA 5-15R outlets, 6-foot AC power cord and keyhole mounting slots. Multi-outlet strip reduces cable clutter and enables the connection of multiple electrical devices to a single AC wall socket. Features rugged metal case to stand up to the most demanding environments, illuminated power switch with transparent cover to prevent accidental shutoff and 15A integrated circuit breaker to prevent dangerous overloads. Lifetime warranty.

INPUT/OUTPUT: Input: NEMA 5-15P/Output: 3 NEMA 5-15R

ELECTRICAL: 120V AC, 50/60Hz, 15A

FORMAT: Corded power distribution strip

Applications

- Offers a reliable, convenient and cost-effective method of power distribution for appliances, power tools, lighting and other electrical equipment in home, office or worksite.
- Unfiltered electrical pass-through makes the power strip ideal for distributing alternate waveform UPS or generator power to connected equipment.

Package Includes

- TLM306NC power strip
- Warranty information
- Instruction manual

Features

- Multi-outlet power strip offers reliable, convenient and cost-effective power distribution for appliances, power tools, lighting and other electrical equipment
- Includes 3 NEMA 5-15R outlets
- Illuminated on/off switch provides one-touch power control for connected equipment
- Transparent switch cover snaps tight to prevent accidental shutoff
- . Convenient keyhole slots provide secure mounting options for a wide variety of surfaces and applications

- 15A power handling capacity with integrated circuit breaker
- 120V AC, 50/60Hz electrical compatibility
- 6-foot AC power cord
- Rugged metal case provides extra safety and durability
- UL certification
- Lifetime warranty

Specifications

Voltage compatibility120V ACFrequency compatibility500 H2Outreut500 H2Outreut154Qhanghi Shang Capacity154Qhady otati and capacity100Outout and and100 H2Outout and and100 H2Outout and protection104 Gradual DataNew Capacity104 Gradual DataInto concording protection104 Gradual DataIntro concording protection104 Gradual Data <tr< th=""><th colspan="2">SYSTEM OVERVIEW</th></tr<>	SYSTEM OVERVIEW			
OUTPUT Output volt amp capacity (amps) 15.4 Output watts 1800 Output watts 3 NEMA 5-15R Outlet orientation Single row of 3 Overload protection 15.4 Input orientation Single row of 3 Outlet orientation Single row of 3 Input orientation Single row of 3 Single row of a Single row of 3 Single row of a single row of 3 Single row of 3 Single row of a single row of 3 Single row of 3 Single row of a single row of 3 Single row of 3 Single row of a single row of 3 Single row of 3 Single row of a single row of 3	Voltage compatibility	120V AC		
Output voit amp capacity (amps)15AOutput watts6800Outlet quantity / type3 NEMA 5-15ROutlet orientationSingle row of 3Overload protection15A circuit breakerINPUTInput connection typeInput corned gage, typeSJT 14A/WGInput cord length (ft.)6Input cord length (ft.)6Input cord length (ft.)18Recommended Electrical Service15A 120VSwitchesIluminated on/off switch controls power to all outletsLebS ALARMS & SWITCHE7Shipping Dimensions10 × 55 × 2.1Shipping Dimensions10 × 55 × 2.1Shipping Dimensions14.4Unit weight (kg)8Int in Unimanient on/or Switch courd surfaceUnit weight (kg)22 × 6.4 × 5.1Unit binsions (HVD/Im)22 × 6.4 × 5.1Integrate kayhole moutingkarele seale mounting to a variety of surfacesIntegrate kayhole moutingKarele seale mounting to a variety of surfacesReceptace ColorLight GrayAdditional InternationalKomples witek Role Substances Directive)	Frequency compatibility	50/60 Hz		
(amps)Image: Constant of the second of the seco	OUTPUT	OUTPUT		
Outlet quantity / type3 NEMA 5-15ROutlet orientationSingle row of 3Overload protection15A circuit breakerINPUTInput connection typeInput connection typeNEMA 5-15PInput cond gauge, typeS.J T 14AWGInput cond legith (ft.)6Recommended Electrical15A 120VBerroleInumated on/off switch controls power to all outletsLocking switch cowTansperent switch cover snaps tight to prevent accidential shutoffShipping weight (ks)1.6Shipping Dimensions2.5 x 2.1Shipping Dimensions2.4 x 14 x 5.3Unit weight (ks)3.5 x 2.0Unit weight (ks)3.5 x 2.0Shipping Dimensions2.4 x 14 x 5.3Unit weight (ks)3.5 x 2.1Unit weight (ks)3.5 x 2.0Unit weight (ks)4.6Unit weight (ks)4.6 <tr< th=""><th></th><th>15A</th></tr<>		15A		
Outlet orientation Single row of 3 Overload protection 15A circuit breaker INPUT Input connection type Input connection type NEMA 5-15P Input cord gauge, type SJT 14AWG Input cord length (ft.) 6 Recommende Electrical 15A 120V EDS ALARKS & SWITCHES Single now off switch controls power to all outlets Switches Illuminated on/off switch controls power to all outlets Locking switch cover Transparent switch cover snaps tight to prevent accidental shutoff PHYSICAL Transparent switch cover snaps tight to prevent accidental shutoff Shipping weight (lbs) 1.6 Shipping weight (lbs) 1.6 Shipping Dimensions 10 x 5.5 x 2.1 WWD/cm) 10 x 5.5 x 2.1 Unit weight (lbs) 1.4 Unit weight (lbs) 1.4 Unit weight (lbs) 2.5 4 x 14 x 5.3 Unit Dimensions (HWD/m) 2.2 x 6.4 x 5.1 Unit Dimensions (HWD/m) 2.2 x 6.4 x 5.1 Integrated keyhele mounting to a variety of surfaces Receptacele Color Light Gray	Output watts	1800		
Overload protection 15A circuit breaker INPUT Input connection type NEMA 5-15P Input cord gauge, type SJT 14AWG Input cord gauge, type Input cord length (ft.) 6 Input cord length (ft.) Becommended Electrical 15A 120V Input cord length (ft.) ECES ALARMS & SWITCHES Infuminated on/off switch controls power to all outlets Locking switch cover Transparent switch cover snaps tight to prevent accidental shutoff PHYSICL 5 Shipping weight (fts) 1.6 Shipping weight (kg) 7 Shipping Weight (kg) 1.0 x 5.5 x 2.1 Chriwbinn 25.4 x 14 x 5.3 Unit weight (kg) 6 Unit weight (kg) 6.1 Unit weight (kg) 6.2 Unit mensions (HWD/m) 2.2 x 6.4 x 5.1 Marcial of construction Melsical menuting to a variety of surfaces Itegrated keyhole mounting 2.2 x 6.4 x 5.1 Marcial of construction Melsical menuting to a variety of surfaces Init Dimensions (HWD/m) 2.2 x 6.4 x 5.1 Receptacle Color Light Gay	Outlet quantity / type	3 NEMA 5-15R		
INPUT Input connection type NEMA 5-15P Input cord gauge, type SJT 14AWG Input cord length (ft.) 6 Input cord length (m) 1.8 Recommended Electrical service 15A 120V LEDS ALARMS & SWITCHES Illuminated on/off switch controls power to all outlets Locking switch cover Transparent switch cover snaps tight to prevent accidential shutoff PHYSICAL 1 Shipping weight (kg) 1.6 Shipping Dimensions 10x 5.5 x 2.1 Shipping Dimensions 25.4 x 14 x 5.3 Unit weight (kg) 6 Unit weight (kg) 6.2 Unit weight (kg) 5.7 x 2.5 x 2 Unit weight (kg) 6.2 Unit weight (kg) 6.2 Unit weight (kg) 6.2 Unit Dimensions (HWD/in) 2.5 x 2.5 x 2 Material of construction Metal case Integrated keyhole mounting to a variety of surfaces Integrated keyhole mounting to a variety of surfaces Integrated keyhole mounting to a variety of surfaces Integrated keyhole mounting to a variety of surfaces <th>Outlet orientation</th> <th>Single row of 3</th>	Outlet orientation	Single row of 3		
Input connection type NEMA 5-15P Input cord gauge, type SJT 14AWG Input cord length (ft.) 6 Input cord length (ft.) 18 Recommended Electrical Service 15A 120V ELEDS ALARMS & SWITCHEE Illuminated on/off switch controls power to all outlets Locking witch cover Transparent switch cover snaps tight to prevent accidential shutoff PHYSICAL 16 Shipping weight (fts) 1.6 Shipping Dimensions 10×5.5×2.1 Shipping Dimensions 10×5.5×2.1 Unit weight (fts) 1.4 Unit weight (fts) 5.4×14×5.3 Unit weight (fts) 6.5 Unit weight (fts) 2.2×6.4×5.1 Unit mentional (HWD/m) 2.2×6.4×5.1 Material of construction Metal case Integrated keyhole mounting to a variety of surfaces Itage for surfaces Recepted Color Lipt Gray Ac line cord color Lipt Gray	Overload protection	15A circuit breaker		
Input cord gauge, type SJT 14AWG Input cord length (ft.) 6 Input cord length (ft.) 1.8 Recommended Electrical Service 15A 120V ELDS ALARMS & SWITCHES Illuminated on/off switch controls power to all outlets Switches Illuminated on/off switch controls power to all outlets Locking switch cover Transparent switch cover snaps tight to prevent accidental shutoff PHYSiCA 5 Shipping veight (kg) 1.6 Shipping Dimensions 10×5.5 x 2.1 VitWD/m) 1.4 Unit weight (kg) 5.5 x 2.1 Unit weight (kg) 5.4 x 14 x 5.3 Unit weight (kg) 6. Unit weight (kg) 6. Unit weight (kg) 6. Unit Dimensions (HWD/m) 2.2 x 6.4 x 5.1 Material of construction Metal case Integrated keyhole mounting to a variety of surfaces Light Gray Ac line cord color Light Gray Act line cord color Light Gray Additional International Complies with RoHS (Restriction of Hazardous Substances Directive)	INPUT			
Input cord length (ft.) 6 Input cord length (m) 1.8 Recommended Electrical 15A 120V Bernice Illuminated on/off switch controls power to all outlets LEDS ALARMS & SWITCHES Illuminated on/off switch controls power to all outlets Switches Illuminated on/off switch controls power to all outlets Locking switch cover Transparent switch cover snaps tight to prevent accidental shutoff PHYSICAL Illuminated on/off switch controls power to all outlets Shipping weight (kg) 1.6 Shipping Dimensions 1.0 × 5.5 × 2.1 WWD/cm) 0 × 5.5 × 2.1 Unit weight (kg) 1.4 Unit weight (kg) 6 Unit weight (kg) 6.5 × 2.5 × 2 Unit blienensions (HWD/in) 8.75 × 2.5 × 2 Unit Dimensions (HWD/in) 8.75 × 2.5 × 2 Material of construction Metal case Integrated keyhole mounting keyhole slots enable mounting to a variety of surfaces Receptace Color Light Gray Ac line cord color Light Gray Additional International Complies with RoHS (Restriction of Hazardous Substances Directiv	Input connection type	NEMA 5-15P		
Input cord length (m) 1.8 Input cord length (m) 1.5A 120V Berovice 15A 120V LEDS ALARMS & SWITCHES Illuminated on/off switch controls power to all outlets Switches Illuminated on/off switch controls power to all outlets Locking switch cover Transparent switch cover snaps tight to prevent accidental shutoff PHYSICAL Transparent switch cover snaps tight to prevent accidental shutoff Shipping weight (kg) 1.6 Shipping Dimensions 1.0 × 5.5 × 2.1 Shipping Dimensions 25.4 × 14 × 5.3 Unit weight (kg) 1.4 Unit weight (kg) 6. Unit blenensions (HWD/m) 2.2 × 6.4 × 5.1 Material of construction Keyhole slots enable mounting to a variety of surfaces Integrated keyhole mounting Light Gray Ac line cord color Light Gray Additional International Complies with ROHS (Restriction of Hazardous Substances Directive)	Input cord gauge, type	SJT 14AWG		
Recommended Electrical Bervice 15A 120V LEDS ALARMS & SWITCHES Switches Illuminated on/off switch controls power to all outlets Locking switch cover Transparent switch cover snaps tight to prevent accidental shutoff PHYSICAL Transparent switch cover snaps tight to prevent accidental shutoff Shipping weight (bs) 1.6 Shipping Dimensions 0 x 5.5 x 2.1 Shipping Dimensions 2.5.4 x 14 x 5.3 Unit weight (bs) 1.4 Unit weight (kg) 8.75 x 2.5 x 2 Unit weight (kg) 2.2 x 6.4 x 5.1 Material of construction Metal case Integrated keyhole mounting tabs Keyhole slots enable mounting to a variety of surfaces Receptacle Color Light Gray Act line cord color Light Gray Additional International Complies with RoHS (Restriction of Hazardous Substances Directive)	Input cord length (ft.)	6		
Service International Section LEDS ALARMS & SWITCHES Switches Illuminated on/off switch controls power to all outlets Locking switch cover Transparent switch cover snaps tight to prevent accidental shutoff PHYSICAL Terresparent switch cover snaps tight to prevent accidental shutoff Shipping weight (bs) 1.6 Shipping Dimensions 10 x 5.5 x 2.1 Shipping Dimensions 25.4 x 14 x 5.3 Unit weight (bs) 1.4 Unit weight (kg) 6 Unit weight (kg) 2.2 x 6.4 x 5.1 Material of construction Metal case Integrated keyhole mounting Keyhole slots enable mounting to a variety of surfaces Receptacle Color Light Gray Act line cord color Light Gray Additional International Complies with RoHS (Restriction of Hazardous Substances Directive)	Input cord length (m)	1.8		
Switches Illuminated on/off switch controls power to all outlets Locking switch cover Transparent switch cover snaps tight to prevent accidental shutoff PHYSICAL Information of the prevent accidental shutoff Shipping weight (lbs) 1.6 Shipping Dimensions 1.0 x 5.5 x 2.1 Shipping Dimensions 1.4 Unit weight (lbs) 1.4 Unit weight (lbg) 6 Unit weight (lbg) 5.5 x 2.5 x 2 Unit weight (lbg) 2.2 x 6.4 x 5.3 Unit weight (lbg) 2.2 x 6.4 x 5.1 Material of construction Metal case Ittegrated keyhole mounting Keyhole slots enable mounting to a variety of surfaces Receptacle Color Light Gray Act line cord color Light Gray CERTIFICATIONS Complies with RoHS (Restriction of Hazardous Substances Directive)		15A 120V		
Locking switch cover Transparent switch cover snaps tight to prevent accidental shutoff PHYSICAL Information accidental shutoff Shipping weight (lbs) 1.6 Shipping weight (kg) .7 Shipping Dimensions 10×5.5×2.1 Shipping Dimensions 25.4×14×5.3 Unit weight (lbs) 1.4 Unit weight (kg) .6 Unit weight (kg) .57×2.5×2 Unit Dimensions (HWD/in) .57×2.5×2 Unit Dimensions (HWD/in) .57×2.5×2 Unit Dimensions (HWD/in) .22.2×6.4×5.1 Material of construction Metal case Itegrated keyhole mounting Keyhole slots enable mounting to a variety of surfaces Receptacle Color Light Gray AC line cord color Light Gray CERTIFICATIONS Complies with ROHS (Restriction of Hazardous Substances Directive)	LEDS ALARMS & SWITCHES			
PHYSICAL Shipping weight (lbs) 1.6 Shipping weight (kg) .7 Shipping Dimensions 10 x 5.5 x 2.1 Shipping Dimensions 25.4 x 14 x 5.3 Unit weight (lbs) 1.4 Unit weight (kg) 6 Unit Dimensions (HWD/in) 8.75 x 2.5 x 2 Unit Dimensions (HWD/in) 2.2 x 6.4 x 5.1 Material of construction Metal case Integrated keyhole mounting to a variety of surfaces table Keyhole slots enable mounting to a variety of surfaces table AC line cord color Light Gray Act line cord color Light Gray Additional International Complies with RoHS (Restriction of Hazardous Substances Directive)	Switches	Illuminated on/off switch controls power to all outlets		
Shipping weight (lbs) 1.6 Shipping weight (kg) .7 Shipping Dimensions (HWD/in) 10 x 5.5 x 2.1 Shipping Dimensions (HWD/cm) 25.4 x 14 x 5.3 Unit weight (lbs) 1.4 Unit weight (kg) 6 Unit Dimensions (HWD/in) 8.75 x 2.5 x 2 Unit Dimensions (HWD/in) 2.2 x 6.4 x 5.1 Material of construction Metal case Integrated keyhole mounting tabs Keyhole slots enable mounting to a variety of surfaces Receptacle Color Light Gray AC line cord color Light Gray CERTIFICATIONS Complies with RoHS (Restriction of Hazardous Substances Directive)	Locking switch cover	Transparent switch cover snaps tight to prevent accidental shutoff		
Shipping Version (kg).7Shipping Dimensions (HWD/in)10 x 5.5 x 2.1Shipping Dimensions (HWD/cm)25.4 x 14 x 5.3Unit weight (lbs)1.4Unit weight (kg).6Unit weight (kg)8.75 x 2.5 x 2Unit Dimensions (HWD/cm)22.2 x 6.4 x 5.1Material of constructionMetal caseIntegrated keyhole mounting tabsKeyhole slots enable mounting to a variety of surfacesReceptacle ColorLight GrayAct line cord colorLight GrayAdditional InternationalComplies with RoHS (Restriction of Hazardous Substances Directive)	PHYSICAL			
Shipping Dimensions (HWD/in)10 x 5.5 x 2.1Shipping Dimensions (HWD/cm)25.4 x 14 x 5.3Unit weight (lbs)1.4Unit weight (kg).6Unit Dimensions (HWD/in)8.75 x 2.5 x 2Unit Dimensions (HWD/cm)22.2 x 6.4 x 5.1Material of constructionMetal caseIntegrated keyhole mounting tabsKeyhole slots enable mounting to a variety of surfaces tabsReceptacle ColorLight GrayCERTIFICATIONSComplies with RoHS (Restriction of Hazardous Substances Directive)	Shipping weight (lbs)	1.6		
(HWD/in)Complex with RoHS (Restriction of Hazardous Substances Directive)Shipping Dimensions (HWD/cm)25.4 × 14 × 5.3Unit weight (lbs)1.4Unit weight (kg).6Unit Dimensions (HWD/in)8.75 × 2.5 × 2Unit Dimensions (HWD/cm)22.2 × 6.4 × 5.1Material of constructionMetal caseIntegrated keyhole mounting tabsKeyhole slots enable mounting to a variety of surfacesReceptacle ColorLight GrayAct line cord colorComplies with RoHS (Restriction of Hazardous Substances Directive)	Shipping weight (kg)	.7		
(HŵD/cm)I.4Unit weight (lbs)1.4Unit weight (kg).6Unit Dimensions (HWD/in)8.75 x 2.5 x 2Unit Dimensions (HWD/cm)22.2 x 6.4 x 5.1Material of constructionMetal caseIntegrated keyhole mounting to a variety of surfacesReceptacle ColorLight GrayAC line cord colorLight GrayCERTIFICATIONSAdditional InternationalComplies with RoHS (Restriction of Hazardous Substances Directive)		10 x 5.5 x 2.1		
Unit veight (kg).6Unit Dimensions (HWD/in)8.75 x 2.5 x 2Unit Dimensions (HWD/cm)22.2 x 6.4 x 5.1Material of constructionMetal caseIntegrated keyhole mounting tabsKeyhole slots enable mounting to a variety of surfacesReceptacle ColorLight GrayAC line cord colorLight GrayCERTIFICATIONSComplies with RoHS (Restriction of Hazardous Substances Directive)		25.4 x 14 x 5.3		
Unit Dimensions (HWD/in)8.75 x 2.5 x 2Unit Dimensions (HWD/cm)22.2 x 6.4 x 5.1Material of constructionMetal caseIntegrated keyhole mounting tabsKeyhole slots enable mounting to a variety of surfacesReceptacle ColorLight GrayAC line cord colorLight GrayCERTIFICATIONSComplies with RoHS (Restriction of Hazardous Substances Directive)	Unit weight (Ibs)	1.4		
Unit Dimensions (HWD/cm)22.2 x 6.4 x 5.1Material of constructionMetal caseIntegrated keyhole mounting tabsKeyhole slots enable mounting to a variety of surfacesReceptacle ColorLight GrayAC line cord colorLight GrayCERTIFICATIONSComplies with RoHS (Restriction of Hazardous Substances Directive)	Unit weight (kg)	.6		
Material of construction Metal case Integrated keyhole mounting tabs Keyhole slots enable mounting to a variety of surfaces Receptacle Color Light Gray AC line cord color Light Gray CERTIFICATIONS Complies with RoHS (Restriction of Hazardous Substances Directive)	Unit Dimensions (HWD/in)	8.75 x 2.5 x 2		
Integrated keyhole mounting tabs Keyhole slots enable mounting to a variety of surfaces Receptacle Color Light Gray AC line cord color Light Gray CERTIFICATIONS Complies with RoHS (Restriction of Hazardous Substances Directive)	Unit Dimensions (HWD/cm)	22.2 x 6.4 x 5.1		
tabs Light Gray AC line cord color Light Gray CERTIFICATIONS Additional International Complies with RoHS (Restriction of Hazardous Substances Directive)	Material of construction	Metal case		
AC line cord color Light Gray CERTIFICATIONS Additional International Complies with RoHS (Restriction of Hazardous Substances Directive)		Keyhole slots enable mounting to a variety of surfaces		
CERTIFICATIONS Additional International Complies with RoHS (Restriction of Hazardous Substances Directive)	Receptacle Color	Light Gray		
Additional International Complies with RoHS (Restriction of Hazardous Substances Directive)	AC line cord color	Light Gray		
	CERTIFICATIONS			
		Complies with RoHS (Restriction of Hazardous Substances Directive)		

UL1363 (Power Tap)	UL1363
cUL / CSA (Canada)	cUL
WARRANTY	
Product Warranty Period	Lifetime

More information, including related products, owner's manuals, and additional technical specifications, can be found online at www.tripplite.com/en/products/model.cfm?txtModeIID=3463.

©2009 Tripp Lite. All Rights Reserved.

Free Manuals Download Website <u>http://myh66.com</u> <u>http://usermanuals.us</u> <u>http://www.somanuals.com</u> <u>http://www.4manuals.cc</u> <u>http://www.4manuals.cc</u> <u>http://www.4manuals.cc</u> <u>http://www.4manuals.com</u> <u>http://www.404manual.com</u> <u>http://www.luxmanual.com</u> <u>http://aubethermostatmanual.com</u> Golf course search by state

http://golfingnear.com Email search by domain

http://emailbydomain.com Auto manuals search

http://auto.somanuals.com TV manuals search

http://tv.somanuals.com