



# Model #: TLM626

### **Protect It! Surge Suppressor**



## **Highlights**

- 6 outlets / 6 ft. cord
- 1208 joule rating
- \$75,000 Ultimate Lifetime Insurance (USA & Canada only)
- Rugged metal case

### **Description**

Tripp Lite's TLM626 surge suppressor offers complete AC surge suppression for comprehensive protection of workstations, personal computers, home stereos, televisions, VCRs, DVD players and other sensitive electronics. Heavy grade AC surge suppression shields connected equipment from damage and performance problems due to transient surges. TLM626 offers 6 right-angle outlets, a 6 foot power cord and diagnostic LEDs to warn of wiring problems and suppressor damage. AC surge suppression rated at 1208 joules shields equipment from surges and line noise. Rugged metal housing with 2 designated transformer plug outlets offers convenient protection of desktop computer equipment and accessories. Lifetime warranty with \$75,000 Ultimate Lifetime Insurance (USA & Canada Only).

PLUG/OUTLETS: Input - 6 ft. AC line cord with NEMA 5-15P plug/Output - 6 NEMA 5-15R right-angle outlets

ELECTRICAL: 120V AC, 50/60Hz, 15A (Requires NEMA 5-15R wall receptacle)

FORMAT: Metal strip

SUPPRESSION: AC: 150V RMS Clamping/1208 joules/330V UL1449

**Applications** 

• Ideal for personal computers, TV/VCR/DVD, stereos and lamps/lighting

Package Includes

- TLM626 surge suppressor
- Instruction manual and warranty information

#### **Features**

- 6 right-angle outlets
- 6 ft. cord
- Surge suppression rating: 1208 joules
- EMI/RFI noise filtering
- 15 amp resettable circuit breaker protects against overload
- Diagnostic LEDs confirm suppressor "protection present" (green) and "grounded" (red) status
- Convenient keyhole slots allow secure mounting on wall or desk

- Can accommodate up to 2 transformers without blocking adjacent outlets
- Rugged metal case provides extra safety and durability
- Illuminated power switch
- \$75,000 Ultimate Lifetime Insurance (USA & Canada Only) covers connected equipment
- Lifetime product warranty

## **Specifications**

OVERVIEW Intended Application Home/Office SYSTEM OVERVIEW Voltage compatibility 120V AC Frequency compatibility 50/60 Hz OUTPU OUTPU OUTPU OUTPU OUTPU OUtlet quantity / type 6 NEMA 5-15R Outlet quantity / type 6 NEMA 5-15R Outlet quantity / type 6 NEMA 5-15R Outlet quantity / type 7 State of Control of Single row of outlets Overload protection 15A resettable combo switch / circuit breaker Transformer accommodation Supports 2 large transformers without covering adjacent outlets INPUT Input cord pague, type 14 gauge, SJT Input cord length (ft.) 6 ft. Input cord length (ft.) 6 ft. Input cord length (m) 1.8 Recommended Electrical Service 120V (110-125V) ELEDS ALARMS & SWITCHES Diagnostic LEDs Built-in LEDs confirm suppressor "protection present" (green) and "grounded" (red) status Switches Combination AC circuit breaker and 2 position on/off power switch SURGE / NOISE SUPPRESSION Protection modes Includes full normal mode (H-N) and common mode (N-G / H-G) line surge suppression AC suppression joule rating 1208 joules Clamping voltage (RMS) 150V AC suppression response time UL1499 let through rating 330V - UL Verified EMI / RFI filtering Up to 208B DATALINE SURGE SUPPRESSION Telephone(PSL Protection No Network (Ethernet) Protection No Network (Ethernet) Protection No Network (Ethernet) Protection No				
SYSTEM OVERVIEW   120V AC   Frequency compatibility   120V AC   Frequency compatibility   50/60 Hz	OVERVIEW			
Voltage compatibility 120V AC  Frequency compatibility 50/60 Hz  OUTPUT  Output volt amp capacity (amps) 15  Output watts 1800  Outlet quantity / type 6 NEMA 5-15R  Outlet orientation Single row of outlets  Overload protection 15A resettable combo switch / circuit breaker  Transformer accommodation Supports 2 large transformers without covering adjacent outlets  INPUT  Input connection type NEMA 5-15P  Input cord gauge, type 14 gauge, SJT  Input cord length (ft.) 6 ft.  Input cord length (ft.) 6 ft.  Input cord length (ft.) 8 built-in LEDs confirm suppressor "protection present" (green) and "grounded" (red) status  Switches Combination AC circuit breaker and 2 position on/off power switch  SURGE / NOISE SUPPRESSION  Protection modes Includes full normal mode (H-N) and common mode (N-G / H-G) line surge suppression  AC suppression joule rating 1208 joules  Clamping voltage (RMS) 150V  AC Suppression response time  UL1499 let through rating Up to 20d8  DATALINE SURGE SUPPRESSION  Fleiphone/DSL Protection No  Notwork (Ethernet) Protection No  Notwork (Ethernet) Protection No  Notwork (Ethernet) Protection No	Intended Application	Home/Office		
Frequency compatibility  OUTPUT  OUTPUT volt amp capacity (amps)  Output watts  1800  Outlet quantity / type  6 NEMA 5-15R  Outlet orientation  Single row of outlets  Overload protection  15A resettable combo switch / circuit breaker  Transformer accommodation  INPUT  Input cornection type  NEMA 5-15P  Input cord length (ft.)  Input cord length (m)  1.8  Recommended Electrical 2001 (10-125V)  Service  Diagnostic LEDs  Built-in LEDs confirm suppressor "protection present" (green) and "grounded" (red) status  Switches  Combination AC circuit breaker and 2 position on/off power switch  SURGE / NOISE SUPPRESSION  Protection modes  Includes full normal mode (H-N) and common mode (N-G / H-G) line surge suppression  AC suppression joule rating  1208 joules  Clamping voltage (RMS)  150V  AC Suppression response time  UL 1499 let through rating  330V - UL Verified  EMI / RFI filtering  Up to 20dB  DATALINE SURGE SUPPRESSION  Network (Ethernet) Protection  No  Network (Ethernet) Protection  No  Network (Ethernet) Protection  No	SYSTEM OVERVIEW	SYSTEM OVERVIEW		
OUTPUT Volt amp capacity (amps) 15 Output watts 1800 Outlet quantity / type 6 NEMA 5-15R Outlet quantity / type 3 Single row of outlets Overload protection 15A resettable combo switch / circuit breaker Transformer accommodation Supports 2 large transformers without covering adjacent outlets INPUT Input connection type NEMA 5-15P Input cord length (ft.) 6 ft. Input cord length (ft.) 1.8 Recommended Electrical Service 2 Built-in LEDs confirm suppressor "protection present" (green) and "grounded" (red) status Switches Combination AC circuit breaker and 2 position on/off power switch SURGE / NOISE SUPPRESSION Protection modes Includes full normal mode (H-N) and common mode (N-G / H-G) line surge suppression AC suppression joule rating 1208 joules Clamping voltage (RMS) 150V AC suppression response 1 1 ns UL-1499 let through rating Up to 20dB DATALINE SURGE SUPPRESSION Telephone/DSL Protection No Network (Ethernet) Protection No Network (Ethernet) Protection No	Voltage compatibility	120V AC		
Output voit amp capacity (amps)         15           Output watts         1800           Outlet quantity / type         6 NEMA 5-15R           Outlet orientation         Single row of outlets           Overload protection         15A resettable combo switch / circuit breaker           Transformer accommodation         Supports 2 large transformers without covering adjacent outlets           INPUT           Input cornection type         NEMA 5-15P           Input cord gauge, type         14 gauge. SJT           Input cord length (ft.)         6 ft.           Input cord length (m)         1.8           Recommended Electrical service         120V (110-125V)           Service         Diagnostic LEDs           Suit-in LEDs confirm suppressor "protection present" (green) and "grounded" (red) status           Switches         Combination AC circuit breaker and 2 position on/off power switch           SURGE / NOISE SUPPRESSION           Protection modes         Includes full normal mode (H-N) and common mode (N-G / H-G) line surge suppression           Clamping voltage (RMS)         150V           AC suppression response         150V           Clamping voltage (RMS)         330V - UL Verified           EMI / RFI filtering         Up to 20dB           DATALINE SURGE SUPPRESSION	Frequency compatibility	50/60 Hz		
Output watts 1800 Outlet quantity / type 6 NEMA 5-15R Outlet orientation Single row of outlets Overload protection 15A resettable combo switch / circuit breaker Transformer accommodation Supports 2 large transformers without covering adjacent outlets  INPUT Input connection type NEMA 5-15P Input cord gauge, type 14 gauge, SJT Input cord length (ft.) 6 ft. Input cord length (ft.) 6 ft. Input cord length (m) 1.8 Recommended Electrical service 120V (110-125V) Service LEDS ALARMS & SWITCHES Diagnostic LEDs Built-in LEDs confirm suppressor "protection present" (green) and "grounded" (red) status  Switches Combination AC circuit breaker and 2 position on/off power switch  SURGE / NOISE SUPPRESSION Protection modes Includes full normal mode (H-N) and common mode (N-G / H-G) line surge suppression  AC suppression joule rating 1208 joules  Clamping voltage (RMS) 150V  AC suppression response time UL1499 let through rating 330V - UL Verified  EMI / RFI filtering Up to 2odB  DATALINE SURGE SUPPRESSION  No Cable (Coax) Protection No Network (Ethernet) Protection No Network (Ethernet) Protection No	OUTPUT			
Outlet quantity / type 6 NEMA 5-15R  Outlet orientation Single row of outlets  Overload protection 15A resettable combo switch / circuit breaker  Transformer accommodation Supports 2 large transformers without covering adjacent outlets  INPUT  Input connection type NEMA 5-15P  Input cord gauge, type 14 gauge, SJT  Input cord length (ft.) 6 ft.  Input cord length (m) 1.8  Recommended Electrical 120V (110-125V)  Service  Diagnostic LEDS Built-in LEDs confirm suppressor "protection present" (green) and "grounded" (red) status  Switches Combination AC circuit breaker and 2 position on/off power switch  SURGE / NOISE SUPPRESSION  Protection modes Includes full normal mode (H-N) and common mode (N-G / H-G) line surge suppression  AC suppression joule rating 1208 joules  Clamping voltage (RMS) 150V  AC suppression response time UL1499 let through rating 330V - UL Verified  BMI / RFI filtering Up to 20dB  DATALINE SURGE SUPPRESSION  Telephone/DSL Protection No  Notwork (Ethernet) Protection No  Network (Ethernet) Protection No		15		
Outlet orientation         Single row of outlets           Overload protection         15A resettable combo switch / circuit breaker           Transformer accommodation         Supports 2 large transformers without covering adjacent outlets           INPUT         Input connection type         NEMA 5-15P           Input cord gauge, type         14 gauge, SJT           Input cord length (ft.)         6 ft.           Input cord length (m)         1.8           Recommended Electrical Service         120V (110-125V)           Service         Diagnostic LEDs         Built-in LEDs confirm suppressor "protection present" (green) and "grounded" (red) status           Switches         Combination AC circuit breaker and 2 position on/off power switch           SURGE / NOISE SUPPRESSION           Protection modes         Includes full normal mode (H-N) and common mode (N-G / H-G) line surge suppression           AC suppression joule rating         150V           AC suppression response time         1 ns           UL1499 let through rating         330V - UL Verified           DATALINE SURGE SUPPRESSION         To 20dB           DATALINE SURGE SUPPRESSION           Telephone/DSL Protection         No           Cable (Coax) Protection         No           Network (Ethernet) Protection         No	Output watts	1800		
Overload protection 15A resettable combo switch / circuit breaker Transformer accommodation Supports 2 large transformers without covering adjacent outlets  INPUT  Input connection type NEMA 5-15P  Input cord gauge, type 14 gauge, SJT  Input cord length (ft.) 6 ft.  Input cord length (m) 1.8  Recommended Electrical 220V (110-125V)  Recommended Electrical 320V (110-125V)  Built-in LEDs confirm suppressor "protection present" (green) and "grounded" (red) status  Switches Combination AC circuit breaker and 2 position on/off power switch  SURGE / NOISE SUPPRESSION  Protection modes Includes full normal mode (H-N) and common mode (N-G / H-G) line surge suppression  AC suppression joule rating 1208 joules  Clamping voltage (RMS) 150V  AC suppression response time  UL1499 let through rating 330V - UL Verified  EMI / RPI filtering Up to 20dB  DATALINE SURGE SUPPRESSION  Telephone/DSL Protection No  Notwork (Ethernet) Protection No  Network (Ethernet) Protection No	Outlet quantity / type	6 NEMA 5-15R		
Transformer accommodation  INPUT  Input connection type Input cord gauge, type Input cord length (ft.)	Outlet orientation	Single row of outlets		
INPUT Input connection type NEMA 5-15P Input cord gauge, type 14 gauge, SJT Input cord length (ft.) 6 ft. Input cord length (ft.) 1.8 Recommended Electrical services 2000	Overload protection	15A resettable combo switch / circuit breaker		
Input cord gauge, type 14 gauge, SJT  Input cord length (ft.) 6 ft.  Input cord length (ft.) 6 ft.  Input cord length (ft.) 1.8  Recommended Electrical 20V (110-125V)  ELEDS ALARMS & SWITCHES  Diagnostic LEDS Built-in LEDs confirm suppressor "protection present" (green) and "grounded" (red) status  Switches Combination AC circuit breaker and 2 position on/off power switch  SURGE / NOISE SUPPRESSION  Protection modes Includes full normal mode (H-N) and common mode (N-G / H-G) line surge suppression  AC suppression joule rating 1208 joules  Clamping voltage (RMS) 150V  AC suppression response time 330V - UL Verified  EMI / RFI filtering Up to 20dB  DATALINE SURGE SUPPRESSION  Telephone/DSL Protection No  Retwork (Ethernet) Protection No	Transformer accommodation	Supports 2 large transformers without covering adjacent outlets		
Input cord gauge, type 14 gauge, SJT  Input cord length (ft.) 6 ft.  Input cord length (m) 1.8  Recommended Electrical 220V (110-125V)  LEDS ALARMS & SWITCHES  Diagnostic LEDs Built-in LEDs confirm suppressor "protection present" (green) and "grounded" (red) status  Switches Combination AC circuit breaker and 2 position on/off power switch  SURGE / NOISE SUPPRESSION  Protection modes Includes full normal mode (H-N) and common mode (N-G / H-G) line surge suppression  AC suppression joule rating 1208 joules  Clamping voltage (RMS) 150V  AC suppression response time 330V - UL Verified  EMI / RFI filtering Up to 20dB  DATALINE SURGE SUPPRESSION  Telephone/DSL Protection No  Cable (Coax) Protection No  Network (Ethernet) Protection No  PHYSICAL	INPUT			
Input cord length (ft.) 6 ft. Input cord length (m) 1.8  Recommended Electrical service 120V (110-125V)  LEDS ALARMS & SWITCHES  Diagnostic LEDs Built-in LEDs confirm suppressor "protection present" (green) and "grounded" (red) status  Switches Combination AC circuit breaker and 2 position on/off power switch  SURGE / NOISE SUPPRESSION  Protection modes Includes full normal mode (H-N) and common mode (N-G / H-G) line surge suppression  AC suppression joule rating 1208 joules  Clamping voltage (RMS) 150V  AC suppression response time 330V - UL Verified  EMI / RFI filtering Up to 20dB  DATALINE SURGE SUPPRESSION  Telephone/DSL Protection No  Cable (Coax) Protection No  Network (Ethernet) Protection No  PHYSICAL	Input connection type	NEMA 5-15P		
Input cord length (m)  Recommended Electrical service  LEDS ALARMS & SWITCHES  Diagnostic LEDs  Built-in LEDs confirm suppressor "protection present" (green) and "grounded" (red) status  Switches  Combination AC circuit breaker and 2 position on/off power switch  SURGE / NOISE SUPPRESSION  Protection modes  Includes full normal mode (H-N) and common mode (N-G / H-G) line surge suppression  AC suppression joule rating  1208 joules  Clamping voltage (RMS)  AC suppression response time  UL1499 let through rating  330V - UL Verified  EMI / RFI filtering  Up to 20dB  DATALINE SURGE SUPPRESSION  Telephone/DSL Protection  No  Cable (Coax) Protection  No  Network (Ethernet) Protection  No  PHYSICAL	Input cord gauge, type	14 gauge, SJT		
Recommended Electrical Service  LEDS ALARMS & SWITCHES  Diagnostic LEDs  Built-in LEDs confirm suppressor "protection present" (green) and "grounded" (red) status  Switches  Combination AC circuit breaker and 2 position on/off power switch  SURGE / NOISE SUPPRESSION  Protection modes  Includes full normal mode (H-N) and common mode (N-G / H-G) line surge suppression  AC suppression joule rating  1208 joules  Clamping voltage (RMS)  150V  AC suppression response time  UL1499 let through rating  330V - UL Verified  EMI / RFI filtering  Up to 20dB  DATALINE SURGE SUPPRESSION  Telephone/DSL Protection  No  Cable (Coax) Protection  No  Network (Ethernet) Protection  No  PHYSICAL	Input cord length (ft.)	6 ft.		
Service  LEDS ALARMS & SWITCHES  Diagnostic LEDs  Built-in LEDs confirm suppressor "protection present" (green) and "grounded" (red) status  Switches  Combination AC circuit breaker and 2 position on/off power switch  SURGE / NOISE SUPPRESSION  Protection modes  Includes full normal mode (H-N) and common mode (N-G / H-G) line surge suppression  AC suppression joule rating  1208 joules  Clamping voltage (RMS)  AC suppression response time  VL1499 let through rating  330V - UL Verified  EMI / RFI filtering  Up to 20dB  DATALINE SURGE SUPPRESSION  Telephone/DSL Protection  No  Cable (Coax) Protection  No  Network (Ethernet) Protection  No  PHYSICAL	Input cord length (m)	1.8		
Diagnostic LEDs Built-in LEDs confirm suppressor "protection present" (green) and "grounded" (red) status  Switches Combination AC circuit breaker and 2 position on/off power switch  SURGE / NOISE SUPPRESSION  Protection modes Includes full normal mode (H-N) and common mode (N-G / H-G) line surge suppression  AC suppression joule rating 1208 joules  Clamping voltage (RMS) 150V  AC suppression response time 330V - UL Verified  UL1499 let through rating 330V - UL Verified  EMI / RFI filtering Up to 20dB  DATALINE SURGE SUPPRESSION  Telephone/DSL Protection No  Cable (Coax) Protection No  Network (Ethernet) Protection No  PHYSICAL		120V (110-125V)		
Switches  Combination AC circuit breaker and 2 position on/off power switch  SURGE / NOISE SUPPRESSION  Protection modes  Includes full normal mode (H-N) and common mode (N-G / H-G) line surge suppression  AC suppression joule rating  Clamping voltage (RMS)  150V  AC suppression response time  VL1499 let through rating  330V - UL Verified  EMI / RFI filtering  Up to 20dB  DATALINE SURGE SUPPRESSION  Telephone/DSL Protection  No  Cable (Coax) Protection  No  Network (Ethernet) Protection  No  PHYSICAL	LEDS ALARMS & SWITCHES			
SURGE / NOISE SUPPRESSION  Protection modes Includes full normal mode (H-N) and common mode (N-G / H-G) line surge suppression  AC suppression joule rating 1208 joules  Clamping voltage (RMS) 150V  AC suppression response time 330V - UL Verified  UL1499 let through rating 330V - UL Verified  EMI / RFI filtering Up to 20dB  DATALINE SURGE SUPPRESSION  Telephone/DSL Protection No  Cable (Coax) Protection No  Network (Ethernet) Protection No  PHYSICAL	Diagnostic LEDs	Built-in LEDs confirm suppressor "protection present" (green) and "grounded" (red) status		
Protection modes Includes full normal mode (H-N) and common mode (N-G / H-G) line surge suppression  AC suppression joule rating 1208 joules  Clamping voltage (RMS) 150V  AC suppression response time 330V - UL Verified  UL1499 let through rating 330V - UL Verified  EMI / RFI filtering Up to 20dB  DATALINE SURGE SUPPRESSION  Telephone/DSL Protection No  Cable (Coax) Protection No  Network (Ethernet) Protection No  PHYSICAL	Switches	Combination AC circuit breaker and 2 position on/off power switch		
AC suppression joule rating 1208 joules  Clamping voltage (RMS) 150V  AC suppression response time < 1 ns  UL1499 let through rating 330V - UL Verified  EMI / RFI filtering Up to 20dB  DATALINE SURGE SUPPRESSION  Telephone/DSL Protection No  Cable (Coax) Protection No  Network (Ethernet) Protection No  PHYSICAL	SURGE / NOISE SUPPRESSION			
Clamping voltage (RMS) 150V  AC suppression response time 150V  UL1499 let through rating 330V - UL Verified  EMI / RFI filtering Up to 20dB  DATALINE SURGE SUPPRESSION  Telephone/DSL Protection No  Cable (Coax) Protection No  Network (Ethernet) Protection No  PHYSICAL	Protection modes	Includes full normal mode (H-N) and common mode (N-G / H-G) line surge suppression		
AC suppression response time <1 ns  UL1499 let through rating 330V - UL Verified  EMI / RFI filtering Up to 20dB  DATALINE SURGE SUPPRESSION  Telephone/DSL Protection No  Cable (Coax) Protection No  Network (Ethernet) Protection No  PHYSICAL	AC suppression joule rating	1208 joules		
time  UL1499 let through rating 330V - UL Verified  EMI / RFI filtering Up to 20dB  DATALINE SURGE SUPPRESSION  Telephone/DSL Protection No  Cable (Coax) Protection No  Network (Ethernet) Protection No  PHYSICAL	Clamping voltage (RMS)	150V		
EMI / RFI filtering Up to 20dB  DATALINE SURGE SUPPRESSION  Telephone/DSL Protection No  Cable (Coax) Protection No  Network (Ethernet) Protection No  PHYSICAL		< 1 ns		
DATALINE SURGE SUPPRESSION  Telephone/DSL Protection No  Cable (Coax) Protection No  Network (Ethernet) Protection No  PHYSICAL	UL1499 let through rating	330V - UL Verified		
Telephone/DSL Protection No Cable (Coax) Protection No Network (Ethernet) Protection No PHYSICAL	EMI / RFI filtering	Up to 20dB		
Cable (Coax) Protection No  Network (Ethernet) Protection No  PHYSICAL	DATALINE SURGE SUPPRESSION			
Network (Ethernet) Protection No PHYSICAL	Telephone/DSL Protection	No		
PHYSICAL	Cable (Coax) Protection	No		
	Network (Ethernet) Protection	No		
Shipping weight (lbs) 2.5	PHYSICAL			
	Shipping weight (lbs)	2.5		
Shipping weight (kg) 1.1	Shipping weight (kg)	1.1		

Shipping Dimensions (HWD/in)	2.25 x 15 x 6	
Shipping Dimensions (HWD/cm)	5.7 x 38.1 x 15.2	
Unit weight (lbs)	1.8	
Unit weight (kg)	.8	
Unit Dimensions (HWD/in)	1.5 x 12.25 x 2.25	
Unit Dimensions (HWD/cm)	3.8 x 31.1 x 5.7	
Material of construction	Metal	
Form factors supported	Supports floor / wall / desktop placement	
Integrated keyhole mounting tabs	Keyhole slots enable mounting to a variety of surfaces	
Receptacle Color	Light Gray	
AC line cord color	Black	
Style	Strip	
CERTIFICATIONS		
Additional International Approvals	Complies with RoHS (Restriction of Hazardous Substances Directive)	
UL1449 1998 Rev. (AC Suppression)	UL1449	
UL1363 (Power Tap)	UL1363	
cUL / CSA (Canada)	cUL	
Approvals	Exceeds IEEE 587 category A&B specifications	
WARRANTY		
Product Warranty Period	Lifetime	
Connected Equipment Coverage	\$75,000	

More information, including related products, owner's manuals, and additional technical specifications, can be found online at www.tripplite.com/en/products/model.cfm?txtModelID=3305.

©2009 Tripp Lite. All Rights Reserved.

Free Manuals Download Website

http://myh66.com

http://usermanuals.us

http://www.somanuals.com

http://www.4manuals.cc

http://www.manual-lib.com

http://www.404manual.com

http://www.luxmanual.com

http://aubethermostatmanual.com

Golf course search by state

http://golfingnear.com

Email search by domain

http://emailbydomain.com

Auto manuals search

http://auto.somanuals.com

TV manuals search

http://tv.somanuals.com