



Tripp Lite
1111 West 35th Street
Chicago, IL 60609 USA
Telephone: +(773) 869 1234
E-mail: saleshelp@tripplite.com

Model #: TLP808TEL

Protect It! Surge Suppressor



Highlights

- 8 outlets / 8-ft. cord
- 2820 joule rating
- Modem/fax surge protection
- \$150,000 [Ultimate Lifetime Insurance](#) (USA, Puerto Rico & Canada only)

Description

Tripp Lite's TLP808TEL surge suppressor has 8 outlets, an 8-ft. cord with a space-saving right-angle plug, and diagnostic LEDs. The unit has a surge suppression rating of 2820 joules to handle the strongest surges. Built-in RJ11 jacks prevent surges from damaging your modem/fax/phone equipment. \$150,000 [Ultimate Lifetime Insurance](#) (USA, Puerto Rico & Canada only)

Applications

- Ideal for home computers and other important electrical equipment

Package Includes

- TLP808TEL
- 6-ft. telephone cord
- Instruction manual with warranty information

Features

- 8 outlets with integrated child safety covers
- 8-ft. cord with space-saving right-angle plug
- Built-in RJ11 jacks (1 in/2 out) prevent surges from damaging your modem/fax/phone equipment; 6-ft. telephone cord included
- Surge suppression rating: 2820 joules
- EMI/RFI noise filtering
- Can accommodate up to 3 transformers without blocking remaining outlets
- \$150,000 [Ultimate Lifetime Insurance](#) (USA, Puerto Rico & Canada only)
- Diagnostic LEDs indicate protection present & ground present
- Keyhole supports for wall mounting
- Lighted power switch
- Lifetime product warranty

Specifications

| OVERVIEW | |
|----------------------|-------------|
| Intended Application | Home/Office |

| SYSTEM OVERVIEW | |
|-----------------------------------|--|
| Voltage compatibility | 120 VAC |
| Frequency compatibility | 50/60 Hz |
| OUTPUT | |
| Output volt amp capacity (amps) | 15A |
| Output watts | 1800W |
| Outlet quantity / type | 8 NEMA 5-15R |
| Outlet orientation | Single row of 5, plus a second row of 3 for transformer accommodation |
| Outlet safety covers | Includes built-in sliding outlet safety covers |
| Transformer accommodation | Supports 3 large transformer plug accessories without covering remaining outlets, accepts up to 6 transformers total |
| INPUT | |
| Input connection type | NEMA 5-15P |
| Input cord gauge, type | 14 gauge, SJT |
| Input cord length (ft.) | 8 ft. |
| Input cord length (m) | 2.4 |
| Recommended Electrical Service | 120V (110-125V) |
| Input plug features | Space-saving right angle input plug |
| LEDS ALARMS & SWITCHES | |
| Diagnostic LEDs | Built-in LEDs confirm suppressor "protection present" (green) and "grounded" (red) status |
| Switches | Combination AC circuit breaker and 2-position red illuminated on/off power switch |
| SURGE / NOISE SUPPRESSION | |
| Protection modes | Includes full normal mode (H-N) and common mode (N-G / H-G) line surge suppression |
| AC suppression joule rating | 2820 joules |
| Clamping voltage (RMS) | 150V |
| AC suppression response time | < 1 ns |
| UL1499 let through rating | 330V - UL Verified |
| EMI / RFI filtering | Up to 40 dB |
| DATALINE SURGE SUPPRESSION | |
| Telephone/DSL Protection | Yes |
| Telephone/DSL Protection Details | 1 line |
| Cable (Coax) Protection | No |
| Network (Ethernet) Protection | No |
| PHYSICAL | |
| Shipping weight (lbs) | 2.2 |
| Shipping weight (kg) | 1.0 |
| Shipping Dimensions (HWD/in) | 2.5 x 14.75 x 8.75 |
| Shipping Dimensions (HWD/cm) | 6.4 x 37.5 x 22.2 |
| Unit weight (lbs) | 1.6 |

| | |
|--|---|
| Unit weight (kg) | 0.7 |
| Unit Dimensions (HWD/in) | 1.6 x 9.25 x 4.25 |
| Unit Dimensions (HWD/cm) | 4.1 x 23.5 x 10.8 |
| Material of construction | Plastic |
| Integrated keyhole mounting tabs | Keyhole mounting slots enable wall mounting |
| Receptacle Color | white |
| AC line cord color | white |
| Style | Strip |
| SPECIAL FEATURES | |
| Additional Information | Pair of phone line output jacks serve as a line splitter to enable the protection of two devices sharing a single dialup phone line |
| CERTIFICATIONS | |
| UL1449 1998 Rev. (AC Suppression) | UL1449 |
| UL1363 (Power Tap) | UL1363 |
| UL497A (Communications) | UL497A |
| FCC Part 68 (Communications) | FCC Part 68 |
| cUL / CSA (Canada) | cUL |
| Industry Canada (Communications) | Industry Canada |
| Approvals | Exceeds IEEE 587 category A&B specifications |
| WARRANTY | |
| Product Warranty Period | Lifetime |
| Connected Equipment Coverage | \$150,000 |

More information, including related products, owner's manuals, and additional technical specifications, can be found online at www.tripplite.com/en/products/model.cfm?txtModelID=141.

©2009 Tripp Lite. All Rights Reserved.

Free Manuals Download Website

<http://myh66.com>

<http://usermanuals.us>

<http://www.somanuals.com>

<http://www.4manuals.cc>

<http://www.manual-lib.com>

<http://www.404manual.com>

<http://www.luxmanual.com>

<http://aubethermostatmanual.com>

Golf course search by state

<http://golfingnear.com>

Email search by domain

<http://emailbydomain.com>

Auto manuals search

<http://auto.somanuals.com>

TV manuals search

<http://tv.somanuals.com>