

# Model #: N001-250-GY

# 250-ft. Gray Snagless Cat5e Molded Patch Cable



## **Highlights**

- Cabling for Category 5 (Cat5) and 5e (Cat5e) applications
- Length: 250-ft. Color: gray Connectors: RJ45 male
- Meets most current industry standards including IEEE 802.3ab, IEEE 802.5, ANSI/EIA/TIA 568, ISO/IEC 11801, and ETL (Category 5e, draft 11)
- Feature molded connectors with integral strain relief. Rated for 350 MHz/ 1 Gbps communication.
- Snagless boots protect the locking tabs on the RJ45 connectors from being damaged during installation
- Lifetime product warranty

# Description

Tripp Lite's 250-ft. gray snagless category 5e (Cat5e) patch cable has 2 snagless RJ45 molded male connectors featuring integral strain relief. The cable is manufactured from PVC 4-pair stranded UTP and is rated for 350MHz/1Gbps communication. All cables are offered in a variety of lengths and colors for all category 5 (Cat5) and 5e cabling needs. Standard category 5e patch cables are also available. Tripp Lite warrants this product to be free from defects in materials and workmanship for life.

System Requirements

• For 1000Base-T (1Gbps Ethernet), 10/100Base-T (Ethernet), 100 Mbps TPDDI, 155 Mbps ATM, ISDN, voice and Token Ring Type3 applications.

Package Includes

• 250Ft Gray Snagless Cat5e Patch Cable

#### **Features**

- Cabling for category 5 (Cat5) and 5e (Cat5e) applications
- Length: 250- Ft. Color: gray Connectors: RJ45 male
- Feature molded connectors with integral strain relief
- Snagless design protects the locking tabs on the RJ45 connectors from being damaged or snapped off during installation
- PVC 4-pair stranded UTP
- Rated for 350MHz/ 1Gbps communication
- Meets most current industry standards including IEEE 802.3ab, IEEE 802.5, ANSI/EIA/TIA 568, ISO/IEC 11801 and ETL (category 5e draft 11)
- Available in other colors and lengths
- Also available without the snagless feature (N002 series)
- Also available Cat6 cables (N201 series)
- Warranted to be free from defects in materials and workmanship for life

## **Specifications**

OVERVIEW

Intended Application	Computer Networking
PHYSICAL	
Color	Gray
Style	Cat5/5e
Length	250 ft.
CONNECTIONS	
Connector A	RJ45 (MALE)
Connector B	RJ45 (MALE)
CERTIFICATIONS	
Approvals	IEEE 802.3ab, IEEE 802.5, ANSI/EIA/TIA 568, ISO/IEC 11801, and ETL (Category 5e, draft 11)

#### **Related Items**

Patch Panels		
N001-050-BK	50-ft. Black Snagless Cat5e Molded Patch Cable	Qty: [optional]
N001-050-BL	50-ft. Blue Snagless Cat5e Molded Patch Cable	Qty: [optional]
N010-007-GY	7-ft. Gray Cat5e 350MHz Cross-over Molded Cable	Qty: [optional]
N022-01K-GY	1,000-ft. Gray Cat5e 350MHz Bulk Solid PVC Cable	Qty: [optional]
N032-001	Cat5e Straight Through Modular In-line Coupler	Qty: [optional]
N033-001	Straight Through Modular In-line Coupler	Qty: [optional]
N050-012	12-Port Cat5e Wall Mount Patch Panel 568B	Qty: [optional]
N052-012	12-Port Cat5e Patch Panel 568B	Qty: [optional]
N052-024	24-Port Cat5e Patch Panel 568B	Qty: [optional]
N052-048	48-Port Cat5e Patch Panel 568B	Qty: [optional]
N001-125-GY	125-ft. Gray Snagless Cat5e Molded Patch Cable	Qty: [optional]
N001-150-GY	150-ft. Gray Snagless Cat5e Molded Patch Cable	Qty: [optional]
Surge Protectors		
DNET1	Network Surge Suppressor - Essential protection for data and communication lines	Qty: [optional]

More information, including related products, owner's manuals, and additional technical specifications, can be found online at www.tripplite.com/en/products/model.cfm?txtModeIID=2494.

©2009 Tripp Lite. All Rights Reserved.

Free Manuals Download Website <u>http://myh66.com</u> <u>http://usermanuals.us</u> <u>http://www.somanuals.com</u> <u>http://www.4manuals.cc</u> <u>http://www.4manuals.cc</u> <u>http://www.4manuals.cc</u> <u>http://www.4manuals.com</u> <u>http://www.404manual.com</u> <u>http://www.luxmanual.com</u> <u>http://aubethermostatmanual.com</u> Golf course search by state

http://golfingnear.com Email search by domain

http://emailbydomain.com Auto manuals search

http://auto.somanuals.com TV manuals search

http://tv.somanuals.com