# QUICK START GUIDE













2000 Series • 115 V / 60 Hz



#### **WELCOME TO U-LINE**

Congratulations on your U-Line purchase. Your product comes from a company with over five decades and three generations of premium modular ice making, refrigeration, and wine preservation experience. U-Line continues to be the American leader, delivering versatility and flexibility for multiple applications including residential, light commercial, outdoor and marine use. U-Line's complete product collection includes modular Wine Captain<sup>®</sup> Models, Beverage Centers, Clear Ice Machines, Crescent Ice Makers, Glass & Solid Door Refrigerators, Refrigerator Drawers, Freezers, and Combo<sup>®</sup> Models.

U-Line has captivated those with an appreciation for the finer things with exceptional functionality, style, inspired innovations and attention to even the smallest details. We are known and respected for our unwavering dedication to product design, quality and selection. U-Line is headquartered in Milwaukee, Wisconsin with a west coast office located in Laguna Beach, California and European support in Dublin, Ireland. U-Line has shipped product to five continents for over two decades and is proud to have the opportunity to ship to you.

#### **PRODUCT INFORMATION**

Looking for additional information on your product? User Guides, Quick Reference Guides, CAD Drawings, Integrated Panel Instructions, Compliance Documentation and Product Warranty information are all available for reference and download at u-line.com under Documentation.

## PROPERTY DAMAGE / INJURY CONCERNS

In the unlikely event property damage or personal injury is suspected related to a U-Line product, please take the following steps:

- 1. U-Line Customer Care must be contacted immediately at +1.800.779.2547.
- 2. Service or repairs performed on the unit without prior written approval from U-Line is not permitted. If the unit has been altered or repaired in the field without prior written approval from U-Line, claims will not be eligible.

## **SERVICE INFORMATION**

Answers to Customer Frequently Asked Questions are available at u-line.com under Customer Care or you may contact our Customer Care group directly, contact information below.

# **GENERAL INQUIRIES**

U-Line Corporation 8900 N. 55th Street Milwaukee, Wisconsin 53223 USA Monday - Friday 8:00 am to 4:30 pm CST

T: +1.414.354.0300 F: +1.414.354.7905 Email: sales@u-line.com

u-line.com

### **SERVICE & PARTS ASSISTANCE**

Monday - Friday 8:00 am to 5:30 pm CST

T: +1.800.779.2547 F: +1.414.354.5696

Service Email: onlineservice@u-line.com Parts Email: onlineparts@u-line.com

### **CONNECT WITH US**



Designed, engineered and assembled in WI, USA

# QUICK START GUIDE



# Contents

- 1 Model List
- 3 Safety and Warning
- 3 Environmental Requirements
- 4 Door Swing
- 5 General Installation
- 6 Control Operation
- 7 First Use
- 8 Sabbath Mode
- 8 Warranty



# Model List

This guide provides the basics to get you started. Looking for more information? Visit u-line.com to view detailed User Guides for all U-Line products.



# Wine Captain® Models

U-2218WCS-00A	U-2224ZWCS-00A
U-2218WCS-01A	U-2224ZWCS-01A
U-2218WCINT-00A	U-2224ZWCS-13A
U-2218WCINT-01A	U-2224ZWCS-15A
	U-2224ZWCINT-00A
	U-2224ZWCINT-01A
	U-2224ZWCINT-60A
	U-2224ZWCINT-61A



### **Beverage Centers**

U-2224BEVS-00A

U-2224BEVS-01A

U-2224BEVS-13A

U-2224BEVS-15A

U-2224BEVINT-00A

U-2224BEVINT-01A

U-2224BEVINT-60A

U-2224BEVINT-61A





### **Glass Door Refrigerators**

U-2218RGLS-00A U-2224RGLS-00A
U-2218RGLS-01A U-2224RGLS-01A
U-2218RGLINT-00A U-2224RGLS-13A
U-2218RGLINT-01A U-2224RGLS-15A
U-2224RGLINT-00A

U-2224RGLINT-01A





U-2218RS-00A U-2224RS-00A U-2218RS-01A U-2224RS-01A U-2218RINT-00A U-2224RINT-00A U-2218RINT-01A U-2224RINT-01A



Visit http://www.u-line.com/product-literature/userguides or scan this QR code to view all user guides online.



# Safety and Warning

#### **NOTICE**

PLEASE READ all instructions before installing, operating, or servicing the appliance.

Use this appliance for its intended purpose only and follow these general precautions with those listed throughout this quide:

#### SAFETY ALERT DEFINITIONS

Throughout this guide are safety items labeled with a Danger, Warning or Caution based on the risk type:



Danger means that failure to follow this safety statement will result in severe personal injury or death.

# **▲ WARNING**

Warning means that failure to follow this safety statement could result in serious personal injury or death.

# **▲** CAUTION

Caution means that failure to follow this safety statement may result in minor or moderate personal injury, property or equipment damage.

# **▲** DANGER

This unit contains R600a (Isobutane) which is a flammable hydrocarbon. It is safe for regular use. Do not use sharp objects to expedite defrosting. Do not service without consulting the "R600a specifications" section included in the User Guide. Do not damage the refrigerant circuit.

# **▲** WARNING

Service must be done by factory authorized service personnel. Any parts shall be replaced with like components. Failure to comply could increase the risk of possible ignition due to incorrect parts or improper service.

# **Environmental Requirements**

This unit is designed to operate between 50°F (10°C) and 100°F (38°C). Higher ambient temperatures may reduce the unit's ability to reach low temperatures and/or reduce ice production on applicable models.

For best performance, keep the unit out of direct sunlight and away from heat generating equipment.

In climates where high humidity and dew points are present, condensation may appear on outside surfaces. This is considered normal. The condensation will evaporate when the humidity drops.



Damages caused by ambient temperatures of  $40^{\circ}F$  (5°C)




# **Door Swing**


Units have a zero clearance when installed adjacent to cabinets.

For Integrated models that are installed adjacent to a wall, 1/4" (6 mm) clearance is recommended from wall on hinge side to allow the door to open 90°. Allow for additional space for any knobs or pulls installed on the integrated panel/frame.

Stainless Steel models that are installed adjacent to a wall require 2-1/4" (57 mm) door clearance on hinge side to allow for door handle.



# Integrated







# General Installation

#### LEVELING INFORMATION

 Use a level to confirm the unit is level. Level should be placed along top edge and side edge as shown.



- 2. If the unit is not level, remove grille and adjust feet as necessary.
- 3. Confirm the unit is level after each adjustment and repeat the previous steps until the unit is level.



### **INSTALLATION TIP**

If the room floor is higher than the floor in the cut-out opening, adjust the rear feet to achieve a total unit rear height of 1/8" (3 mm) less than the opening's rear height. Shorten the unit height in the front by adjusting the front feet. This allows the unit to be gently tipped into the opening. Adjust the front feet to level the unit after it is correctly positioned in the opening.


#### **INSTALLATION**

- 1. Plug in the power cord.
- 2. Gently push the unit into position. Be careful to not entangle the power cord.
- 3. Re-check the leveling, from front to back and side to side. Make any necessary adjustments. The unit's top surface should be approximately 1/8" (3 mm) below the countertop.
- 4. Install the anti-tip bracket.
- 5. Remove the tape from the glass shelves and wipe out the inside of the unit with a clean, water-dampened cloth.



# **Control Operation**

# **ALL 2200 SERIES EXCEPT ZWC**




# **CONTROL FUNCTION GUIDE**

FUNCTION	COMMAND	DISPLAY/OPTIONS
ON/OFF	Press o and release	Unit will immediately turn ON or OFF.
Toggle lights	Press and release to leave interior light on for 3 hours	Glass door wine and beverage centers only.
Adjust temperature	Press △ or ▽ and release	When the "F" or "C" in the display is flashing, press or to adjust the set point temperature.
View temperature in unit	Press △ and ▽ together and release	The display will flash and then toggle from set point to temperature in unit.
Toggle between F/C	Hold △ and ♥ for five seconds	The display will change units.



### 2200 SERIES ZWC



### **CONTROL FUNCTION GUIDE**

FUNCTION	COMMAND	DISPLAY/OPTIONS
ON/OFF	Press o and release	Unit will immediately turn ON or OFF.
Toggle lights	Press 👸 and release	Leave interior light on for 3 hours.
Adjust temperature	Press or and release	The zone you are setting will have its light turned on (top zone first).
	Press or to adjust set point temperature	Display will show the set temperature.
	Press 🕲 to change zones	Light will switch from top zone to the bottom zone.
	Press or to adjust set point temperature	Display will show the set temperature.
	Press 🕲 to confirm and exit	
View temperature in unit	Press △ and ▽ together and release	The display will flash and then toggle from set point to temperature in unit. The temperature shown will correspond to the illuminated zone.
Toggle between F/C	Hold △ and ▽ for five seconds	The display will change units.

# First Use


All U-Line controls are preset at the factory. Initial startup requires no adjustments.

When plugged in, the unit will begin operating under the factory default settings. If the unit was turned off during installation, simply press  $\odot$  and the unit will immediately switch on. To turn the unit off, press  $\odot$ .

### **NOTICE**

U-Line recommends allowing the unit to run overnight before loading with product.





This unit is Star-K certified and offers a Sabbath mode. Sabbath mode disables system responses to user initiated activities and all external functions, including lighting, display and audible alarms. The unit will still maintain internal temperatures and set points. View a full list of Star-K certified U-Line units at www.star-k.org.

To enable Sabbath Mode:

- 1. Press (4) and hold for ten seconds and release (the °F/°C symbol will flash briefly at the end of the ten second period).
- 2. The interior light and control display (3) will go dark until user resets mode.
- 3. NOTE: Although the display will not be visible, the temperature controls in the unit remain active and preserve the interior temperature.

Sabbath Mode remains active until (4) is quickly pressed and released.

# Warranty

#### **U-LINE CORPORATION LIMITED WARRANTY**

- U-Line Corporation ("U-Line") warrants each U-Line product to be free from defects in materials and workmanship for a period of one year (two years on Modular 3000 Series) from the date of purchase.
   U-Line further warrants the sealed system (consisting of the compressor, condenser, evaporator, hot gas bypass valve, dryer, and connecting tube) in each U-Line product to be free from defects in materials and workmanship for a period of five years from the date of purchase.
- 2. During the initial one year warranty period (two years on Modular 3000 Series) for all U-Line products U-Line shall: (1) repair any product or replace any part of a product; and (2) for all Marine, RV and Domestic U-Line products sold and serviced in the United States (including Alaska and Hawaii) and Canada, U-Line shall be responsible for the labor costs performed by a U-Line authorized service company, incurred in connection with the replacement of any defective part. During years two through five of the warranty period for the sealed system, U-Line shall: (1) at U-Line's option repair or replace any part of the sealed system; and (2) for all Marine, RV and Domestic U-Line products sold and serviced in the United States (including Alaska and Hawaii) and Canada, U-Line shall be responsible for the labor costs incurred in connection with the replacement of any defective part of the sealed system. All other charges, including transportation charges for replacements under this warranty and labor costs not specifically covered by this warranty, shall be the responsibility of the purchaser. This warranty extends only to the original purchaser of the U-Line product. The Product Registration Card included with the product should be promptly completed by you and mailed back to U-Line or you can register on-line at www.u-lineservice.com.
- 3. The warranty listed above does not apply to floor display models. The warranty for these models shall be 30 days from the date of retail purchase and only if U-Line's Product Registration Card included with the

# QUICK START GUIDE



unit is completed and mailed back or electronically submitted to U-Line. This 30 day warranty does not apply to cosmetic damages. A proof of purchase may be required.

- 4. The following conditions are excluded from this limited warranty: use of cleaners other than the recommended stainless steel cleaners and U-Line Clear Ice Maker cleaner; installation charges; damages caused by disasters or acts of God, such as fire, floods, wind and lightning; damages incurred or resulting from shipping, improper installation, unauthorized modification, or misuse/abuse of the product; customer education calls; food loss and spoilage; door and water level adjustments (except during the first 30 days from the date of installation); defrosting the product; adjusting the controls; door reversal; and cleaning the condenser.
- 5. U-Line products are designed to operate in ambient temperatures between 50°F and 100°F unless otherwise noted in the product manual. Exposure to temperatures outside this range may cause degradation of performance and issues such as lower ice production or spoiled contents that are not covered under the terms of this warranty as a result of that exposure. U-Line product may not be subjected to temperatures below 40°F without following the winterization and vacation shutdown procedures in the user guide.
- 6. U-Line's Outdoor Limited Warranty, set forth in this Paragraph 6, shall apply to U-Line models deemed suitable for outdoor use by Underwriters Laboratory ("UL") as noted in the U-Line Product Catalog, U-Line's website and/or on the serial tag located inside the product.
  - A. Outdoor product may come into contact with rain by virtue of outdoor use. Exposure to other sources of water shall also cause this warranty to be void, including flooding of the area in proximity of the unit greater than 1/8" deep in water, hurricanes, splashing

- of pool water, or directing a spray from a hose or similar device into and around the unit.
- 7. If a product defect is discovered during the applicable warranty period, you must promptly notify either U-Line at 8900 N. 55th Street, Milwaukee, Wisconsin 53223 USA or at +1.800.779.2547 or the dealer from whom you purchased the product. In no event shall such notification be received later than 30 days after the expiration of the applicable warranty period. U-Line may require that defective parts be returned, at your expense, to U-Line's factory in Milwaukee, Wisconsin, for inspection. Any action by you for breach of warranty must be commenced within one year after the applicable warranty period.
- 8. THIS LIMITED WARRANTY IS IN LIEU OF ANY AND ALL OTHER WARRANTIES, EXPRESS OR IMPLIED, INCLUDING ANY IMPLIED WARRANTY OF MERCHANTABILITY OR IMPLIED WARRANTY OF FITNESS FOR A PARTICULAR PURPOSE, ALL OF WHICH ARE DISCLAIMED. U-Line's sole liability and your exclusive remedy under this warranty are set forth in the paragraphs above. U-Line shall have no liability whatsoever for any incidental, consequential or special damages arising from the sale, use or installation of the product or from any other cause whatsoever, whether based on warranty (express or implied) or otherwise based on contract, tort or any other theory of liability.

Some states do not allow limitations on how long an implied warranty lasts or the exclusion or limitation of incidental or consequential damages, so the above limitations may not apply to you. This warranty gives you specific legal rights, and you may also have other rights which vary from state to state.

Warranty 6/2014 Rev.G

Copyright © 2014 U-Line Corporation. All Rights Reserved. Publication Number 30424 8/2014 Rev.A

Free Manuals Download Website

http://myh66.com

http://usermanuals.us

http://www.somanuals.com

http://www.4manuals.cc

http://www.manual-lib.com

http://www.404manual.com

http://www.luxmanual.com

http://aubethermostatmanual.com

Golf course search by state

http://golfingnear.com

Email search by domain

http://emailbydomain.com

Auto manuals search

http://auto.somanuals.com

TV manuals search

http://tv.somanuals.com