

Micro-Switch/5

5 Port 10/100Base-TX Fast Ethernet Switch

PART NUMBER	DESCRIPTION
FEP-32005T-1	Palm-sized 5 Port 10/100Base-TX Fast Ethernet Switch

Specifications

Standard Compliance:

IEEE 802.3 10BASE-T Ethernet,
IEEE 802.3u 100BASE-TX Fast Ethernet
ANSI/IEEE standard 802.3 N-Way Auto-negotiation

Protocol:

CSMA/CD

Interface:

Five (5) RJ-45 Jacks with Auto MDI/MDIX crossover,

Max Forwarding Rate:

14,880 pps Ethernet port

Max Filtering Rate:

148,800 pps per Fast Ethernet port

Buffer Memory:

1MB

MAC Address Table:

1K-Entry

LED Indicators:

Per Port: LNK/ACT, FDX/COL
Per Unit: Power

Cable distance:

100m Max. with Category 3, 4, 5, 5e UTP for 10Base-T
100m Max. with Category 5/5e/6 UTP for 100Base-TX

Dimensions:

4.37" (L) x 2.77" (W) x 0.76" (H) / 111mm x 70mm x 19mm

Enclosure:

Metal

Operating Temperature:

0°C to 45°C (32°F to 113°F)

Operating Humidity:

10% to 90% (Non-condensing)

Power Supply:

External power adapter 9V DC / 700mA

EMI:

FCC Class B, CE Mark

Safety:

UL, cUL



908 Canada Court
City of Industry, CA 91748 U.S.A.

Phone: 626.964.7873 or 800.346.6668 Fax: 626.964.7880
www.unicomlink.com e-mail: info@unicomlink.com

©UNICOM 2007. UNICOM is a trademark of UNICOM Electric, Inc. All rights reserved.
Specifications subject to change without notice.

Micro-Switch/8

8 Port 10/100 Base-TX Fast Ethernet Switch

PART NUMBER	DESCRIPTION
FEP-32008T-1	Compact 8-Port 10/100Base-TX Fast Ethernet Switch

Specifications

Standard Compliance:

IEEE 802.3 10BASE-T Ethernet,
IEEE 802.3u 100BASE-TX Fast Ethernet
ANSI/IEEE standard 802.3 N-Way Auto-negotiation

Interface:

Eight (8) RJ-45 Jacks with Auto MDI/MDIX crossover

Switching Method:

Store-and-Forward

Forwarding Rate:

14,880pps for 10Mbps; 148,800pps for 100Mbps

Buffer Memory:

512KB DRAM

MAC Address Table:

2K-Entry

Cable Distance:

100m Max. with Category 3, 4, 5, 5e UTP for 10Base-T
100m Max. with Category 5, 5e, 6 UTP for 100Base-TX

LED Indicators:

Per Port: Link/Activity, Full Duplex/Collision
Per Unit: Power

Dimensions:

6.5" (L) x 3.93" (W) x 0.98"(H)
165mm x 100mm x 25mm

Operating Temperature:

0°C to 45°C (32°F to 113°F)

Operating Humidity:

10% to 90% (Non-condensing)

Power Supply:

External power adapter 9V DC / 700mA

Enclosure:

Metal

EMI:

FCC part 15 class A, CE Mark

Safety:

UL, cUL



908 Canada Court
City of Industry, CA 91748 U.S.A.

Phone: 626.964.7873 or 800.346.6668 Fax: 626.964.7880
www.unicomlink.com e-mail: info@unicomlink.com

©UNICOM 2007. UNICOM is a trademark of UNICOM Electric, Inc. All rights reserved.
Specifications subject to change without notice.

Micro-Switch/16 & 24

16 and 24 Port 10/100 Base-TX Fast Ethernet Switches

PART NUMBER	DESCRIPTION
FEP-32016T	16 Port 10/100Base-TX Desktop Fast Ethernet Switch
FEP-32024T	24 Port 10/100Base-TX Desktop Fast Ethernet Switch

Specifications

Standard Compliance:

IEEE 802.3 10Base-T Ethernet,
IEEE 802.3u 100Base-TX Fast Ethernet
IEEE802.3x Flow Control and Back-pressure
IEEE ANSI/IEEE802.3 N-Way Auto-negotiation

Interface:

Sixteen or twenty-four RJ-45 Jacks
with Auto MDI/MDIX crossover

Switching Method:

Store-and-Forward

Forwarding Rate:

14,880pps for 10Mbps; 148,800pps for 100Mbps

Buffer Memory:

1.25Mbits

MAC Address Table:

4K Mac address table

Back-plane:

4.8Gbps

Cable Distance:

10Base-T: 2-pair UTP/STP Cat. 3/5e/6 cable, EIA/TIA-568
100-ohm (up to 100m)
100Base-TX: 2-pair UTP/STP Cat. 5e/6 cable, EIA/TIA-568
100-ohm (up to 100m)

LED Indicators:

Per Port: Link/Activity; Per Unit: Power

Dimensions:

250mmx 133 mm x 37mm (L x W x H)
9.85" x 4.45" x1.46"

Operating Temperature:

0°C to 45°C (32°F to 113°F)

Operating Humidity:

10% to 90% (Non-condensing)

Power Supply:

Internal power supply, 100-240 VAC, 50~60Hz

EMI:

FCC Class A, CE

Safety:

CE/EN60950, UL, cUL



908 Canada Court
City of Industry, CA 91748 U.S.A.

Phone: 626.964.7873 or 800.346.6668 Fax: 626.964.7880
www.unicomlink.com e-mail: info@unicomlink.com

©UNICOM 2007. UNICOM is a trademark of UNICOM Electric, Inc. All rights reserved.
Specifications subject to change without notice.

Free Manuals Download Website

<http://myh66.com>

<http://usermanuals.us>

<http://www.somanuals.com>

<http://www.4manuals.cc>

<http://www.manual-lib.com>

<http://www.404manual.com>

<http://www.luxmanual.com>

<http://aubethermostatmanual.com>

Golf course search by state

<http://golfingnear.com>

Email search by domain

<http://emailbydomain.com>

Auto manuals search

<http://auto.somanuals.com>

TV manuals search

<http://tv.somanuals.com>