

SmartGST-2600M

24 Port 10/100Base-TX Managed Switch with two SFP (Mini) GBIC Slots

PART NUMBER	DESCRIPTION
GEP-63226T	24 port 10/100Base-TX Managed Switch with two SFP (Mini) GBIC Slots

Specifications

Standards:

IEEE802.3u 100BASE-TX
IEEE802.3z Gigabit fiber
IEEE802.3ab 1000Base-T
IEEE802.3x Flow control and Back pressure
IEEE802.3ad Port trunk with LACP
IEEE802.1d Spanning tree protocol
IEEE802.1w Rapid Spanning tree protocol
IEEE802.1p Class of service
IEEE802.1Q VLAN Tagging IEEE 802.1x user authentication
IEEE 802.1x User Authentication (Radius)
IEEE802.1ab LLDP

Interface:

RS-232 console: Female DB-9, Copper: 24 x RJ-45, Mini-GBIC: 2 x Mini-GBIC socket

Management Interface:

SNMP, Console, and Web management

Spanning Tree:

Insures only one path between any two nodes on network

IGMP, GVRP:

IGMP support to reduce IP multi-cast traffic for the multimedia applications, support for Group VLAN Resolution Protocol; Supports up to 256 Policy ACL (Access Control List)

Port Mirroring:

Global system supports 3 mirroring types:
"RX, TX, and Both packet"

Broadcast Storm Filtering:

Only allows a percentage of ports total bandwidth before broadcast traffic is dropped

Trunking:

Supports IEEE802.3ab LLDP with LACP function

Quality of Service:

Per port provides 4 priority queues:
Port Base, Tag Base and Type of Service Priority

LED Indicators:

24 Port 10/100TX: Link/Activity, 100Mbps, FDx/COL;
Mini GBIC: Link, Activity; Per Unit: Power

Operational Environment:

0°C to 45°C (32°F to 113°F), 5%~95%RH

Dimensions:

440 mm x 161 mm x 44 mm (L x W x H)

Power Supply:

Internal power 100~240 VAC, 50~60 Hz

EM and Safety:

FCC Class A, CE Mark, UL, cUL, CE/EN60950

Management Features:

- Web-based management
- SNMP network management
- Console and Telnet management
- IEEE 802.1q Port Base VLAN and VLAN Tagging
- IEEE 802.1d Spanning Tree
- IP Multi-cast, IGMP Snooping
- Class of Service
- Port Mirror, Broadcast Filter
- Static MAC Address
- Port Security and GVRP supported.



908 Canada Court
City of Industry, CA 91748 U.S.A.

Phone: 626.964.7873 or 800.346.6668 Fax: 626.964.7880
www.unicomlink.com e-mail: info@unicomlink.com

©UNICOM 2007. UNICOM is a trademark of UNICOM Electric, Inc. All rights reserved.
Specifications subject to change without notice.

Free Manuals Download Website

<http://myh66.com>

<http://usermanuals.us>

<http://www.somanuals.com>

<http://www.4manuals.cc>

<http://www.manual-lib.com>

<http://www.404manual.com>

<http://www.luxmanual.com>

<http://aubethermostatmanual.com>

Golf course search by state

<http://golfingnear.com>

Email search by domain

<http://emailbydomain.com>

Auto manuals search

<http://auto.somanuals.com>

TV manuals search

<http://tv.somanuals.com>