

ULTRA


Micro Fly X6-Series Cases

Micro Fly X6-Series, Micro ATX Case w/ 600 Watt XVS-Series

In the past, trying to find a compact case that is still versatile and truly dynamic was a daunting task. But that's all changed now that there's the Ultra Micro Fly! The Micro Fly can utilize any micro ATX motherboard, and because the Micro Fly is 1.5" deeper than similar cases, it can accept standard depth ATX power supplies and standard depth optical drives. Despite the Micro Fly's compact size, cooling is never a problem since the Micro Fly comes included with an 80MM fan in the front bringing cool air in, and a 120MM fan in the rear pulling hot air out. The Micro Fly also includes front USB, Firewire and Audio Outputs and is available with an optional, Ultra XVS-Series 600W power supply with custom length cables. Available in three designs: BX6, MX6, SX.



XVS Series 600-Watt Power Supply




Expansion Slots



Rear I/O Panel



5.25" Drive Bays



Rear 120mm Fan



Temperature Display



Front USB, Audio and FireWire

Removable Motherboard Tray

Specifications

- Models: BX6, MX6, SX6
- 5 Drive Bay:
 - 2 - External 5.25"
 - 1 - External 3.5"
 - 2 - Internal 3.5"
- Material: Aluminum
- Form Factor: Micro ATX
- Expansion Slots:
 - 4 Standard Slots
- Rear 120mm Fan
- Front 80mm Fan
- Dimensions:
 - Width: 11.25"
 - Height: 9"
 - Depth: 15"



BX6 Microfly Micro ATX Case

w/ 600 Watt Modular XVS PSU

Part #: ULT40035

UPC#: 022769400358

Dimensions: 15x11.25x9" Weight: 5 lbs.



MX6 Microfly Micro ATX Case

w/ 600 Watt Modular XVS PSU

Part #: ULT40037

UPC#: 022769400372

Dimensions: 15x11.25x9" Weight: 5 lbs.



SX6 Microfly Micro ATX Case

w/ 600 Watt Modular XVS PSU

Part #: ULT40036

UPC#: 022769400365

Dimensions: 15x11.25x9" Weight: 5 lbs.



600 Watt Modular XVS Power Supply



Connections:

- 1 - 20/24 Pin Motherboard Connector
- 1 - 4 Pin +12V Motherboard Connectors
- 1 - 6 Pin PCI-Express Connectors
- 1 - 5 Pin SATA Power Cable (2 Devices)
- 2 - 4 Pin Power Cable (2 Devices)
- 1 - 4 Pin Power Cable (2 Devices + 1 Floppy)

OUTPUT

Max Output Current	+3.3VDC	+5VDC	+12VDC	-12VDC	-5VDC	+5VSB
	26A	32A	35A	0.6A	0.6A	2.0A
Max Combined Wattage	180 W		420 W	3 W	7.2 W	10 W
	580 W			20 W		
600 W						

ULTRA

1-800-830-0051

www.ultraproducts.com

ULTRA

Free Manuals Download Website

<http://myh66.com>

<http://usermanuals.us>

<http://www.somanuals.com>

<http://www.4manuals.cc>

<http://www.manual-lib.com>

<http://www.404manual.com>

<http://www.luxmanual.com>

<http://aubethermostatmanual.com>

Golf course search by state

<http://golfingnear.com>

Email search by domain

<http://emailbydomain.com>

Auto manuals search

<http://auto.somanuals.com>

TV manuals search

<http://tv.somanuals.com>