

GMR2889-2CK

- 15 GMRS / 7 FRS Channels
- 142 Privacy Codes (CTCSS Tone and DCS Code)

 - Battery Charger

 - Group Scan
- Optional Headset Accessories

 - Emergency Weather Alert

18 Receive Indicator

20 Battery Level Indicator

19 Miss Indicator

21 VOX Indicator

22 Call Indicator

23 Charging Contacts



general mobile radio service

*Range may vary depending on environmental and/or topographical conditions

GMR2889-2CK RADIO

Up to 28 Mile Range*

Internal VOX Circuitry

Backlit LCD Display


Headset Jack

Roger Beep

143 Group Codes

Direct Call


Silent Mode



- 5 D-call Kev
- 6 Menu/Group Key
- 7 Speaker
- 8 Volume Setting Nob
- 9 Up/Down Button
- 10 Headset Jack 11 Channel Tone/Scan Kev
- 12 Monitor Kev

- Power Boost Button for
- Maximum Range All Call
 - Auto Channel Change Cal

 - Battery Level Meter
 - Channel Monitor
- Channel Scan
- 10 Selectable Call/Ring Tone Alerts
 - Keypad Lock
 - NÓÁA Emergency.
 - Weather Channels
 - DC IN 9V Jack



PACKAGE CONTENTS

Your package contains two radios, two rechargeable NiMH battery packs (#BT-1013), one AC adapter (#AD-314), one charging cradle (#RC1281), two belt clips and this reference guide. You can operate the unit using the rechargeable NiMH battery pack or 4 AAA alkaline batteries (not included). To order the following optional accessories, visit out web site @www.uniden.com or call 1-800-554-3988 durina business hours.

Use only Uniden accessories.

- NiMH Battery Pack #BT-1013
- Charging Cradle #RC1281
- VOX Headset #HS910/HS915/7A-133
- AC Adapter #AD-314
- DC Adapter #DC-1002

GMRS LICENSE

The radio operates on the General Mobile Radio Service (GMRS) frequencies when using Channels 1-7 and channels 15-22. You must have a GMRS license issued by the Federal Communications Commission to legally use these channels. For licensing information and application forms, visit the FCC online at: www.fcc.gov/wtb/uls or call the FCC hotline at 1 800-418-3676. If you have any questions, you can contact the FCC direct at 1-888-225-5322. No license is required for operation on channels 8-14 or operation on any channel in Canada.

INSTALL THE BATTERY

Your radio uses a supplied NiMH battery pack or 4 AAA alkaline batteries (not included)

To install the NiMH battery pack

- 1) Make sure the radio is off.
- 2) Remove the battery compartment door by pressing the tab at the bottom of the compartment door, and remove the cover.

- 3) Put the NiMH battery pack in the battery compartment applying the battery contacts to the lower charge contacts. Be sure to follow the instructions written on the battery pack's label. Installing the battery pack incorrectly will prevent the unit from operating.
- 4) Replace the battery compartment door.

USING THE RADIO BATTERY LEVEL AND LOW BATTERY ALERT

This radio has a battery level meter that indicates the status of the batteries. When the battery level is low. **BATT** appears and the battery level meter icon flashes. Recharge the NiMH battery pack immediately or, if you are using the alkaline batteries, replace the alkaline batteries in order to continue using the radio.

Warning! To avoid the risk of personal injury or property damage from fire or electrical shock, only use the Uniden accessories specifically designated for this product.

CHARGING THE RADIO

If you use the rechargeable NiMH battery pack, the radios can be charged directly or by using the supplied charging cradle.

Charge by Using the Radio

- 1) Connect the DC adapter's plug to the radios DC IN 9V jack and plug other end into your vehicle's accessory power outlet.
- 2) Charge the battery pack for 16 hours until the battery indicator stops flashing.

Using the Charging Cradle

- 1) Connect the adapter's plug to DC IN 9V jack of the charging cradle and plug the other end into an AC outlet. 2) Set the charging cradle on the desk or tabletop,
- and place the radio in the charging cradle with the keypad facing forward
- 3) Make sure that the LED illuminates. Charge the battery pack for 16 hours and remove the radio from the charging cradle after charging.

Other power cords could damage your radio.

approved DC adapter from Uniden.

• Use only the supplied battery and AC adapter or

Charge time may vary depending on the battery

life remaining.

 For charging batteries directly without the cradle. use only the #DC-1002 Cigarette Lighter Adapter code, available from WWW.Uniden.com.

- Do not recharge alkaline batteries. Doing so car create a safety hazard or damage the radio.
- For fastest charging, turn off the radio before charging.
- Batteries must be installed for operation. even from external power.
- If battery power is low, you cannot operate the radio even using external power. Let the batteries charge before using. If you try to transmit while power is low, the radio automatically turns off.

USING THE RADIO

In order to get the most out of your new radio, read this reference guide completely before attempting to operate the unit.

Turning the Radio On and Adjusting the Volume

- 1) Rotate *vol/off* clockwise until it clicks, and set
- volume to a comfortable listening level 2) To turn off the radio, rotate vol/off
- counterclockwise until it clicks.

Adjusting the Sound (Key Beeps)

Your radio sounds a beep each time you press a key (except for PTT and Power boost) To turn this sound off, press and hold *d-call* while turning on the radio. Repeat this step to turn the sound on.

Choosing a Channel

Your radio has 22 channels and 142 Privacy codes you can use to talk to others. In order to speak to someone, both your radios must be set to the same channel and Privacy code.

To choose a channel:

Press *ch tone/scn*, then press \blacktriangle or ∇ to increase or decrease the channel number displayed.

Note: Channels 1-7 and 15-22 have a typical range of up to 28 miles by pressing the **Power Boost** button. **HI** is displayed when you select a GMRS channel, and LO is displayed when you select a FRS channels.

Warning! The range of channels 1-7 and 15-22 can be boosted only when you use NiMH batteries. When you press Power boost while using alkaline batteries, the range is not boosted.

SETTING UP GROUP MODE

In order to use Group Mode you need to initialize a couple of settings in your radio:

- Set the radio to Group Mode
- Set a Group Code
 - Set a Ring Tone
 - Set a Unit Number
 - Set a "Nickname"

Setting the Radio to Group Mode

To set the radio to Group Mode, which enables Direct Call. Auto Channel Change and All Call, press and hold menu/grp for 2 seconds. The radio displays oF GRUP. Press A to display on GRUP. then press menu/grp to advance to setting the Group Code.

Note: In group mode, you cannot receive

Setting the Group Code

radio displays on GRUP.

other.

number

n RING

selected tone.

next section.

Setting the Unit Number

unique unit number. from 1-16

next section.

Setting the Ring Tone

transmissions from other radios unless they are

Set the group code for your radio group from 0-142.

also set to the same channel and group code.

Everyone in your group must select the same

group code in order to communicate with each

1) Press and hold menu/arp for 2 seconds. The

number). Press \blacktriangle or \checkmark to select the group

) Tap *menu/arp*. The radio displays Gnnn (n is a

3) Press **PTT** or **Power boost** to return to normal

This setting selects the tone you hear when

1) Press and hold *menu/arp* for 2 seconds, then

With each press, you hear a sample of the

Each radio in your group needs to be set to a

1) Press and hold *menu/grp* for 2 seconds, then

displays **n** - - - - (or your current nickname).

2) Press \blacktriangle or \checkmark to select the desired unit number.

tap *menu/grp* three times until the radio

tap menu/grp two times until the radio displays

someone places a direct call to you.

operation, or press *menu/grp* to continue to the

Setting Your Nickname

Your nickname appears on other units' displays when you make a All Call or direct call. This is also the name that appears on other radio displays when someone wants to make a direct call to you. When no nickname is set, the unit number appears.

- 1) Press and hold *menu/grp* for 2 seconds, then tap menu/arp four times until the radio displays **n** _ _ _ _ (or your current nickname) with the first place in the nickname flashing.
- 2) Press \blacktriangle or \checkmark to select the letter, then **ch** tone/scn to advance to the next letter until you have entered your nickname.
- 3) Press *menu/arp* to confirm the setting and exit the group settings menu.

Using Group Mode

Group mode lets you make direct calls to other people in your group without alerting the entire group and also lets you guickly change everyone in your group to another channel from a single radio. Before using group mode, follow the instructions in "Setting Up Group Mode" on every radio in your group. Then, to record the unit ID and everyone's nickname in every radio, send a call to "All" from each radio one time (see "Sending a Direct Call").

Sending a Direct Call

Direct Call lets you call everyone in your group at once, or call a single person in your group without anyone else in the group knowing. It is like a "speed dial" directly to the person(s) you want to talk to.

To call everyone in your group, press *d-call* in group mode. The radio flashes ALL. Then, press d-call again. Everyone in your group receives a call "chirp" for about 3 seconds. When the chirp ends, begin your conversation.

Note: When you make a direct call to "all," your radio also sends out your nickname or ID so that it will show up in the call list for everyone in your aroup.

 Press ▲ or ▼ to select the desired ring sound. To call one person in your group, without having other people know, press *d-call* in group mode. Then, use \blacktriangle or \checkmark to select the person you want to 3) Press PTT or Power boost to return to normal call and press *d-call* again. Your radio sounds operation, or press *menu/grp* to continue to the tones for 3 seconds as it sends the call. When the selected person answers, you can begin your conversation. You can silence the call tones at any time by pressing PTT or Power boost.

> Your conversation remains private between you and the person you called until 15 seconds after your last conversation. Then, your radio automatically exits private mode.

Automatically Changing Channels

Auto Channel Change lets you easily coordinate a channel change for everyone in your group. You might want to do this when you find you are getting a lot of interference on your current channel. Or, you can use this feature to change from a lowpower channel (8-14) to one of the high-powered channels (1-7, 15-22) if you need more range (or to a low-power channel if you need longer battery (alif

To start an auto channel change, on any radio in the group tap *ch tone/scn* twice. The current channel and CHCX appears. Use ▲ or ▼ to select the target channel. You can check whether the selected channel is clear. Then press *d-call*. Your radio chirps for about 10 seconds while it sends out the channel change signal. As each radio receives the channel change signal, it chirps once, then changes to the new channel.

To ensure all radios make it to the new channel. we recommend you:

- · Make sure you are in an open environment, where the radio will get the best range.
- Optimize range during the channel change signal by raising the radio over your head to give the best possible height.
- Do a "roll call" on the new channel after the move to be sure no one was left behind. If you missed someone, return to the previous channel and issue the signal again.

USING THE RADIO IN STANDARD MODE

Use the radio in standard (not group) mode when you need to be able to communicate with radios that do not have the group feature.

Choosing a Privacy Code

You can select a Privacy Code from 1-142 for each channel. oFF (OFF) indicates no Privacy code selected and your radio can receive a signal regardless of the code settings of the transmitting radio.

- 1) Press ch tone/scn twice. The Privacy code indicator flashes
- 2) Press \blacktriangle or \checkmark to increase or decrease the code. You can also select oFF. 3) Press ch tone/scn again.
- Note: Only tones 1-38 are standard across radio brands. Other settings might differ from brand to brand. See the specifications for the specific tones used for each setting.

Channel Scan Feature

Your radio has a channel scan feature that lets you easily scan all 22 channels. When an active channel is detected, the radio pauses on that channel until the channel is clear. Then after a 2second delay, the radio resumes scanning, Pressing PTT or Power boost while the scan is paused on a channel lets you transmit on that channel.

To turn on channel scan:

Press and hold *ch tone/scn* until SCAN appears. The channel number changes as the radio rapidly cycles through the channels.

To turn off channel scan:

Press d-call. PTT. Power boost. wx/alert o menu/grp, or press and hold ch tone/scn for 2 seconds

Talking on Your Radio

- To talk to others using the radio:
- 1) Press and hold **PTT** or **Power boost** and speak in a clear, normal voice about 2-3 inches away from the microphone. While you transmit. TXHI or **TXLO** appears on the display according to the type of channel. To avoid cutting off the first part of your transmission, pause slightly after pressing PTT or Power boost before you start talking.
-) When you finish speaking, release **PTT** or Power boost. You can now receive incoming calls. While receiving, rx appears on the display.

Note: When you press Power boost. BOOS appear on the display. The radio transmits at maximum power when a GMRS channel is selected. If Power boost is continuously pressed. 1 minute after you start pressing **Power boost** the transmission stops and vou hear a boost timeout error tone.

Monitor Mode Feature

Your radio lets you listen for weak signals on the current channel at the press of a key.

To turn on the Monitor Mode:

- For brief listening, press mon. MON appears and rx flashes.
- Press and hold mon for 2 seconds until two beeps sound for continuous listening. The receiver circuit stavs open, so you hear both the noise and weak signals.

To turn off Monitor Mode:

Press mon to return to the previous mode. MON and rx disappear.

Navigating through the Normal Menu

To access the advanced features of your radio has a Menu function.



-) To enter the menu, press menu/grp.
- Additional presses of *menu/qrp* advances you through the menu. After the last menu item, the radio exits to the previous mode.
- 3) Other ways to exit the Menu function are: a. Press PTT. Power boost. mon. d-call. wx/alert. or ch tone/scn.
- b. Wait 10 seconds until the radio automatically returns to the previous mode.

Voice Operated Transmission

Your radio has a user selectable Voice Operated Transmitter (VOX) that can be used for automatic voice transmissions. The VOX feature is designed to be used with a headset with a microphone. Transmission is starts when you speak into the microphone instead of pushing the PTT and Power boost button.

To select the VOX level:

) Enter the menu. VOX appears and the current setting flashes. The current level (OFF. 1-5) flashes, Level oF (OFF) disables VOX, while levels 1-5 set the sensitivity of the VOX circuit. Press either \blacktriangle or \checkmark to set the desired VOX sensitivity level. Use level 1 for increased sensitivity to voice in normally quiet environments, and use a higher level to reduce undesired activation in very noisy environments.

Transmitting a Call Tone

Your radio is equipped with 10 selectable call tones that are transmitted when you press *d-call* in standard mode.

- To select a call tone:
-) Enter the menu. Advance through the menu until **CALL** appears. The current call tone number (1-10) flashes.
- 2) Press \blacktriangle or \checkmark to increase or decrease the number to the desired call tone. Each tone will be heard through the speaker.

To transmit the selected call tone, press d-call. T selected tone is transmitted for a fixed length of time. Call Tone is cancelled if you press PTT or Power boost.

Setting Silent Mode

When you turn on the silent mode, all incoming calls are muted: the radio blinks the display backlight, the channel indicator, SLNT and call to alert you to an incoming call. If you do not respond to the call within 15 seconds, the backlight turns off, and the call will blink until there is no signal. Silent mode is disabled for 15 seconds when you transmit, receive, or press any other button.

- To set the silent mode:
-) Enter the menu. Advance through the menu until the SLNT appears. The current setting flashes. Press ▲ to display on SLNT.

Note: To prevent unwanted silent alerts, be sure to use a Privacv code or group code whenever vou use the Silent mode feature. You can hear the received voice when you turn on channel scan and an active channel is detected even durina silent mode.

Missed Call Alerts

If you receive an incoming call while silent mode is on and do not respond, the radio will turn on the Missed Call icon. If you are using the Group Mode. the radio will also indicate the person who made the call

Kev Lock

- To lock the keypad:
- 1) Enter the menu. Advance through the menu until LOCK appears. The radio displays oF LOCK.
- 2) To switch Key Lock from oF (OFF) to on (ON), nress 🔺
- 3) To confirm the setting, press menu/grp. The radio returns to the current mode

Note: If you exit the setting mode before confirming your selection by pressing menu/grp. Key Lock is set to oF (OFF).

- To unlock the keypad:
- Turn off the radio by rotating vol/of counterclockwise until it clicks.
- 2) Turn on the radio again by rotating vol/off clockwise until it clicks. The keypad is unlocked

Automatic Power Save Feature

Your radio has a unique circuit designed to dramatically extend the life of the batteries. If there is no transmission nor an incoming call within 3 seconds, your radio switches to the Power Save mode. The radio is still able to receive transmissions in this mode.

LCD Backlight

The LCD Backlight automatically turns on when any key (except the PTT and Power boost button) is pressed. The LCD remains lit for 10 seconds before turning off.

Downloadstrone hum Somethielsochen ext stempels Search And Download

Roger Beep

Roger beep is a beep that is sent to notify the end of transmission (both PTT and VOX transmission). You can hear the roger beep can be heard through the speaker when both roger beep and key beep are on. When roger beep is on and key beep is off, you do not hear the roger beep, but it is transmitted to your party.

To turn the roger beep OFF, press and hold **A** while turning ON the radio. Repeat this step to turn the beep ON.

USING THE WEATHER RADIO

Your radio can receive weather broadcasts from the NOAA National Weather Service. When in the Weather Radio Alert mode, the system functions as it does in standard mode but also monitors the selected weather channel for alerts when not communicating. While using the Weather Radio, you are not able to receive GMRS communications.

- 1) To turn on the Weather Radio Broadcast mode. press wx/alert. WX appears.
- Press ch tone/scn. then press ▲ or ▼ to increase or decrease the number to the desired Weather Channel.
- 3) To exit the Weather Radio Broadcast mode, press wx/alert. WX disappears.
- To change the channel continuously, press and hold \blacktriangle or \checkmark for more than 1 second.
- When in the Weather Radio Broadcast mode, you can only set the Key Lock from the Menu mode.

Choosing an Emergency/Weather Channel

There are 7 NOAA channel frequencies available and these frequencies are common between the US and Canada. You need to know what frequency is being transmitted in your location.

1) Press and hold wx/alert. alert appears.
2) When the unit receives a warning signal, it beeps
for 5 seconds. (alert) and channel indicator
hlink

- 3) To turn off Weather Alert, press and hold wx/alert. alert disappears.
- When Weather Alert is activated, the highest priority is given to this function. It checks the weather alert signals every 7 seconds. When the unit finds a warning signal, it switches to the warning receive mode automatically.
- Weather Alert is activated even if key beep is turned off.

NOAA Weather Radio Frequency List Channel 1 162.550 MHz Channel 5 162.450 MHz Channel 2 162.400 MHz Channel 6 162.500 MHz Channel 3 162.475 MHz Channel 7 162.525 MHz Channel 4 162.425 MHz

SPECI	FICATIONS				
Channels	15 GMRS/7 FRS/7 Weather	16	114.8		36
Sub Codes	38 Sub-Audible Tones	17	118.8		37
	104 DCS Codes	18	123.0		38
Operating Frequency		19	127.3		
GMRS/FRS:	462.5500 - 467.7125 MHz				
WX:	162.4000 - 162.5500 MHz				
Power Source	NiMH Battery Pack (BT-1013) or 4 AAA Alkaline Batteries	DCS	Code List		
Range Channel	1-7 up to 18 miles	Tone	Octal	Tone	Octal
-	(28 miles with Power boost	No.	Code	No.	Code
	button)	39	023	74	251
	Channel 8-14 up to 5 miles	40	025	75	261
	Channel 15-22 up to 18 miles	41	026	76	263
	(28 miles with Power boost	42	031	77	265
	button)	43	032	78	271
Battery Life	15 Hours typ NiMH	44	043	79	306
	Battery Pack (5/5/90 duty	45	040	80	311
	cucle)	46	051	81	315
		47	054	82	331
Frequency Chart		47	065	83	343
	Oh Fran [MUL-] Oraca Daf	-			
Ch. Freq. [MHz] Cross Ref. 1 462.5625 FRS & GM		49	071	84	346
2 462.5875 FRS & GM		50	072	85	351
3 462.6125 FRS & GM		51	073	86	364
4 462.6375 FRS & GM		52	074	87	365
5 462.6625 FRS & GM		53	114	88	371
6 462.6875 FRS & GM		54	115	89	411
7 462.7125 FRS & GM		55	116	90	412
8 467.5625 FRS 8	19 462.6500 GMRS 13	56	125	91	413
9 467.5875 FRS 9	20 462.6750 GMRS 10	57	131	92	423
10 467.6125 FRS 10	21 462.7000 GMRS 14	58	132	93	431
11 467.6375 FRS 11	22 462.7250 GMRS 15	59	134	94	432
		60	143	95	445
CTCSS Chart (Hz)		61	152	96	464
		62	155	97	465
Code Freq.	Code Freq.	63	156	98	466
oFF OFF	20 131.8	64	162	99	503
1 67.0	21 136.5	65	165	100	506
2 71.9	22 141.3	66	172	101	516
3 74.4	23 146.2	67	174	102	532
4 77.0	24 151.4	68	205	102	546
5 79.7	25 156.7	69	223	103	565
6 82.5 7 85.4	26 162.2 27 167.9	70	225	104	606
8 88.5	28 173.8	70	220	105	612
9 91.5	29 179.9	72	243 244	100	624
10 94.8	30 186.2	1			
11 97.4	31 192.8	73	245	108	627
12 100.0	32 203.5				
13 103.5	33 210.7				
14 107.2	34 218.1				
15 110.9	35 225.7				

233.6

241.8

250.3

Tone Octal

Code

631

632

654

662

664

703

712

723

731

732

734

743

754

036

053

122

145

212

225

246

252

255

266

274

325

332

356

446

452

454

455

462

523

526

No.

109

110

111

112

113

114

115

116

117

118

119

120

121

122

123

124

125

126

127

128

129

130

131

132

133

134

135

136

137

138

139

140

141

142

REGULATORY INFORMATION	RF EXPOSURE INFORMATION
 This device complies with Part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) This device may not cause harmful interference. (2) This device must accept any interference received, including interference that may cause undesired operation. Important: Changes or modifications to this unit not expressly approved by Uniden could void your authority to operate this unit. Your radio is set up to transmit a regulated signal on an assigned frequency. It is against the law to alter or adjust the settings inside the radio to exceed those limitations. Any adjustments to your radio must be made by quilified technicians. De be afe and sure Never open your radio's case. Your radio might cause TV or radio interference even when it is operating properly. To determine whether your radio is causing the interference, turn it off. If the interference goes away, your radio is causing it. Try to eliminate the interference, the FCC requires that you stop using the radio. Hazardous Environments: Do not operate the radio in hazardous environments. Explosion or fire may result. Do not operate the radio near unshielded electrical blasting caps. Under certain conditions, radios can interfere with blasting operations and may cause an explosion. Turn your radio OFF to prevent accidental transmission when in a blasting area or in areas posted: "Turn off two-way radio." Construction crews often use remote control RF devices to set off explosives. Care and Safety: To clean the radio, use a soft clot dampened with water. Do not use cleaners or solvents because they can harm the body of the unit angle ak inside, causing permanent damage. Use a dry, lint-free clot to clean the batteries immediately. Dry the battery compartment with a soft clot to minimize potential water damage. Leave the batteries immediately. 	 WARNING! Read this information before using the radio. In August 1996 the Federal Communications Commission (FCC) of the United States with its action in Report and Order FCC 96-326 adopted an updated safety standard for human exposure to radio frequency electromagnetic energy emitted by FCC regulated transmitters. Those guidelines are consistent with the safety standard previously set by both U.S. and international standards bodies. The design of the radio complies with the FCC guidelines and these international standards. Never allow children to operate the radio without adult supervision and the knowledge of the following guidelines. WARNING! It is up to the user to properly operate this radio transmitter to insure safe operation. Please adhere to the following: Use only the supplied or an approved antenna. Unauthorized antennas, modifications, or attachments could impair call quality, damage the radio, or result in violation of FCC regulations. Do not use the radio with a damaged antenna. If a damaged antenna comes into contact with the skin, a minor burn may result. Please contact your local dealer for a replacement antenna. Body-worn Operation This device was tested for typical body-worn operations using the supplied belt-clip. For hand-held operation, the radio should be held 1 inch from the user's face. The use of accessories that do not satisfy these requirements may not comply with FCC RF exposure requirements and should be avoided. For more information about RF exposure, please visit the FCC web site at www.fcc.gov.

set out below. this product.

ONE YEAR LIMITED WARRANTY

Important: Evidence of original purchase is required for warranty service. WARRANTOR: UNIDEN AMERICA

CORPORATION ("Uniden")

ELEMENTS OF WARRANTY: Uniden warrants, for one year, to the original retail owner, this Uniden Product to be free from defects in materials and craftsmanship with only the limitations or exclusions

WARRANTY DURATION: This warranty to the original user shall terminate and be of no further effect 12 months after the date of original retail sale. The warranty is invalid if the Product is: (A) damaged or not maintained as reasonable or necessary, (B) modified, altered, or used as part of any conversion kits, sub-assemblies, or any configurations not sold by Uniden, (C) improperly installed, (D) serviced or repaired by someone other than an authorized Uniden service center for a defect or malfunction covered by this warranty, (E) used in any conjunction with equipment or parts or as part of any system not manufactured by Uniden, or (F) installed or programmed by anyone other than as detailed by the owner's manual for

STATEMENT OF REMEDY: In the event that the product does not conform to this warranty at any time while this warranty is in effect, warrantor will either, at its option, repair or replace the defective unit and return it to you without charge for parts, service, or any other cost (except shipping and handling) incurred by warrantor or its representatives in connection with the performance of this warranty. Warrantor, at its option, may replace the unit with a new or refurbished unit. THE LIMITED WARRANTY SET FORTH ABOVE IS THE SOLE AND ENTIRE WARRANTY PERTAINING TO THE PRODUCT AND IS IN LIEU OF AND EXCLUDES ALL OTHER WARRANTIES OF ANY NATURE WHATSOEVER, WHETHER EXPRESS, IMPLIED OR ARISING BY OPERATION OF LAW, INCLUDING, BUT NOT LIMITED TO ANY IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE.THIS WARRANTY DOES NOT COVER OR PROVIDE FOR THE REIMBURSEMENT OVERPAYMENT OF INCIDENTAL OR CONSEQUENTIAL DAMAGES. Some states do not allow this exclusion or limitation of incidental or consequential damages so the above limitation or exclusion may not apply to you. LEGAL REMEDIES: This warranty gives you specific legal rights, and you may also have other rights which vary from state to state. This warranty

is void outside the United States of America and Canada.

PROCEDURE FOR OBTAINING PERFORMANCE OF WARRANTY: If, after following the instructions in the owner's manual you are certain that the Product is defective, pack the Product carefully (preferably in its original packaging). Disconnect the battery from the Product and separately secure the battery in its own separate packaging within the shipping carton. The Product should include all parts and accessories originally packaged with the Product. Include evidence of original purchase and a note describing the defect that has caused you to return it. The Product should be shipped freight prepaid, by traceable means, to warrantor at:

Uniden America Service 4700 Amon Carter Blvd, Fort Worth, TX 76155 (800) 297-1023 during regular business hours (CST) (See www.uniden.com for current hours of operation.)

Covered under one or more of the following U.S. patents:

5,203,015	5,214,789	5,491,745	5,497,508
5,517,677	5,557,606	5,574,994	5,610,946
5,613,201	5,625,870	5,627,876	5,628,059
5,634,196	5,634,205	5,678,176	5,697,096
5,717,312	5,722,070	5,787,345	5,901,341
6,021,326	6,084,861	6,163,691	6,195,415
6,353,730	6,618,015	6,839,550	6,980,770
7,102,568	7,138,945	7,200,358	7,251,453

IIniden

© 2008 Uniden America Corporation All rights reserved Printed in China UTZZ01038ZZ(0)

Free Manuals Download Website <u>http://myh66.com</u> <u>http://usermanuals.us</u> <u>http://www.somanuals.com</u> <u>http://www.4manuals.cc</u> <u>http://www.4manuals.cc</u> <u>http://www.4manuals.cc</u> <u>http://www.4manuals.com</u> <u>http://www.404manual.com</u> <u>http://www.luxmanual.com</u> <u>http://aubethermostatmanual.com</u> Golf course search by state

http://golfingnear.com Email search by domain

http://emailbydomain.com Auto manuals search

http://auto.somanuals.com TV manuals search

http://tv.somanuals.com