

**On-Premises
Washers & Dryers**

UniMac[®]

**Commercial Topload Washer
Commercial Frontload Washer
Commercial Stack Washer/Dryer
Commercial Dryer
Commercial Stack Dryer**



Expert Solutions from the Laundry Experts

Specifications

Washer	Topload UWT821	Frontload FTUA1
Width - in (mm)	25 5/8" (651)	26 7/8" (683)
Depth - in (mm)	28" (711)	28" (711)
Height - in (mm)	43" (1092)	41 3/8" (1054)
Height to Work Surface - in (mm)	36" (914)	41 3/8" (1054)
Operation	Manual Control	Manual Control
Basket Volume - cu. ft. (liters)	2.8 (79)	2.84 (80)
Spin Speed - RPM	High Speed 710 Low Speed 473	500, 650, 1000
Water Temperatures	Hot, Warm and Cold	Hot/Cold, Warm/Warm Warm/Cold, Cold/Cold
Cycles	Normal, Permanent Press or Delicate	Regular, Permanent Press, Delicate, Rinse and Spin or Spin
Cycle Time	16-31 minutes plus fill time	27 minutes plus fill time
Water Pressure - psi (bar)	Pressure fill 20 to 120 (1.4/8.3)	Pressure fill 20 to 120 (1.4/8.3)
Cycle Cue Lights	Yes	Yes
Top and Lid Finish	Porcelain	Porcelain
Color	White	White
Motor	2-speed, 1/2 HP reversing for 1725 or 1140 RPM	Multi-speed 3/4 HP
Electrical Specifications	120/60/1-15 amp	120/60/1-15 amp
Net Weight (Approx.) - lb (kg)	190 (86)	240 (109)
Dom. Shipping Weight (Approx.) - lb (kg)	210 (95)	260 (118)
Agency Approvals	UL	UL, cULus

Dryers	Single Rear Control UDE807 (Electric) UDG809 (Gas)	Single Front Control FEU17 (Electric) FGU17 (Gas)	Stack USE807 (Electric) USG809 (Gas)
Width - in (mm)	26 7/8" (683)	26 7/8" (683)	26 7/8" (683)
Depth - in (mm)	28" (711)	28" (711)	28" (711)
Height - in (mm)	43" (1092)	41 3/8" (1054)	76 5/8" (1946)
Height to Work Surface - in (mm)	36" (914)	41 3/8" (1054)	N/A
Cylinder Volume - cu. ft. (liters)	7.0 (198)	7.0 (198)	7.0 (198)
Color	White	White	White
Motor HP	60 Hz: 1/3 HP, 5.5 amp	60 Hz: 1/3 HP, 5.5 amp	60 Hz: 1/3 HP, 5.5 amp
Motor RPM	60 Hz: 1725	60 Hz: 1725	60 Hz: 1725
Btu Per Hour	25,000 (6,300 kcal)	25,000 (6,300 kcal)	25,000 (6,300 kcal)
Electrical Requirements	Gas: 120/60/1 - 15 amp Electric: 120/240/60/1 - 30 amp 120/208/60/1 - 30 amp	Gas: 120/60/1 - 15 amp Electric: 120/240/60/1 - 30 amp 120/208/60/1 - 30 amp	Gas: 120/60/1 - 15 amp Electric: 120/240/60/1 - 30 amp 120/208/60/1 - 30 amp
Heating Element (Electric)	60 Hz: 5350W, 240V Also 4750W, 208V	60 Hz: 5350W, 240V Also 4750W, 208V	60 Hz: 5350W, 240V Also 4750W, 208V
Type of Gas (Gas models only)	Factory-equipped for natural/mixed gas Convertible to LP gas*	Factory-equipped for natural/mixed gas Convertible to LP gas*	Factory-equipped for natural/mixed gas Convertible to LP gas*
Utility Connections - in (mm)	3/8" NPT (9.5)	3/8" NPT (9.5)	3/8" NPT (9.5)
Air Outlet Diameter - in (mm)	4" (102)	4" (102)	4" (102)
Exhaust Airflow**	220 (105 liters/sec.)	220 (105 liters/sec.)	220 (105 liters/sec.)
Net Weight (Approx.) - lb (kg)	Gas: 140 (64) Electric: 135 (61)	Gas: 155 (70) Electric: 150 (68)	Gas: 275 (125) Electric: 265 (120)
Dom. Shipping Weight (Approx.) - lb (kg)	Gas: 150 (68) Electric: 145 (66)	Gas: 165 (75) Electric: 160 (73)	Gas: 290 (132) Electric: 280 (127)
Agency Approvals	UL, CSA	UL, CSA	UL, CSA

Strong Limited Parts Warranty

UniMac proudly offers the following limited warranties on its topload washer:
Through Three Years* – any part on the entire machine.
Through Five Years* – the transmission assembly.
Through Lifetime* – the stainless steel washtub.

UniMac proudly offers the following limited warranties on its frontload washer:
Through One Year* – any part on the entire machine.

UniMac proudly offers the following limited warranty on its commercial dryer:
Through Three Years* – any part on the entire machine.

* Parts only, labor not included. See UniMac Warranty Bond for specifics.



Stack Washer/Dryer	LTUA7 (Electric) LTUA9 (Gas)
Width - in (mm)	26 7/8" (683)
Depth - in (mm)	28" (711)
Height - in (mm)	75 1/4" (1911)
Color	White
Net Weight (Approx.) - lb (kg)	Gas: 355 (161) Electric: 350 (159)
Dom. Shipping Weight (Approx.) - lb (kg)	Gas: 385 (175) Electric: 380 (172)
Agency Approvals	UL, CSA

* IMPORTANT: Any product revisions or conversions must be made by the Manufacturer's Authorized Dealers, Distributors, or local service personnel. Any approvals may vary depending on configuration. Consult factory for details.

** Measured at point of exit from dryer. Maximum exhaust static back pressure: 60 Hz: 0.6" W.C. Gas models are certified by CSA International; electric models are Underwriters Laboratories certified.

For the most accurate information the installation guide should be used for all design and construction purposes. Due to continuous product improvements, design and specifications are subject to change without notice. The quality management systems at all Alliance Laundry Systems manufacturing facilities have been registered as ISO 9001:2000 compliant. Features and certifications may vary by model.

© Copyright 2007 Alliance Laundry Systems LLC

Printed in the U.S.A.

Printed on paper manufactured with virgin pulp from certified sources and a minimum of 10% post-consumer recovered fiber.

www.uniwash.com

Alliance Laundry Systems
Shepard Street, Ripon, WI 54971 Telephone: 1-800-587-5458





Dryers

At UniMac, washers and dryers are considered more than just laundry equipment. They are key players in the success of on-premises laundry facilities and as such, must continuously achieve high levels of efficiency, quality and durability. UniMac always has maintained a standard of excellence in laundry equipment manufacturing that is recognized around the world. With over 60 years of engineering expertise, you can be assured that you are getting the best washers and dryers on the market that will meet your needs now and in the future.



Extra-Large 7.0 cu. ft. Capacity

UniMac's extra-large capacity drying cylinder needs very little space, yet easily handles sizeable wash loads. Smooth baffles tumble loads freely for maximum dry air movement.



Stack Washer/Dryers



Floor Space

By stacking the dryer on top of the washer, you gain a large amount of floor space. These ENERGY STAR® qualified units are the **ultimate space savers**. You can place laundry equipment in places that were never before possible.

The utility connections are identical to those used of residential style equipment. There is no extra work or floor space required.



Large Door Opening

For ease in loading and unloading, UniMac designed its dryer with a 2.06 sq. ft. door opening, one of the **largest in the industry**.



Front Serviceability

UniMac's two-piece front panel increases ease of service, which can **save time** and expense. Motor, blower, heating element, gas valve and thermostats can be serviced through the lower panel without disconnecting the door switch.

Frontload Washers



Utility Cost Savings

Utility costs are a big part of your laundry dollar. UniMac can help you reduce your costs with our efficient frontload washers.



The frontload washer is **ENERGY STAR® qualified** and excels in energy efficiency. The listing was earned by our washer's low usage of hot water, low motor energy consumption and high moisture removal. The washer's **super-high spin speed** reduces drying time and energy costs.

You could **save hundreds of dollars** per year on electricity, gas, water and sewer fees. These savings are due to **less hot water**, less overall water consumption and shorter drying times.

Saves Time

If you believe **time is money**, then you will be excited to experience how UniMac's frontload washers cut time from every wash and dry cycle. The super-high **spin speed of 1,000 RPM** removes much more water than topload washers. This greatly **reduces the drying time**. In fact, our tests show drying time is reduced as much as 30%!

Front Controls and Supply Dispenser

The unique front control design allows for **convenient storage** on top or the washer can easily fit under a counter. Add your detergent, bleach or softener with the automatic front mount supply dispenser, **walk away** and the washer will take care of the rest.



Liquid Supply Injector


Some installations may require a connection to an automated liquid supply system. There are two supply signals and two injection ports included within the washer.

Heavy-Duty See-Through Door

Loading and unloading are a breeze with UniMac's extra-wide 15 1/2" door, which boasts a 180° swing. A heavy-duty stainless steel hinge ensures the door will stand up to the rigors of the on-premises laundry. The see-through door also enables users to monitor the wash process.



Topload Washers



Rugged Suspension System

UniMac incorporates a liquid-filled balance ring at the top of the tub along with a seven-point suspension system to handle **bulky loads with ease**.

Front Serviceability

UniMac engineered its washer to easily handle large loads while occupying minimal floor space. Our **100% front serviceable** design eliminates the need for extra floor space around the unit, making it ideal for small or large laundry rooms. Simple removal of the front panel or control hood provides easy access to all major components from the installed position, which can save you time and money.



Durable Stainless Steel Tub

To keep linens looking their best longer, UniMac's washer features a stainless steel washtub that will actually become smoother with each use, so it won't pill, fray or snag fabric. In fact, stainless steel won't corrode, chip, crack or pit under normal use and it is extremely rust resistant. That's why we provide a **lifetime warranty**.



Agitator

For superior washability, UniMac's wavy vane agitator offers a 210° agitation stroke that delivers maximum side-to-side, top-to-bottom washing action to **get linens their cleanest**.



Free Manuals Download Website

<http://myh66.com>

<http://usermanuals.us>

<http://www.somanuals.com>

<http://www.4manuals.cc>

<http://www.manual-lib.com>

<http://www.404manual.com>

<http://www.luxmanual.com>

<http://aubethermostatmanual.com>

Golf course search by state

<http://golfingnear.com>

Email search by domain

<http://emailbydomain.com>

Auto manuals search

<http://auto.somanuals.com>

TV manuals search

<http://tv.somanuals.com>